

FLEECE-TAPE (Trade name)

TECHNICAL DATA - SELF ADHESIVE BUTYL FLEECE-TAPE

Description:	Butyl tape, with split and overlapping release liner. The fleece top layer allows good bonding to other substrates like plaster and various adhesives.
Material composition:	Carrier: Polypropylene Spunbond Coating: Self-adhesive butyl rubber, elastic and ageing resistant
Application:	Sealing Fleece Tape for elastic joint sealing. Suitable for wet room application according to humidity class A0 (i.e. Bathrooms), and for waterproofing applications, above and below ground. The Fleece-Tape can be used with cavity drain membranes, and in particular with Delta-PT meshed membrane where the fleece acts as a key when plastering.
Colour:	Grey
Width:	100 mm
Thickness:	approx. 0.91 mm
Weight:	approx. 78 g / m
Temperature resistance:	min. / max. - 5°C / + 60°C
Roll length:	20 m
Packaging:	1 Roll per Box

Technical properties: (ca.)	DIN	Value
Burst pressure: max.	Internal test	0.38 bar
Tensile MD	EN ISO 527-3	34 N / 15 mm
Tensile CD	EN ISO 527-3	25 N / 15 mm
Elongation MD	EN ISO 527-3	51 %
Elongation CD	EN ISO 527-3	78 %
Water tightness	EN 1928 B	0.23 bar
Peel test	Internal test	> 13 N / 20 mm

Certified according EN ISO 9001:

2013 Made in Germany

Storage: Material has to be stored at temperatures > 10 C°, dry and protected against direct sunlight. Material should be used latest 12 months after date of dispatch.

DELTA Membrane Systems Ltd.

Delta House, Merlin Way, North Weald, Epping, Essex, CM16 6HR.

Tel: 01992 523523 Fax: 01992 523250 Email: info@deltamembranes.com