



## Introduction

Hush F3 Adhesive is a water based rubber/resin flooring adhesive that has excellent wet grab with an early build up of strength. It is protected against bio-degradation and is suitable for use over normal underfloor heating installations.

Hush F3 Adhesive can be used for securing fibre bonded carpets, hessian, felt, secondary latex and rubber foam backed carpets and cork tiles up to 3.2mm thick.

Hush F3 Adhesive has been tested to the standards of the International Maritime Organisation and approved for use in marine floor installations.

Hush F3 Adhesive can be applied to smooth underlayments, structurally sound, smooth, dry subfloors of concrete and sand/cement screed, plywood, flooring grade chipboard and hardboard.

Waterproof surface membranes, sound flooring grade asphalt and some non-absorbent surfaces must be skimmed with a minimum of 3mm of the appropriate smoothing underlayment.

Hush F3 Adhesive can be applied directly to some non-absorbent subfloors such as Power Floated Concrete, Terrazzo and Granolithic, however, impervious backed floorcoverings should not be adhered directly to these subfloors and a suitable smoothing underlayment should be applied.

For details on other subfloors, contact our Technical Service Department.



**VIEW ON OUR WEBSITE**

## Standards

All aspects of the installation of floorcoverings should be in accordance with the requirements of the relevant British Standard Code of Practice i.e. BS 5325 (Installation of textile floorcoverings) and supplementary specifications.

## Technical Information

Colour	Cream /Yellow
Consistency	Viscous Liquid
Coverage Rate (Approx.)	3m <sup>2</sup> per litre using a 2mm x 6mm trowel
Open Time	Up to 15 minutes depending on temperature, humidity and absorbency of the subfloor

## Features

- High strength
- Good wet grab
- Suitable for the installation of most carpets
- Approved for marine use

## Packages

15 litre bucket

## How much material?

Pack Size	Trowel Size	Coverage per unit
15 litres	2mm x 6mm	45m <sup>2</sup>

Note: Coverage rates will depend on the condition and absorbency of the subfloor.

## HUSH ACOUSTICS

TEL: 0151 933 2026

EMAIL: [info@hushacoustics.co.uk](mailto:info@hushacoustics.co.uk)

[www.hushacoustics.co.uk](http://www.hushacoustics.co.uk)

[in](https://www.linkedin.com/company/hush-acoustics) hush-acoustics [@](https://www.instagram.com/hushacoustics) hushacoustics

[@](https://twitter.com/hushacoustics)hushacoustics [f](https://www.facebook.com/hushuk.acoustics) hushuk.acoustics

44 Canal Street, Bootle, Liverpool L20 8QU

Offices also based in London and Yorkshire



**HUSH ACOUSTICS**  
Sound Insulation Products and Systems