

RonaDeck Resin Bound Surfacing System

15 Year Guarantee

The RonaDeck Resin Bound Surfacing System is guaranteed for 15 years from date of installation against:

- General loss of stone
- Cracking
- Damage as a result of oil spillage
- UV Degradation
- Colour Change
- Frost Damage

Conditions

The guarantee is subject to:

1. Proper use of the complete RonaDeck Resin Bound Surfacing System including proof of purchase of the required amount resin and aggregate as manufactured by Ronacrete Ltd
2. Its installation to specification by a Ronacrete approved installation contractor
3. The proper care and maintenance of the RonaDeck Resin Bound Surfacing System as described in the Cleaning and Maintenance document for the RonaDeck Resin Bound Surfacing System
4. Payment for the system having been received in full by Ronacrete Ltd. Non-payment will result in the guarantee not being issued, or being withdrawn.
5. Written notification to Ronacrete Ltd of project address, installation date, installation contractor, copies of invoices for material and labour supply, description by contractor of substrate type and design, area in square metres, nature of use (e.g. domestic, other), weather during installation as issued by Meteorological Office

Exclusions and Limitations


1. Damage caused by forceful impact, improper use, inappropriate traffic, mechanical or chemical damage.
2. Reflective cracking from the base (e.g. concrete, tarmac).
3. Damage caused by movement created by growth of tree roots, wheel tracking, failure of substrate, slippage, heave.
4. Failure to install on to a suitable substrate such as structural concrete or wearing course tarmac or other approved suitable substrate.
5. Failure to install onto a free water-draining surface.
6. Colour change as a result of dirt retention or spillage/staining.
7. Use for any purpose or by any traffic other than that described for the product.
8. Damage not immediately reported to the installation contractor.
9. Our liability (except in the case of death or personal injury caused by us) under or in connection with this agreement, whether in contract, tort, negligence, breach of statutory duty or otherwise, shall not exceed the sum of materials supplied by Ronacrete Ltd for this contract.
10. We shall not be liable in contract, tort, negligence, breach of statutory duty or otherwise for any loss, damage, costs or expenses of any nature whatsoever incurred or suffered by you or any other party of an indirect or consequential nature including without limitation any economic loss or other loss of turnover, profits, business or goodwill.



Page 1 of a 4 page document

The information detailed in this leaflet is liable to modification from time to time in the light of experience and of normal product application, and before using, customers are advised to check with Ronacrete Ltd, quoting the reference number, that they possess the latest issue. Any person or company using the product without first making further enquiries as to the suitability of the product for the intended use does so at his own risk, and Ronacrete Ltd can accept no responsibility for the performance of the product, or for any loss or damage arising out of such use.

Ronacrete Ltd
Ronac House
Flex Meadow
Harlow
Essex CM19 5TD, U.K.
T: +44 (0) 1279 638 700
www.ronacrete.co.uk
support@ronacrete.co.uk



Cleaning and Maintenance Guide for RonaDeck Resin Bound Surfacing

The following has been prepared to allow you to protect and preserve your RonaDeck Resin Bound Surface.

Regular Cleaning

As with any surfacing material, RonaDeck Resin Bound Surfacing should be cleaned regularly and as frequently as necessary to maintain its appearance. Cleaning will also aid identification of any areas that require repair. Sweep with a broom to remove leaves, paper, etc. Use water as necessary to wash the surface.

Removing Moss and Algae

Remove any moss or algae on the surface with a proprietary moss removal solution. RonaDeck Resin Bound Surfacing Cleaner (FP) or diluted household bleach can be used to kill moss within the surface. If using bleach take care to avoid prolonged contact with aggregates such as limestone to avoid discolouring. Wash thoroughly with plenty of clean water afterwards, and abide by local regulations with regard to use of chemicals.

Chewing Gum Removal

Chewing gum can be removed by scraping or chipping or using proprietary local "spot" removal solutions, or by larger scale commercial cleaning. Take care not to dislodge aggregate.

Power Washing

If power washing the surface, the maximum pressure should not exceed 125 bar, use cold water only, a fan type jet, maintain at least 300mm between the lance and the surface and spray at such an angle to avoid dislodging the aggregate.

Removing Cement Stains

Cement stains can be removed using hydrochloric acid (follow health and safety guidance), and test first to ensure no surface damage or discolouration will occur.

Using The Surface

RonaDeck Resin Bound Surfacing is designed to be used by foot/pedestrian traffic and by light domestic vehicle traffic. Other Ronacrete systems are available for heavier traffic loads. Protect the surface from high impact loading, for example scaffolding, skips, pneumatic supports on skip lorries, and avoid dragging heavy loads across the surface. Protect the surface from liquids and other materials which may stain, soften or damage the surface, such as engine fluids, petrol, oil, diesel, paints, chewing gum, cement.

Localised Repairs

RonaDeck Resin Bound Surfacing can be repaired using the same combination of resin and aggregate as used during installation. Repairs should be carried out immediately they are required to avoid further damage and degradation.

Exclusions

Damage caused by forceful impact, improper use, inappropriate traffic, mechanical damage.
Reflective cracking from the base (e.g. concrete, tarmac).
Damage caused by movement created by growth of tree roots, wheel tracking, failure of substrate, slippage, heave.
Failure to install on to suitable substrate such as structural concrete or wearing course tarmac or other approved suitable substrate. Failure to install onto a free water-draining surface.
Colour change as a result of dirt retention or spillage/staining.
Use for any purpose or by any traffic other than that described for the product.



Page 2 of a 4 page document

The information detailed in this leaflet is liable to modification from time to time in the light of experience and of normal product application, and before using, customers are advised to check with Ronacrete Ltd, quoting the reference number, that they possess the latest issue. Any person or company using the product without first making further enquiries as to the suitability of the product for the intended use does so at his own risk, and Ronacrete Ltd can accept no responsibility for the performance of the product, or for any loss or damage arising out of such use.

Ronacrete Ltd
Ronac House
Flex Meadow
Harlow
Essex CM19 5TD, U.K.
T: +44 (0) 1279 638 700
www.ronacrete.co.uk
support@ronacrete.co.uk



RonaDeck Resin Bound Surfacing Agreement and Acceptance of Installation on Completion of Works

This document must be signed by the Client and the Installation Contractor within 4 weeks of completion of installation following which the guarantee will be issued, subject to inspection.

It was agreed by the Client and the Installation Contractor that the Ronacrete system has been satisfactorily applied and the client accepts definite and satisfactory completion of the works.

The Installation Contractor confirms that the Ronacrete system has been installed to specification and in accordance with the technical data sheets issued by the Company and any additional written instruction specific to the project.

Signed by Client _____

Name (print) _____

Date _____

Signed by Contractor _____

Name (print) _____

Date _____



Page 4 of a 4 page document

The information detailed in this leaflet is liable to modification from time to time in the light of experience and of normal product application, and before using, customers are advised to check with Ronacrete Ltd, quoting the reference number, that they possess the latest issue. Any person or company using the product without first making further enquiries as to the suitability of the product for the intended use does so at his own risk, and Ronacrete Ltd can accept no responsibility for the performance of the product, or for any loss or damage arising out of such use.

Ronacrete Ltd
Ronac House
Flex Meadow
Harlow
Essex CM19 5TD, U.K.
T: +44 (0) 1279 638 700
www.ronacrete.co.uk
support@ronacrete.co.uk