

ECOPHON AKUSTO[™] SCREEN

Ecophon Akusto[™] Screen has an exposed profile system. The size of the product is 1500 x 1200mm, thickness 40 mm. Available in Texona surface. Suitable for open space offices. Combined with a sound absorbing ceiling to achieve excellent acoustic properties in the room.



SYSTEM RANGE

| Size, mm | 1500x1200 | | | | | |
|--------------|-----------|--|--|--|--|--|
| Freestanding | • | | | | | |
| Thickness | 40 | | | | | |
| Inst. Diagr. | M564 | | | | | |




TYPE OF APPLICATION

• Office

ACOUSTIC

Sound Absorption

Sound absorption and sound attenuation test results according to ISO 20189.





| | тнк | Screen sound attenuation Δ Ls (dB) | | | | | Weighted screen sound attenuation (dB) | |
|-----------|-----|---|--------|--------|---------|---------|--|--|
| mm | mm | 125 Hz | 250 Hz | 500 Hz | 1000 Hz | 2000 Hz | 4000 Hz | Weighted screen sound attenuation (db) |
| 1500x1200 | 40 | 4.0 | 7.0 | 6.0 | 8.0 | 12.0 | 16.0 | 10.0 |



INDOOR AIR QUALITY

| Certificate / Label | | S AIR CO. | ÉMISSIONS DANS L'AIR INTÉRIEUR* |
|------------------------------|----------|--------------|---------------------------------|
| Eurofins Indoor Air Comfort* | IAC Gold | | (A+ |
| French VOC | A+ | SHIFTED PROB | |



CIRCULARITY

*this value does not take into account the aluminium frame

| Minimum post-consumer recycled content | 48%* |
|--|------------------|
| Recyclability | Fully recyclable |



HUMIDITY RESISTANCE

Class A, relative humidity 70% and 25°C, according to EN 13964:2014



VISUAL APPEARANCE

Texona in white has high light reflectance. For more information regarding visual appearance of the various surfaces: See Ecophon Colours and surfaces.



CLEANABILITY

Weekly dusting and vacuum cleaning.



USE OF DISINFECTANTS

Texona Ginger, Sea salt, Thyme, Oyster and Garlic withstand the frequent use of ethanol (70%)-based disinfectants. Dampen a soft polyester microfiber cloth with the solution and wipe the surface in gentle circular movements.



INSTALLATION

Installed according to the installation guide that is delivered with the product.




MECHANICAL PROPERTIES

The product is tested according to EN14073-2 and EN1023.

COLOURS AND DESIGN







Quantity specification (excl. wastage)

Size, mm 1500x1200

-

1 Akusto Screen

