



protective sealer

Temporary Protection prior to Grouting

DESCRIPTION

Water-based temporary protection for tiles.

Use for

- Temporary protective coating of most tile surfaces including ceramics, marble, mosaics, natural stone tiles, terracotta and terrazzo.
- May be used with all BAL grouting products.

PRODUCT INFORMATION

Composition: Water-based polymer emulsion.

Pack size: 2.5 litres

Key features: Protects surface against discolouration when using pigmented grouts. Sealer is removed by washing-off process after grouting.

USAGE & SERVICE CONDITIONS

Glazed ceramic tiles	✓
Unglazed ceramic tiles	✓
Mosaics	✓
Terrazzo	✓
Marble	✓
Polished porcelain	✓
Natural Stone (1)	✓
Terracotta (1)	✓

Usage: Coverage	
Typical Coverage ^	
10-14.8m ² /litre	

^ With 2-coat application

(1) Provided the surface is smooth.

SURFACE PREPARATION

Ensure tile surfaces are clean, dry, sound, and free from contamination.

APPLICATION/USAGE

Do NOT use in temperatures below 5°C or in damp conditions.

Usage procedure

Use undiluted, before grouting begins:

1. Apply BAL PROTECTIVE SEALER with clean, colour-fast lint-free cloth.
2. Rub well into tile surface, but avoid application to un-grouted joints.
3. Allow 15 minutes for sealer first coat to dry.
4. Apply a second coat.
5. Allow to dry for minimum 1 hour.
6. Apply BAL grout according to instructions on data sheet or packaging.
7. During washing-off process, sealer will be removed. Any residual sealer can be removed with clean water after grout has set.

HEALTH & SAFETY INFORMATION/ GOOD PRACTICE ADVICE

For detailed information and safety guidance, please refer to Product Material Safety Data Sheet [MSDS].

TECHNICAL ADVISORY SERVICE

For free expert guidance on use of this product, or any aspect of tiling, contact the BAL TECHNICAL ADVISORY AND SPECIFICATION SERVICE on
Tel: 01782 591120 or 0845 600 1 222 or Fax: 01782 591121.

POWERSPEC

A unique computerised online specification system for the design and installation of ceramic, mosaic and natural stone tiling. Visit www.powerspeconline.com

SHELF LIFE

12 months under normal dry conditions. Protect from frost and damp.

QUALITY AND ENVIRONMENTAL STANDARDS

Manufacturing quality assurance standards conform to BS EN ISO 9001. Satisfies the environmental management requirements and operational scope of ISO 14001.

25 YEAR GUARANTEE

All BAL products are supplied with a 25 year product guarantee to be free from manufacturing defects and to be fit for purpose. The guarantee covers materials replacement costs and labour.

This guarantee is subject to use of product in accordance with BAL's instructions and technical data, and good working practice. No liability can be accepted for any loss or damage arising from incorrect use of products or poor workmanship, over which BAL has no control.

Contact BAL Marketing Department for full details.

CONDITIONS OF SALE

Sold subject to the Company's Conditions of Sale.
Available on request.

For sales and technical queries, contact:

BUILDING ADHESIVES LTD

Longton Road, Trentham, Stoke-on-Trent, ST4 8JB, England
www.bal-adhesives.com

Sales

Tel: +44 (0) 1782 591160

Fax: +44 (0) 1782 591131

Technical

Tel: +44 (0) 1782 591120 or

+44 (0) 845 600 1 222

Fax: +44 (0) 1782 591121

Unit 622, Phase III

Northwest Business Park

Ballycoolin, Dublin 15, Ireland

Tel: +353 (0) 1 880 9210

Fax: +353 (0) 1 880 9211

NOTE: BAL reserves the right to update instructions, technical data and other information at any time without notice.

 **Powerspec**
www.powerspeconline.com



 **BAL**

Protective Sealer