



FMF system					
External width: 366mm Internal width: 300mm Length: 1000mm					
Channel reference	Height (mm)		Hydraulic section (cm ²)	Ø outlet	
	a	b		Vert.	Horiz.
F300MF000R	300	245	710	250	-
F300MF00R	390	335	975	250	-
F300MF10R	440	385	1100	250	-
F300MF20R	490	435	1240	250	-
F300MF60R	600	545	1550	-	-

Review: 2013-10

ULMA Architectural Solutions reserves the right to modify the specifications of any of its products without prior notice.

Information about the shown products is only indicative and is based on the existing technical features at the time of issuing.

In the event of any discrepancy in the translation of this document into different languages, the Spanish version will be used.

Latest version in www.ulmaarchitectural.com

PFor more details, see technical sheets and installation guide.

Description

ULMA polymer concrete linear drainage channel model F300MF.
Casted espheroidal graphite ductile iron edge with passivating and corrosion resistant effect.
8 point bolt-locked system per lm.
Load class up to F900, EN 1433 Standard.
Vertically and horizontally channel aligning tongue and groove joints.
CE Conformity Declaration and compliance with EN 1433 Standard.
External width 366 mm, internal width 300 mm and total length 1000 mm. Total external heights available between 300 mm and 600 mm. Installation possible with no slope or stepped fall.



ARCHITECTURAL SOLUTIONS



Tel.: +34 943 78 06 00
info@ulmaarchitectural.com
ulmaarchitectural.com