

RF SMOKE ALARM

BATTERY-OPERATED | MODEL 2106



CAVIUS 78MM SMOKE ALARM WITH RF CONNECTIVITY

Overview & Key Features

Battery-operated 78mm diameter optical smoke alarm in the Cavius family, with built-in RF connectivity. Can be interlinked with up to 31 other Cavius devices including RF smoke and heat alarms, Cavius relay and ancilliary devices.

- Grade F1
- 10-year sealed-in battery life – never needs replacing
- Designed for domestic use including motorhomes and caravans
- Dual insect screen to minimise nuisance alarms
- Wall and ceiling mounting options
- Quick and easy set-up and coding
- Certified to EN 14604:2005 + AC:2008
- 10-year manufacturer's warranty

Technical Specifications

General

| | |
|----------------------------------------|-----------------------------------|
| Order code: | CV2106 |
| Compatibility: | Cavius RF alarm family |
| Primary Power Source: | 10-year sealed-in lithium battery |
| Product & Battery Life: | 10-years |
| Low Battery Warning: | Yes |
| Sound Output: | 85 dB (A) at 3 metres |
| Alarm Frequency: | 869.675 MHz, max 20 mW |
| Wireless Range: | >100 m open field |
| Mounting Options: | Wall or ceiling |
| Number of interconnected units: | 32 |
| Operating Temperature Range: | +4°C to +38°C |
| Storage Temperature Range: | -20°C to +60°C |
| Humidity Range: | Up to 90% RH (non-condensing) |

Weights and Dimensions

| | |
|--------------------------------------------|-------------|
| Alarm Dimensions: | 78mm x 40mm |
| Alarm Weight (including batteries): | 105g |
| Case Quantity: | 10 units |

Warranty

10-year manufacturer's warranty