

reddot design award
winner

RF HEAT ALARM

MAINS-POWERED | MODEL 3202



CAVIUS 78MM HEAT ALARM WITH RF CONNECTIVITY

Overview & Key Features

Mains-powered 78mm diameter heat alarm in the Cavius family, with built-in RF connectivity. Can be interlinked with up to 31 other Cavius devices including RF smoke and heat alarms, Cavius relay and ancillary devices.

- Grade D1
- 230V mains-powered with 10-year back-up battery
- Designed for domestic use in homes and garages
- Wall and ceiling mounting options
- Quick and easy set-up and coding
- Certified to BS 5446-2:2003
- 10-year manufacturer's warranty

Technical Specifications

General

Order code:	CV3202
Compatibility:	Cavius RF alarm family
Primary Power Source:	230V Mains
Product & Battery Life:	10-years
Low Battery Warning:	Yes
Sound Output:	85 dB (A) at 3 metres
Alarm Frequency:	869.675 MHz, max 20 mW
Wireless Range:	>100 m open field
Mounting Options:	Wall or ceiling
Number of interconnected units:	32
Operating Temperature Range:	+4°C to +38°C
Storage Temperature Range:	-20°C to +60°C
Humidity Range:	Up to 90% RH (non-condensing)

Weights and Dimensions

Alarm Dimensions:	78mm x 50mm
Alarm Weight (including batteries):	131g
Case Quantity:	10 units

Warranty

10-year manufacturer's warranty