





## **CROWN CASEMENT**

## / FLUSH VENT SUITE

The Crown Flush Window Suite from Technal gives you the options to help make the right choices for both you and your customer. Building on the strengths of the existing Crown Window range, the new flush window offer is designed to address the key elements in any customer decision process and give you the best solution.

Windows with a consistent unbroken external appearance, have come to be known as 'Flush'. Associated with clean lines, flush windows have always been popular and have now a contemporary resonance with the discerning modern home owner.

The Technal Crown Flush Window suite brings the same clean lines in long lasting Aluminium. The Crown modular approach in engineering this window, is designed to deliver both aesthetic and performance options.

A significant investment in any home, the Crown Flush Suite gives greater flexibility in choosing the right windows and without compromise.

#### **EXTERNAL STYLE**

Externally Crown Flush windows offer two discreet styles.

- Traditional Flush: providing a uniform and consistent exterior face, incorporating the shaped mullion and transoms of the original flush window
- Slim Flush: Presenting on a single flat plane but without the mullion transom profile dividing the windows, reducing sightlines, and increasing light penetration

#### **INTERNAL TASTE**

Recognising that the Window appearance, from the inside is as important as the outside, we have multiple internal profile variations from which to choose.

- Softline: A traditional internal frame profile and vent beading
- Square: Simple square frame profile and vent headers presenting a more contemporary look

This option is enhanced by the abilty to offer stepped or internal flush framing.

#### **FUNCTIONALITY**

As an extension to the Crown window the Flush Vent is available in 75mm frame depths. Opening lights are hung on concealed, stainless steel variable geometry friction hinges.


The Espagnolette multi point locking system is constructed with stainless steel shoot rods, and zinc plated die cast keeps.

The window can accommodate Insulating glass units of 24mm and 28mm thickness.

# **FLEXIBILITY**


## / VERSATILE PROFILE OPTIONS

#### **EXTERNAL PROFILES**



#### TRADITIONAL MULLION

### INTERNAL PROFILE EXAMPLES



#### **EXTERNAL PROFILES**



TRADITIONAL FLUSH

• Transom/Mullion

CW338 CW336



**SLIM FLUSH** 

• Transom/Mullion

CW337 CW316

#### YOUR CHOICE

Mixing internal and external profile options within then the flush suite, lets you make the windows your own.

Adding to this finish and dual colour options allows you to create a distinct look and feel to suit your local market.

Traditional or contemporary the Crown window suite provides all the options.

#### INTERNAL PROFILE EXAMPLES



- Transom/Mullion
- Vent

CW316 CW340



- Transom/Mullion
- Vent

CW337 CW340





- Transom/Mullion
- Vent

CW316 CW341



- Vent
- Frame

CW340 CW346



- Vent
- Frame

CW340 CW334




- Vent
- Frame
- CW341 CW347

#### **COLOURS AND FINISHES**

The Crown Flush window is available in over 300 premium colours for you to choose from.

From neutral tones to metallic finishes, you can opt for the same colour throughout, or choose different colours for the inside and outside of your window and door frames to create the perfect, individual and stylish look.

Whatever your colour preference, you will enjoy the benefits of one of the most durable finishes available for windows and doors. The low maintenance of our window and door finish, means it will need only an occasional wipe down with soapy water to keep it looking as good as new.





### HARDWARE

Locking chrome handles are standard on the Crown Flush window range with other options available. The efficient espagnolette lock ensures smooth window operation and friction stays remove the need for hinges, that would break clean lines of the Flush window and allow for a safe opening of the window.

Traditional monkey tail ironmongery and matching dummy casement stays are also available to complete the traditional look as required.

#### **SECURITY**


The standard espagnolette locking mechanism with bespoke locking keeps, can be dealocked with the handle key.


The product is available compliant to PAS24 Secured by Design Standards





#### **VERSATILE INTEGRATED WINDOW**


The Crown Flush window can be used independently, but can also be combined using Universal frame coupler profiles with our other 75mm systems. Making the window compatible with Technal 75mm systems to create façades, screens or side lights.














# **SPECIFICATION**

# **PERFORMANCE**

Stay Size	8"	12"	16"
Max Width	436	636	736
Max Height	1336	1336	1336
Max Weight	18kg	22kg	24kg
Min Width	236	336	436
Min Height	386	386	386

	Air	Water	Wind
	Permeability	Tightness	Resistance
1	Class 3 (600 Pa)	Class 9A (600 Pa)	Class B5 (2000 Pa)*

As an extension to the Crown window range, the flush window suite meets part L building regulations and is WER rated.

\* Exposure category varies with Width/Height of window and mullion / transom used, as these are the only unsupported members. An accurate figure can be obtained using BS6399:Part 2 calculations and inertia values given in the product manual

Side Hung Casement - 8" Stay 18kg Max Weight - Min Height 386			
12mm Glazing Thickness		8mm Glazing Thickness	
Height	Width	Height	Width
1336	436	1336	436
1336	414	1336	414
1336	392	1336	392
1336	369	1336	369
1336	347	1336	347
1336	325	1336	325
1336	303	1336	303
1336	281	1336	281
1336	258	1336	258
1336	236	1336	236

Side Hung Casement - 12" Stay 22kg Max Weight - Min Height 386			
12mm Glazing Thickness		8mm Glazing Thickness	
Height	Width	Height	Width
1126	636	1336	636
1188	603	1336	603
1258	569	1336	569
1336	536	1336	536
1336	503	1336	503
1336	469	1336	469
1336	436	1336	436
1336	403	1336	403
1336	369	1336	369
1336	336	1336	336

Side Hung Casement - 16" Stay 24kg Max Weight - Min Height 386			
12mm Glazing Thickness		8mm Glazing Thickness	
Height	Width	Height	Width
1061	736	1336	736
1112	703	1336	703
1167	669	1336	669
1228	636	1336	636
1296	603	1336	603
1336	569	1336	569
1336	536	1336	536
1336	503	1336	503
1336	469	1336	469
1336	436	1336	436









## **IMAGINE WHAT'S NEXT**

Hydro Building Systems UK Ltd Severn Drive, Tewkesbury Gloucestershire. GL20 8SF Tel: 01684 853500 - www.technal.co.uk

