

The 780MBX is a mains powered ionisation smoke alarm with 9V alkaline battery back-up and a PUSH-FIT docking base system; designed to ensure quick and easy installation of base unit to the mains feed supply at installation stage (1st fix) and for quick and easy connection of alarm to base unit (2nd fix).



## Product features:

- 230V mains powered heat alarm
- 9V alkaline battery back-up
- PUSH-FIT docking base (DS700 included)
- Advanced Thermistor sensing technology
- Test button
- Low battery warning
- Multi-alarm interlink (up to 12 smoke and heat units)
- LED operating indicators
- Alarm source indicator
- 5 year guarantee
- BS 5446-PT2: 2003

<b>Model number</b>	780MBX (1 x 680MBX + 1 x DS700)
<b>Description</b>	230V heat alarm with alkaline battery bk-up
<b>Technology</b>	Advanced Thermistor
<b>Sensitivity</b>	N/A
<b>Alarm sound level</b>	85db at 3 metres
<b>Battery type</b>	9V PP3 Alkaline
<b>Operation AC/DC</b>	AC
<b>Installation positions</b>	Ceiling
<b>Operating temperature</b>	Alarm range 54°C to 70°C
<b>Operating humidity</b>	10% to 85% relative
<b>Storage temperature</b>	5°C (40°F) to 38°C (100°F)
<b>Storage humidity</b>	10% to 85% relative
<b>Guarantee</b>	5 years

<b>Unit dimensions</b>	Alarm = 127mm (D) x 60mm (H) Base = 140mm (D) x 33mm (H)
<b>Unit weight</b>	Alarm = 213g, Base = 91g
<b>Pack dimensions</b>	141mm (H) x 141mm (W) x 76mm (D)
<b>Pack weight</b>	315g
<b>Master pack quantity</b>	10
<b>Master pack dimensions</b>	TBC
<b>Master pack weight</b>	TBC
<b>Pack barcode</b>	5022391064930
<b>Outer barcode</b>	15022391064937
<b>Approvals</b>	BS 5446-PT2: 2003

Please note that specifications may be subject to change at any time.