

The 780MRL is a mains powered heat alarm with rechargeable lithium battery back-up and a PUSH-FIT docking base system; designed to ensure quick and easy installation of base unit to the mains feed supply at installation stage (1st fix) and for quick and easy connection of alarm to base unit (2nd fix).



Product features:

- 230V mains powered heat alarm
- Long life rechargeable lithium battery back-up
- PUSH-FIT docking base (DS700 included)
- Advanced Thermistor sensing technology
- Test button
- Low battery warning
- Multi-alarm interlink (up to 12 smoke & heat units)
- LED operating indicators
- Alarm source indicator
- 5 year guarantee
- BS 5446 - PT2: 2003

Model number	780MRL (1 x 680MRL + 1 x DS700)
Description	230V heat alarm with lithium battery bk-up
Technology	Advanced Thermistor
Sensitivity	N/A
Alarm sound level	85db at 3 metres
Battery type	Rechargeable lithium battery
Operation AC/DC	AC
Installation positions	Ceiling
Operating temperature	Alarm range 54°C to 70°C
Operating humidity	10% to 85% relative
Storage temperature	5°C (40°F) to 38°C (100°F)
Storage humidity	10% to 85% relative
Guarantee	5 years

Unit dimensions	Alarm = 127mm (D) x 60mm (H) Base = 140mm (D) x 33mm (H)
Unit weight	Alarm = 195g, Base = 91g
Pack dimensions	141mm (H) x 141mm (W) x 76mm (D)
Pack weight	295g
Master pack quantity	10
Master pack dimensions	TBC
Master pack weight	TBC
Pack barcode	5022391064947
Outer barcode	15022391064944
Approvals	BS 5446 - PT2: 2003

Please note that specifications may be subject to change at any time.