Model No: EDV-LR-BP



Overview

The Eau de Vie "LR model" is a slot-in cassette version of the free standing variants. It can be installed on existing shelving and sited remotely from the dispense tap or taps, affording more flexibility in confined spaces. The Large Remote comes complete with an integral filter to ensure great tasting water. The water filter reduces chlorine, odours, particles, bad taste and health contaminants.

The cooling chamber is hidden inside with filters external for easy maintenance and replacement.

The unit is designed to dispense directly into glasses or Eau De Vie bottles which are distinguishable as still or sparkling water due to the bottle cap design.

Features

- Compact and flexible
- Capable of supplying quality fresh filtered water
- Water is supplied chilled with the option of still and sparkling
- Easy access for changing filters
- Simple to install
- Optional UV filter that kills bacteria which may be in the mains water
- Cooling capacity of 150 litres per hour
- 80 litres continuous supply
- Standard dimensions 474(w) x 459(d) x 514(h)



Easy installation, connects to mains cold water supply and plugs into 2 x 13 amp sockets. Supplied with external water filters to provide premium quality tasting water.

The unit requires connection to a CO² cylinder which is housed externally and supplied by gas suppliers.

Benefits

- Free up valuable storage space
- Improved profits compared to bottled water
- Eco friendly
- Reduced environmental impact compared to transporting bottled water
- Reusable Eau De Vie branded bottles reduces waste disposal & recycling costs
- Provide added value to customers and employees
- Easy to operate by non skilled staff
- Hygienic and easy to keep clean
- A font for all occasions chilled fresh filtered still & sparkling water (remotely sited)


Accessories


- Racks specifically designed for bottle washing
- Six bottle carrier
- Rack transportation dollies
- Branded 750ml or 500ml glass bottles
- "Still" Silver bottle top
- "Sparkling" Gold bottle top

- Branded paper cups
- Branded paper cup dispenser
- Branded aluminium water flasks
- Filters
- Sanitizing spray bottles (6 x 750 ml)
- Bottle Seal "Still"
- Bottle Seal "Sparkling"

Model No: EDV-LR







Dimensions (CAD blocks available upon application (00 44 (0)1908 359 000)

Width
 Depth
 Height
 474 mm
 459 mm
 514 mm

Water Connection

Cold water mains potable supply
 3/4 BSP Isolator (3/4 BSP-3/8 Adaptor required)

Water Pressure Min 1.5 /Max 3.5 Bar

Excess spillage into drip tray (No drainage required)

Electrical Connection

Mains Supply
 Run Current
 Start Current
 Mains Supply
 230 V 1Ph 50 Hz Rated input 800 Watts
 2.6 Amps
 7.0 Amps

Fuse at 10 Amps
Supply Lead 2M Mains Cable 3 Pin UK Plug

Refrigeration Performance

• Ice bank weight 8 Kg Nominal

Maximum ambient temperature
 Refrigerant type/charge
 Natural Hydrocarbon R290

Refrigerant type/charge

Weight

Packed 50 kg Unpacked 40 kg

Operational 45 kg

Capacities based on incoming water temperatures

