



Air cooled  
multi-scroll  
heat pump,  
high efficiency,  
standard sound

EWYQ-G-XS



Scroll compressor

- › Single refrigerant circuit (2 scroll compressors) with single evaporator
- › Compact design to allow easy indoor installation or retrofit operations
- › Partial and total heat recovery option available
- › Stainless steel plate heat exchanger

# EWYQ-G-XS



Heating & Cooling				EWYQ-G-XS	075	085	100	110	120	140	160
Cooling capacity	Nom.			kW	77.8 (1)	88.1 (1)	101 (1)	117 (1)	127 (1)	147 (1)	165 (1)
Heating capacity	Nom.			kW	82.2 (2)	91.2 (2)	110 (2)	127 (2)	138 (2)	156 (2)	170 (2)
Power input	Cooling	Nom.			kW	27.0 (1)	31.5 (1)	36.0 (1)	39.5 (1)	44.7 (1)	50.2 (1)
	Heating	Nom.			kW	26 (2)	29 (2)	34 (2)	39 (2)	43 (2)	50 (2)
Capacity control	Method			Step							
	Minimum capacity			%	50	44	50	44	50	43	50
EER					2.88 (1)	2.80 (1)	2.81 (1)	2.97 (1)	2.84 (1)	2.92 (1)	2.85 (1)
ESEER					3.90	3.94	3.97	4.03	3.92	3.96	
COP					3.14 (2)	3.12 (2)	3.24 (2)	3.25 (2)	3.20 (2)	3.11 (2)	3.13 (2)
SCOP					3.25	3.20	3.46	3.42	3.39	3.33	3.35
IPLV					4.40	4.47	4.40	4.49	4.40	4.50	
Dimensions	Unit	Height	mm	1,800							
		Width	mm	1,195							
		Depth	mm	2,826		3,426			4,026		
Weight	Unit			kg	850	912	1,077	1,183	1,213	1,333	1,394
		Operation weight		kg	858	921	1,088	1,194	1,224	1,344	1,411
Water heat exchanger	Type			Brazen plate							
	Water flow rate	Cooling	Nom.	l/s	3.7	4.2	4.8	5.6	6.1	7.0	7.9
		Heating	Nom.	l/s	4.0	4.4	5.3	6.1	6.7	7.5	8.2
	Water pressure drop	Cooling	Nom.	kPa	8.40	8.30	8.70	11.6	13.7	18.2	19.9
		Heating	Nom.	kPa	9.50	9.10	11.20	14.40	17.20	21.70	22.50
Water volume				l	8.10	9.40	10.8			16.7	
Air heat exchanger	Type			High efficiency fin and tube type with integral subcooler							
Compressor	Type			Scroll compressor							
	Quantity			2							
Fan	Type			Direct propeller							
	Quantity			6		8			10		
	Air flow rate	Nom.	l/s	10,042		9,861		13,148		16,435	
	Speed			rpm							
Sound power level	Cooling	Nom.	dB(A)	84	85	87	1,360			89	
Sound pressure level	Cooling	Nom.	dB(A)	66	68	70				71	
Operation range	Air side	Cooling	Min.~Max.	°CDB	-10~45						
		Heating	Min.~Max.	°CDB	-10~45						
	Water side	Cooling	Min.~Max.	°CDB	-10~15						
		Heating	Min.~Max.	°CDB	-10~15						
Refrigerant	Type/GWP			R-410A/2,087.5							
	Circuits			Quantity							
Refrigerant charge	Per circuit			kg	15.0	18.0	23.0				30.0
				TCO <sub>2</sub> eq	31.3	37.6	48.0				62.6
Piping connections	Evaporator water inlet/outlet (OD)			2" 1/2							
Unit	Starting current	Max	A	210	261	267	316	323	363	377	
		Running current	Cooling	Nom.	A	52	56	60	69	76	88
			Max	A	66	72	78	87	95	111	125
Power supply	Phase/Frequency/Voltage			Hz/V							
				3~/50/400							

(1) Cooling: entering evaporator water temp. 12°C; leaving evaporator water temp. 7°C; ambient air temp. 35°C; full load operation. (2) Heating capacity, unit power input and COP are based on the following conditions: ambient 7°C; condenser 40.0/45.0°C, unit at full load operation | Equipment contains fluorinated greenhouse gases. Actual refrigerant charge depends on the final unit construction, details can be found on the unit labels.

For more information email [info@daikinapplied.uk](mailto:info@daikinapplied.uk) or visit [www.daikinapplied.uk](http://www.daikinapplied.uk)

**London Sales Office**  
69 Questor Estate  
Pearsons Way  
Dartford, Kent  
DA1 1JN  
01322 424950

**Head Office**  
Bassington Industrial Estate  
Cramlington, Northumberland  
NE23 8AF  
01670 566159



Daikin Europe N.V. participates in the Eurovent Certification programme for Liquid Chilling Packages (LCP), Air handling units (AHU), Fan coil units (FCU) and variable refrigerant flow systems (VRF) Check ongoing validity of certificate online: [www.eurovent-certification.com](http://www.eurovent-certification.com) or using: [www.certiflash.com](http://www.certiflash.com)

The present publication is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this publication to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this publication. All content is copyrighted by Daikin Europe N.V. Printed on non-chlorinated paper.

