

COMMERCIALLY ENGINEERED LVT FOR YOUR HOME.



EXPONA® LUXURY VINYL TILE COLLECTION

Introducing Expona Luxury Vinyl Tiles (LVT), designed to enhance home interiors, engineered to withstand the demands of commercial spaces.

Each of the twenty eight shades in this expertly curated flooring collection has been selected from the premium 'Expona Commercial' portfolio. With a superior variety of realistic designs and versatile formats, Expona flooring combines style and performance.

Explore infinite design floor possibilities with three standout timber shades, available in plank, parquet and ready to use Versailles tiles. These versatile designs work effortlessly as standalone floors or when laid together to create natural zones within your home.

This brochure will guide you step by step through the process of choosing your ideal Expona LVT floor. Browse inspirational home interiors, see your favourite flooring designs in your home using the Polyflor room visualiser and request free sampling to help your final selection.

PICTURE IT INSTANTLY IN YOUR HOME

polyflor.com/visualiser





DESIGN FLOOR SOLUTIONS



Three stunning oak designs available in ready to use design floor solutions. Effortless as standalone floors or striking when

laid together, the possibilities are endless.





STONE

P 28

A balanced palette of sophisticated organic designs and man-made materials, emulating the intricacies of natural stone and cement.

WOOD -

P12

Authentically replicating the detailed variation of natural timber, every shade has been carefully considered to provide a unique selection of wood designs.





DESIGN FLOOR SOLUTIONS

PARQUET 152.4 x 609.6mm

4123 Sherwood Oak Parquet

4128 Oiled Oak Parquet





4126 Everglade Oak Parquet

4101 Everglade Oak

PLANK 184.2 x 1219.2mm VERSAILLES

609.6 x 609.6mm



4099 Sherwood Oak



4124 Sherwood Oak Versailles



4098 Oiled Oak



4129 Oiled Oak Versailles





4127 Everglade Oak Versailles



\leftarrow Sherwood Oak \rightarrow



PARQUET 4123 **Sherwood Oak Parquet** 152.4 x 609.6mm



PLANK 4099 Sherwood Oak 184.2 x 1219.2mm



VERSAILLES 4124 Sherwood Oak Versailles 609.6 x 609.6mm 4099 **Sherwood Oak** 184.2 x 1219.2mm



Everglade Oak ightarrow

 \leftarrow Oiled Oak



PARQUET 4126 Everglade Oak Parquet 152.4 x 609.6mm





PLANK 4098 Oiled Oak 184.2 x 1219.2mm



VERSAILLES 4129 Oiled Oak Versailles 609.6 x 609.6mm



PLANK 4101 Everglade Oak 184.2 x 1219.2mm



VERSAILLES 4127 Everglade Oak Versailles 609.6 x 609.6mm







184.2 x 1219.2mm



4085 Light Classic Oak

4132 Una White Oak



4020 Grey Ash



4133 Wilder Oak



4022 Honey Ash

4079 Roasted Oak



203.2 x 1219.2mm



4081 Blond Limed Oak



4031 Natural Brushed Oak



4082 Grey Limed Oak



4083 Dark Limed Oak

184.2 x 1524mm



4134 Everest Oak




4058 French Vanilla Oak





4057 Saffron Oak



4114 Wild Orchard Oak












4031 **Natural Brushed Oak** 203.2 x 1219.2mm







4079 Roasted Oak 184.2 x 1219.2mm






4058 **French Vanilla Oak** 184.2 x 1524mm





4081 Blond Limed Oak 203.2 x 1219.2mm









4083 Dark Limed Oak 203.2 x 1219.2mm



304.8 x 914.4mm



5058 Dovestail Slate



5057 Urban Slate

STONE





5099 **Bister**



609.6 x 609.6mm



5067 Light Grey Concrete



5069 Dark Grey Concrete









5099 **Bister** 457.2 x 914.4mm









5058 Dovestail Slate 304.8 x 914.4mm

DESIGN YOUR IDEAL HOME



The first stage of designing an interior is refining your ideas and planning your finished look. You can find further information and resources on our website **polyflor.com**.



SELECT YOUR FLOOR

Browse our brochure and retail presenter at your leisure and make a shortlist of your favourite designs.

Our **room visualiser** is also available to help you picture any design instantly, in every room of your home **polyflor.com/visualiser**.



ORDER FREE SAMPLES

Free samples of each shade are available to order through our website **polyflor.com** or you can call the dedicated Polyflor Samples Hotline on **+44 (0)161 767 2551**.



DISCUSS YOUR PROJECT

It is always useful to be prepared when visiting your local flooring retailer. Start by providing a rough guide of the room shape and measurements. Be sure to bring your shortlist of chosen designs, including shade name and number.




ENJOY YOUR NEW FLOOR

We want you to enjoy your floor for years to come, so we have prepared a list of top tips to help you keep your floor looking as good as new, see page 38 for details.

FLOORCARE

We want your EXPONA floor to look its best for many years to come and to help you achieve this we have laid out the following floorcare guidelines. EXPONA does not harbour dust mites or bacteria, making it ideal for the home environment.



4129 Oiled Oak Versailles with 4098 Oiled Oak border

Initial cleaning after your new floor has been installed:

- Avoid walking on the floor for at least 24 hours following completion of installation
- Sweep or vacuum to prevent loose dirt or grit from scratching the floor
- Polishing your floor can be beneficial to help prevent slight surface scratches and to provide further protection

Day to day cleaning:

- Sweep or vacuum the floor to remove loose dirt, grit or dust
- Use clean mops and neutral cleaning solutions to regularly clean your floor Contact Polyflor for details of approved maintenance products
- Dilute the floor cleanser to the manufacturer's instructions
- Mop the floor evenly
- · Collect any excess liquid in a mop bucket
- Rinse the floor with clean water and allow to dry

Regular cleaning is more beneficial to the floorcovering and is more cost effective than occasional heavy cleaning.

Do:


- Install barrier mats at entrances to pick up grit and moisture
 - (Please note, some rubber-backed mats may discolour the floor)
- Ensure your furniture is fitted with protective pads where necessary to prevent scratches
- ✓ Use protective cups under heavy furniture to prevent indentation
- Remove spillages as quickly as possible to reduce risk of staining and causing slip hazards
- Always use clean equipment when maintaining your floor
- Regularly trim pets claws as these can cause fine scratches

Don't:


- X Use abrasive liquids or metal scouring pads as these can damage the floor
- 🔀 Clean the floor with solvents, caustic detergents, washing up liquids, soap powders, bleach, furniture polishes, petroleum based products, pine gels, stain removers or highly coloured products. Such products may make the floor slippery or cause permanent damage
- X Drag furniture with unprotected feet across the floor

We highly recommend you use the Polyflor floor care kit to maintain your Expona floor. You can find out more information and order your floor care kit from your Expona retailer.

PARQUET LAYING PATTERNS




FULL PLANK & TILE LAYING PATTERNS



LAYING PATTERNS

Herringbone tile




10 x 914mm









2512 Walnut



1011 Classic Oak & 2512 Walnut Cross Grain Marquetry Strip







FEATURE STRIPS

5 x 1000mm

5100 **Silver**

5103 **Black**

5110 **Brown**

2553 Walnut Marquetry Strip



5110 Brown Feature Strip

Product Sizes	Size	Shades	Quantity per Box	Coverage per Box	
	152.4 x 609.6mm	3	36	3.34m ²	
	152.4 x 1219.2mm	3	18	3.34m ²	
Plank	184.2 x 1219.2mm	6	15	3.37m ²	
	184.2 x 1524mm	4	12	3.37m ²	
	203.2 x 1219.2mm	4	14	3.46m ²	
	304.8 x 914.4mm	2	12	3.34m ²	
Tile	457.2 x 914.4mm	1	8	3.34m ²	
	609.6 x 609.6mm	5	9	3.34m ²	
Product Format	Standard	Result			
Gauge	ISO 24346 (EN 428)	2.5mm			
Wear Layer	ISO 24340 (EN 429)	0.55mm			
Total Weight	ISO 23997 (EN 430)	4290g/m ²			
Finish		PUR			
Performance Requirements	Standard	Result			
General Performance	ISO 10582 (EN 649) ASTM F1700	Conforms Class III Type A+B			
Jse Area	ISO 10874 (EN 685)	23, 33, 42			
Slip Resistance	EN 13893 DIN 51130/DIN EN 16165 App. B ASTM D2047 AS 4586	Class DS R10 >0.5 R10			
	For safety flooring with sustainable wet slip resistance, refer to the Polysafe ranges.				
Binder Content	ISO 10582	Туре I			
Abrasion Resistance	EN 649	Group T			
Reaction to Fire	EN 13501-1 ASTM E662 ASTM E648 CAN/ULC S102.2	Class BfI-S1 <450 Pass Class 1 FSV < 300; SDV < 500			
Static Electrical Propensity	EN 1815	≤2.0kV Classified as 'antistatic'			
Residual Indentation	ISO 24343-1 (EN 433) ASTM F970 ASTM F1914	≤0.05mm* ≤0.005″ @ 750psi ≤0.005″			
Castor Chair (continuous use)	ISO 4918 (EN 425)	Suitable			
Dimensional Stability	ISO 23999 (EN 434) ASTM F2199	≤0.10% max Pass			
Flexibility	ASTM F137	1" - Pass			
Underfloor Heating		Suitable, max 27°C			
Light Fastness	ISO 105-B02	(Method 3) >6			
Resistance to Light	ASTM F1515	ΔE ≤ 8.0 - Meets			
Resistance to Heat	ASTM F1514	ΔE ≤ 8.0 - Meets			
*Average test value from current production					

*Average test value from current production

Sustainability	Standard	Result	
BRE Green Guide		A+ ENP 429	
GreenTag	LCA Rate Gold Plus	GreenRate level A	
Specific EN 15804 EPD		Available	
Recyclable		100%	
Recycled Content		40%	
REACh		Compliant	
Indoor Air Comfort Gold		Eurofins certified product	
FloorScore		Certified	
Finnish M1		Certified	
AgBB/ABG		Pass	
Responsible Sourcing	BES 6001 SA 8000	Very good Approved factory	
Acoustic Performance	Standard	Result	
Impact Sound Reduction	ISO 10140-3 ASTM E90/492	2dB 55 STC	
Impact Insulation Class (IIC)	ASTM E90/492	IIC 36	
Maintenance Performance	Standard	Result	
Resistance to Chemicals	ISO 26987 (EN 423)	Good	

Maintenance Performance	Standard	Resul
Resistance to Chemicals	ISO 26987 (EN 423)	Good
Resistance to chemicals	ASTM F925	Good
Regular light maintenance is more cost-effective than pe	eriodic heavy maintenance and more beneficial to t	he floor covering.

UK CA B5 EN 14041 CE EN 14041 EN 14041 SES











REVÉTEMENTS DE SOL RÉSILIENTS DIPEC 3 3 2 2 728/348 http://evaluation.cstb.fr





43

EXPONA

80 wood and stone designs, available in a range of dimensions and design floor formats.







Not found exactly what you had in mind? Each of the twenty eight shades in this collection has been selected from the premium 'Expona Commercial' portfolio.

To discover even more options, view the full eighty shade Expona Commercial range in the wood and stone presenters or visit **Polyflor.com**.

PICTURE IT INSTANTLY



SUSTAINABILITY

As a leading global manufacturer of high-quality, high-performance sustainable floor coverings, Polyflor has demonstrated a high level of commitment to minimising environmental impact. This meets the company's values, but also complies with ongoing objectives for ISO 14001 Environmental Management System and BES 6001 Responsible Sourcing accreditation.

Expona Commercial is 100% recyclable, whilst also containing 40% recycled material. It contains 76% natural material and is also phthalate free.

Not only do we look to minimise our carbon footprint, but yours too. Expona Commercial is extremely durable with its 0.55mm wear layer and PUR finish. Easily cleaned with fewer chemicals, less water, and less energy, it is also non-shedding and does not harbour dust; important for clean air quality.

Further to this, Expona Commercial achieves Indoor Air Comfort Gold and FloorScore certification for exceptionally low VOC emissions, providing indoor air quality and comfort.

For more information on our sustainability credentials, go to polyflor.com

15 YEAR RESIDENTIAL GUARANTEE

The Expona Luxury Vinyl Tile collection has been developed to meet the highest technical specification of its type. Ideal for all areas of the home, the products ensure high performance and optimum style. Compared with many natural flooring options, Expona Luxury Vinyl Tiles will resist household stains under normal conditions and will not crack, chip or splinter. All products purchased from the range are guaranteed in residential home installations against normal wear and tear in the recommended environment, provided that they have been fitted correctly and maintained in accordance with the manufacturer's instructions. In order to make a claim, customers must apply in writing indicating where the flooring was purchased and provide satisfactory proof of purchase.


This guarantee only applies in the event of visible wearing out of the decorative pattern on the surface, providing the flooring has been subject to normal usage in the recommended environment. It does not cover general misuse. Full terms and conditions of the guarantee are available on request from your flooring wholesaler or Polyflor Ltd.



TRY IT NOW



ORDER FREE SAMPLES



CONTACT US

polyflor.com and follow the links to the technical pages, +44 (0) 161 767 1912 / tech@polyflor.com

POLYFLOR[™] INTERNATIONAL

Australia Polyflor Australia Tel: 1800 777 425 E-mail: sales@polyflor.com.au

Canada Polyflor Canada Inc. Tel: +1 905 364 3000 E-mail: sales@polyflor.ca

China Polyflor Hong Kong O/B Polyflor Ltd. Tel: +(852) 2865 0101 E-mail: info@polyflor.com.hk

Colombia Polyflor Ltd. (LATAM Office) Tel: +57 (601) 7431965 E-mail: info@polyflor.com

France James Halstead France SAS Tel: +33 (0)8 20 20 32 11 E-mail: info@jhfrance.fr

Germany objectflor Art und Design Belags GmbH Tel: +49 (0) 2236 966 330 E-mail: info@objectflor.de

India Polyflor India Pvt Ltd. Tel: +91 22 4023 2485 E-mail: info@polyflor.co.in

Ireland Polyflor Ireland Tel: +353 (1) 864 9304 E-mail: salesireland@polyflor.com

Malaysia Polyflor Martex Tel: 1300 80 7788 E-mail: sales@polyflor.com.my Middle East Polyflor FZE Tel: +971 50 406 8114 E-mail: aelwakil@polyflorfze.ae

New Zealand Polyflor New Zealand Ltd. Tel: 0800 765 935 Tel: +64 9 269 1111 E-mail: sales@polyflor.co.nz

Norway Polyflor Nordic Tel: +47 23 00 84 00 E-mail: firmapost@polyflor.no

Poland Polflor Sp. Z.o.o Tel: +48 (0) 61 820 3155 E-mail: polyflor@polflor.com.pl

South Africa Poly Sales Africa (Pty.) Ltd. Tel: +27 (0) 11 609 3500 E-mail: info@polyflor.co.za

Spain Polyflor Ltd. Tel: +34 619 949 054 E-mail: info@polyflor.com

Sweden FalckDesign AB Tel: +46 (0) 300 15820 E-mail: info@falckdesign.com

POLYFLOR[™] UK

Polyflor Ltd. PO Box 3, Radcliffe New Road, Whitefield, Manchester, M45 7NR

Tel: +44 (0) 161 767 1111 E-mail: info@polyflor.co

www.polyflor.com

<u>Hames</u>Halitead[™] FLOORING