

Ecophon Industry™ Modus

A function ceiling suitable for noise reduction in industry premises, where different sizes and installation methods are required. Ecophon Industry Modus can be installed in exposed grid systems or with screw and washer.

The system consists of Ecophon Industry Modus tiles and Ecophon Connect grid systems, with an approximate weight of 3-5 kg/m² depending on thickness. The tiles are manufactured from high density glass wool. The visible surface is a batch painted glass tissue (S) and the back of the tile is covered with glass tissue. The edges are natural.


For best performance and system quality, use Ecophon Connect grid and accessories. The grid is manufactured from galvanized steel.

(Ecophon Industry Modus is a function ceiling system any smaller aesthetical deviations between the tiles may occur. These deviations do not have any impact on the functionality of the system).




Sweden


SYSTEM RANGE



Size, mm	1200x600	1200x1200	1200x1200
Direct	•	•	•
T24	•	•	•
Thickness	50	50	100
Inst. Diagr.	M22, M23, M44, M444	M22, M23, M44, M444	M22, M23, M44, M444




Industry Modus tile.



Section of Industry Modus system.



Section of Industry Modus TAL system.



Section of Industry Modus S system.




Acoustic

Sound Absorption:

Test results according to EN ISO 354. Classification according to EN ISO 11654.

α_p , Practical sound absorption coefficient



- Industry Modus S 50 mm, 50 mm o.d.s.
- Industry Modus S 50 mm, 200 mm o.d.s.
- Industry Modus S 100 mm, 100 mm o.d.s.
- - - Industry Modus S 100 mm, 200 mm o.d.s.

THK mm	o.d.s. mm	α_p , Practical sound absorption coefficient						α_w	Sound absorption class
		125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz		
50	50	0.20	0.65	0.95	0.95	1.00	1.00	0.95	A
50	200	0.45	0.95	1.00	0.95	1.00	1.00	1.00	A
100	100	0.55	1.00	1.00	1.00	1.00	1.00	1.00	A
100	200	0.75	1.00	1.00	1.00	1.00	1.00	1.00	A

THK mm	o.d.s. mm	NRC	SAA
100	100	1.10	1.07
100	200	1.10	1.07
100	400	1.05	1.03



Indoor Air Quality

Certificate / Label	
Eurofins Indoor Air Comfort®	IAC
French VOC	A
Finnish M1	•



Environmental Footprint

Kg CO ₂ equiv/m ²	
Industry Modus S 50mm	1,39 (Industry family EPD in conformity with ISO 14025 / EN 15804)
Industry Modus S 100mm	2,46 (Industry EPD in conformity with ISO 14025 / EN 15804)



Circularity

Minimum post-consumer recycled content (50 mm)	60%
Minimum post-consumer recycled content (100 mm)	63%
Recyclability	Fully recyclable



Fire safety

Country	Standard	Class	The glass wool core of the tiles is tested and classified as non-combustible according to EN ISO 1182.
Europe	EN 13501-1	A2-s1,d0	



Humidity Resistance

Class C, relative humidity 95% and 30°C, according to EN 13964:2014



Visual appearance

S White 190, nearest NCS colour sample S 0500-N, 80% light reflectance. S Grey 981, nearest NCS colour sample S 2502-Y, 45% light reflectance. S Black 970, nearest NCS colour sample S 8502-Y, 4% light reflectance. S Nature, 60% light reflectance. Slight colour differences can occur.



Cleanability

Weekly dusting and vacuum cleaning



Accessibility

The tiles are easily demountable. Minimum demounting depth according to installation diagrams.



Installation

Installed according to installation diagrams, installation guides and drawing aid. For information regarding minimum overall depth of system see quantity specification.



System weight

The weight of the system (including suspension grid) should be approximately 3-5 kg/m².



Mechanical properties


See table about Max live load and Min load bearing capacity and Functional demands, Mechanical properties at www.ecophon.com.



CE

Ecophon ceiling systems are CE marked according to the European harmonized standard EN 13964:2014. CE marked construction products are covered by a Declaration of Performance (DOP) which enables customers and users to easily compare performance of products available on the European market.



INSTALLATION DIAGRAM (M22) FOR ECOPHON MODUS WITH INLINE CARRIER




© Ecophon Group

QUANTITY SPECIFICATION (EXCL. WASTAGE)

		Size, mm		
		1200x600	1200x1200	1200x1200
1	Industry Modus	1,4/m ²	0,7/m ²	0,7/m ²
2	Connect Inline carrier, installed at 1200 mm centres	0,9m/m ²	0,9m/m ²	0,9m/m ²
3	Connect Screw (for light weight concrete or metal)	1,6/m ²	2,3/m ²	2,3/m ²
4	Connect Washer	0,9/m ²	0,9/m ²	0,9/m ²
Δ Min. overall depth of system: 50 or 100 mm		-	-	-
δ Min. demounting depth: The system is non-demountable		-	-	-




Profiles support tiles in one direction



Screw and washer in centre of tiles





INSTALLATION DIAGRAM (M23) FOR ECOPHON MODUS WITH SCREW AND WASHER



© Ecophon Group


QUANTITY SPECIFICATION (EXCL. WASTAGE)

		Size, mm		
		1200x600	1200x1200	1200x1200
1	Industry Modus	1,4/m²	0,7/m²	0,7/m²
2	Connect Screw (for light weight concrete or metal)	5,6/m²	2,8/m²	2,8/m²
3	Connect Washer	5,6/m²	2,8/m²	2,8/m²
Δ Min. overall depth of system: 50 or 100 mm		-	-	-
δ Min. demounting depth: The system is non-demountable		-	-	-



Panel with Connect Screw AL and Connect Washer AL



INSTALLATION DIAGRAM (M44) FOR ECOPHON INDUSTRY MODUS, 2- OR 4- SIDED SUPPORT




© Ecophon Group

QUANTITY SPECIFICATION (EXCL. WASTAGE)

	Size, mm		
	1200x600	1200x1200	1200x1200
1 Industry Modus	1,4/m ²	0,7/m ²	0,7/m ²
2 Connect Adjustable hanger, installed at 1200 mm centres (only 4-sided support)	0,7/m ²	0,7/m ²	0,7/m ²
3 Connect Hanger Clip (not to be used in swimming hall environments)	0,7/m ²	0,7/m ²	0,7/m ²
4 Connect T24 Cross tee, L=1200, installed at 1200 or 600 mm centres (only 4-sided support)	1,7m/m ²	0,9m/m ²	0,9m/m ²
5 Connect T24 Main runner, installed at 1200 mm centres (only 4-sided support)	0,9m/m ²	0,9m/m ²	0,9m/m ²
6 For direct installation: Connect Direct Bracket, installed at 1200 mm centres	0,7/m ²	0,7/m ²	0,7/m ²
7 Connect Angle trim, fixed at 300 mm centres	as required	as required	as required
8 Connect Shadow-line trim, fixed at 300 mm centres	as required	as required	as required
Δ Min. overall depth of system: 50, 80 or 100 mm with Direct fixing bracket. 100 mm with Adjustable hanger.	-	-	-
δ Min. demounting depth: 150 mm for 50 mm thickness. 250 mm for 100 mm thickness.	-	-	-



Suspension with adjustable hanger and clip




Suspension with direct bracket

Size, mm	Max live load (N)	Min load bearing capacity (N)
1200x600	40	160
1200x1200	40	160
1200x1200	40	160

Live load/load bearing capacity



INSTALLATION DIAGRAM (M444) FOR ECOPHON INDUSTRY MODUS, 2-SIDED SUPPORT



© Ecophon Group

QUANTITY SPECIFICATION (EXCL. WASTAGE)

	Size, mm		
	1200x600	1200x1200	1200x1200
1 Industry Modus	1,4/m ²	0,7/m ²	0,7/m ²
2 Connect T24 Main runner, installed at 1195 mm centres (only 2-sided support)	0,9m/m ²	0,9m/m ²	0,9m/m ²
3 For direct installation: Connect Direct Bracket, installed at 1200 mm centres	0,7/m ²	0,7/m ²	0,7/m ²
4 Connect Angle trim, fixed at 300 mm centres	as required	as required	as required
5 Connect Shadow-line trim, fixed at 300 mm centres	as required	as required	as required
Δ Min. overall depth of system: 50, 80 or 100 mm with Direct fixing bracket.	-	-	-
δ Min. demounting depth: The system is non-demountable	-	-	-



Suspension with direct bracket

Ecophon Industry™ Ambit


Suitable for noise reduction in industrial premises, where a concealed grid and no visible suspension details are required. The tiles are not demountable.

The Ecophon Industry Ambit system consists of Ecophon Industry Ambit tiles and Connect Ambit fixing, with an approximate weight of 3 kg/m². The tiles are manufactured from high density glass wool. The visible surface is a batch painted glass tissue in white and the back of the tile is covered with glass tissue. The edges are primed.




The Print shop,


SYSTEM RANGE




Size, mm	1200x600
Direct	•
Thickness	40
Inst. Diag.	M40



Industry Ambit tile.



Section of Industry Ambit system.



Industry Ambit system.




Acoustic

Sound Absorption:

Test results according to EN ISO 354. Classification according to EN ISO 11654.

α_p , Practical sound absorption coefficient



— Industry Ambit 40 mm, 40 mm o.d.s.

THK mm	o.d.s. mm	α_p , Practical sound absorption coefficient						α_w	Sound absorption class
		125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz		
40	40	0.15	0.60	0.95	1.00	1.00	1.00	0.90	A



Indoor Air Quality

Certificate / Label	
Eurofins Indoor Air Comfort®	IAC
French VOC	A
Finnish M1	•



Environmental Footprint

	Kg CO ₂ equiv/m ²
Industry Ambit	4,81 (Industry family EPD in conformity with ISO 14025 / EN 15804)



Circularity

Minimum post-consumer recycled content	59%
Recyclability	Fully recyclable



Fire safety

Country	Standard	Class
Europe	EN 13501-1	A2-s1,d0

The glass wool core of the tiles is tested and classified as non-combustible according to EN ISO 1182.



Humidity Resistance

Class C, relative humidity 95% and 30°C, according to EN 13964:2014



Visual appearance

White 190, nearest NCS colour sample S 0500-N, 80% light reflectance. Since the product has a coloured glassfelt as a surface, it can appear mottled, specially with indirect lighting. Slight colour differences can occur.



Cleanability

Weekly dusting and vacuum cleaning.



Accessibility

The tiles are non-demountable.



Installation

Installed according to installation diagrams, installation guides and drawing aid. For information regarding minimum overall depth of system see quantity specification.



System weight

The weight of the system should be approximately 3 kg/m².



Mechanical properties


Additional live load has to be fixed to the soffit.



CE

Ecophon ceiling systems are CE marked according to the European harmonized standard EN13964:2014. CE marked construction products are covered by a Declaration of Performance (DOP) which enables customers and users to easily compare performance of products available on the European market.



INSTALLATION DIAGRAM (M40) FOR ECOPHON INDUSTRY AMBIT




© Ecophon Group

QUANTITY SPECIFICATION (EXCL. WASTAGE)


		Size, mm
		1200x600
1	Industry Ambit	1,4/m²
2	Timber batten	as required
3	Connect Ambit fixing	2,8/m²
Δ Min. overall depth of system: 40 mm		-
δ Min. demounting depth: The system is non-demountable		-



Installation on timber batten with screw and washer



Installation with Connect Ambit fixing



Installation with Connect Angle trim C3

Ecophon Industry™ RTP


Suitable for noise reduction in industrial premises, where an impact resistant ceiling is needed. The system consists of Ecophon Industry RTP panels and Ecophon Connect grid system, with an approximate weight of 4-6 kg/m² depending on thickness. The panels have a glass wool core. The visible surface is a perforated sheet metal facing (Ø3 mm hole diameter, 15% perforated area) on top of a black glass tissue. The metal facing is bent around the long edges of the panels and overlaps the back surface. All edges are primed in black. The perforated sheet metal facing is galvanized, but also available in white.

Connect grid and accessories. The grid is manufactured from galvanized steel.


For best performance and system quality, use Ecophon




SYSTEM RANGE




Size, mm	1200x600	1200x600
T24	•	•
Thickness	30	50
Inst. Diagr.	M172	M172



Industry RTP system.



Section of Industry RTP system.



Industry RTP panel.




Acoustic

Sound Absorption:

Test results according to EN ISO 354. Classification according to EN ISO 11654.

α_p , Practical sound absorption coefficient



- Industry RTP 30 mm, 50 mm o.d.s.
- Industry RTP 30 mm, 200 mm o.d.s.
- Industry RTP 50 mm, 50 mm o.d.s.
- - - Industry RTP 50 mm, 200 mm o.d.s.

THK mm	o.d.s. mm	α_p , Practical sound absorption coefficient						α_w	Sound absorption class
		125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz		
30	50	0.10	0.50	0.95	1.00	1.00	1.00	0.80	B
30	200	0.50	0.85	0.95	1.00	1.00	1.00	1.00	A
50	50	0.20	0.80	1.00	1.00	1.00	1.00	1.00	A
50	200	0.60	0.85	0.95	1.00	1.00	1.00	1.00	A

THK mm	o.d.s. mm	NRC	SAA
30	50	0.85	0.89
30	200	0.95	0.96
50	50	0.95	0.99
50	200	0.95	0.99



Indoor Air Quality

Certificate / Label

Eurofins Indoor Air Comfort®	IAC
French VOC	A
Finnish M1	•



Circularity

Minimum post-consumer recycled content (30 mm)	65%
Minimum post-consumer recycled content (50 mm)	67%
Recyclability	Fully recyclable



Fire safety

Country	Standard	Class
Europe	EN 13501-1	A2-s1,d0

The glass wool core of the tiles is tested and classified as non-combustible according to EN ISO 1182.



Humidity Resistance

Class A, relative humidity 70% and 25°C, according to EN 13964:2014



Visual appearance

Galvanized 189, 55% light reflectance, White 170, 65% light reflectance.



Cleanability

Weekly dusting and vacuum cleaning.



Accessibility

The tiles are easily demountable. Minimum demounting depth according to installation diagrams.



Installation

Installed according to installation diagrams, installation guides and drawing aid. For information regarding minimum overall depth of system see quantity specification.



System weight

The weight of the system (including suspension grid) should be approximately 4-6 kg/m².



Mechanical properties


See table about Max live load and Min load bearing capacity and Functional demands, Mechanical properties at www.ecophon.com.



CE

Ecophon ceiling systems are CE marked according to the European harmonized standard EN 13964:2014. CE marked construction products are covered by a Declaration of Performance (DOP) which enables customers and users to easily compare performance of products available on the European market.



INSTALLATION DIAGRAM (M172) FOR ECOPHON INDUSTRY RTP.




© Ecophon Group

QUANTITY SPECIFICATION (EXCL. WASTAGE)

	Size, mm	
	1200x600	1200x600
1 Industry RTP	1,4/m ²	1,4/m ²
2 Connect T24 Main runner, installed at 1200 mm centres (max. distance from wall 600 mm, can be extended up to 1200 mm if no live load between Main runner 0,9m/m ² and wall).	0,9m/m ²	0,9m/m ²
3 Connect T24 Cross tee, L=1200 mm, installed at 600 mm centres	1,7m/m ²	1,7m/m ²
4 Connect Adjustable Hanger, installed at 1200 mm centres (max. distance from wall 600 mm)	0,7/m ²	0,7/m ²
5 Connect Hanger Clip (not to be used in swimming hall environments)	0,7/m ²	0,7/m ²
6 For direct installation: Connect Direct Bracket, installed at 1200 mm centres	0,7/m ²	0,7/m ²
7 Connect Angle trim, fixed at 300 mm centres	as required	as required
8 Connect Shadow-line trim, fixed at 300 mm centres	as required	as required
Δ Min. overall depth of system, with Adjustable hanger: 100 mm, with Direct bracket 50 mm	-	-
δ Min. demounting depth: 170 mm (30 mm thickness), 220 mm (50 mm thickness)	-	-



Suspension with adjustable hanger and clip



Suspension with Direct bracket

Size, mm	Max live load (N)	Min load bearing capacity (N)
1200x600	30	160
1200x600	30	160

Live load/load bearing capacity