

EXTERIOR EASIPLAST

A high performance polymer modified cement based repair mortar for use as a masonry crack filler and for small repairs.

AVAILABILITY

Colour range Not applicable.

Packaging 4 kilogram bag.

PROPERTIES

Drying time Allow to dry to an even colour. Generally 1-4 days depending on thickness.

Composition Portland cement, sand and additives.

Spreading rate Variable depending on width and depth of filling or making good.

Wet thickness As required up to a maximum of 25mm (1") per application.

Dry thickness Up to a maximum of 25mm (1") per application.

Volume solids 100%.

Flash point Not applicable.

VOC content Not applicable.

EU limit value for this product (cat.A/c): 75 g/l (2007) / 40 g/l (2010)
This product contains max. 6 g/l VOC.

Limitations Do not apply when there is a risk of rain, or when air or substrate temperatures are likely to fall below 5°C. Do not surface fill over existing coatings. If applied in cold damp conditions lime bloom may appear on the surface and can be transmitted through the chosen decorative finish.

PREPARATION

New surfaces All surfaces must be sound, suitably dry and free from anything that will interfere with the adhesion of the materials to be applied.

Previously decorated surfaces

All surfaces must be sound, suitably dry and free from anything that will interfere with the adhesion of the materials to be applied. Remove all loose, and failing or suspect material by scraping or brushing with a stiff bristle brush (not wire) to a sound edge. Organic growth must be removed and the areas treated with Sandtex Trade Fungicide. For surfaces in poor condition mechanical means may be necessary e.g. pressure washing between 1500-2000 psi (102-136 bar), proprietary paint removal system, wet or dry grit blasting. Care must be taken not to damage the underlying surface. Fill cracks and small defects in masonry surfaces with Sandtex Trade Exterior Easiplast and finish to match existing.

Mixing Loosen contents of bag. Add Sandtex Trade Exterior Easiplast to water and mix to a workable consistency to suit the work in hand.

APPLICATION Apply by hawk/trowel, pointing trowel or filling knife.

CLEANING Wash with clean water immediately after use. Do not empty or wash the mixed remains of Sandtex Exterior Easiplast into drainage systems.

HEALTH AND SAFETY Please refer to the Safety, Health and Environmental Information on the container. Take special precautions during the surface preparation of pre 1960's painted surfaces as they may contain harmful lead. For further information contact the Customer Relations Team. When preparing the surfaces avoid the inhalation of dust and/or metal particles. Wear a suitable facemask. Material Safety Data Sheets for this and all other Sandtex products are freely available from the place of purchase or the address below. Store in secure dry conditions inaccessible to children or animals. Containers should be kept closed during storage. Do not empty into drains, watercourses or access routes to septic tanks.

GENERAL INFORMATION

Apply all products in accordance with BS 6150: 2006 Code of practice for painting of buildings and BS 8000: Part 12: 1989 Code of practice for decorative wallcoverings and painting. Under normal and frost free conditions this product will remain usable for up to two years if stored correctly and unopened.

Every care is taken to ensure that all information provided on this Technical Data Sheet is accurate. Final results cannot be guaranteed by the manufacturer as it has no control over the conditions under which its products are applied.

For help or more information contact our Customer Relations Team on 0845 372 3425. Before using this product please ensure you have the latest information. The information is correct at date of issue July 2008.



Sandtex Trade
Hollins Road, Darwen, Lancs BB3 0BG
Tel: 0845 372 3425 Fax: 0845 372 3426 Email: info@sandtextrade.co.uk
Website: www.sandtextrade.co.uk