

ACOUSTIC PRODUCTS LTD

GLASSFOLD GS35 GLAZED MOVABLE WALL

L20/540 NBS STYLE TECHNICAL SPECIFICATION

SLIDING FOLDING PARTITIONS TO: _____

Refer to drawing no(s): _____

Manufacturer and reference: Glassfold Glazed Movable Wall by
Acoustic Products Ltd
139 Tankerton Road
Whitstable
Kent
CT5 2AW
Tel 01227 281140
Fax 01227 281141
Email: enquiries@acoustic-products.co.uk

Characteristics: Manually operated modular single glazed panel system. Panel sizes up to 1300mm wide x 2800mm high using 10mm tempered glass or up to 1300mm wide x 4000mm high using 12mm tempered glass with a maximum loading per panel of 100kgs for the 2-point suspension 90 degree stacking system or 500kgs per panel using the 2-point suspension 135 degree stacking system. No limit to the overall opening width/number of panels, segmented low radius curved track options available. Top and bottom Satin Anodised Aluminium rails powder coated to RAL/BS spec optional. The system is supplied as standard with a full height glazed door at one or both ends of the opening.

Manifestation: _____
(As specified).

Furniture: SAA ironmongery to door panel or _____
(As specified).

Track and Roller System: Two point suspension for offset/remote stacking. Heavy duty top track powder coat finish white. No floor track.

Acoustic Rating: Non acoustic.