



HUSH-BAR RESILIENT BAR

Hush-Bar resilient bars are used to optimise acoustic performance by virtually decoupling a lining from a ceiling or wall structure. By using the Hush-Bars the airborne and impact sound transmission is significantly reduced. The Hush-Bars are one of the most important elements of a system to ensure compliance with the Building Regulations for sound transmission through separating ceilings and walls.



Acoustic Performance

| Impact $L'_{nT,w}$ dB | Airborne $D_{nT,w}$ dB | Airborne $D_{nT,w} + C_{tr}$ dB |
|--------------------------|---------------------------|------------------------------------|
| 55 | 55 | 49 |

Results based on Hush-System 2003 Plus test results incorporating Hush-Bar Resilient Bars

Product Data

- To be screw fixed to the underside of timber joists or battens at 600mm centres
- Can be screw fixed to timber and metal stud walls at 450mm centres
- Comprises of metal bars
- Overall depth 16mm
- Overall Bar Dimensions 2400mm long x 65mm wide x 16mm deep

Profile



Features

- ✓ Excellent acoustic performance
- ✓ Used extensively within refurbishment and new build projects as part of a sound insulation system for separating ceilings and walls
- ✓ Suitable for suspending up to 30kg/m²
- ✓ Reduces airborne sound transmission
- ✓ Building Regulations Part E (England and Wales), Section 5 (Scotland) and Part G (Northern Ireland)
- ✓ Can be used as part of Robust Details ceiling systems
- ✓ Can be used as part of a Code For Sustainable Homes development
- ✓ Easy to install

Suitable for:



HUSH (UK) LIMITED
44 Canal Street,
South Sefton,
Merseyside L20 8QU.

Tel: 0151 933 2026
Fax: 0151 944 1146
Email: info@hush.uk.com
www.hush.uk.com



HUSH ACOUSTICS
Sound Insulation Products and Systems

RESIDENTIAL BUILDING REGULATIONS

Overview

The nuisance of noise is regarded as a health and safety issue for persons living in dwellings and all occupants of a dwelling should be allowed to follow normal domestic activities, including sleep and rest, without threat to their health from noise.

Noise is transmitted in buildings by both airborne and impact sound sources and UK Building Regulations requires that both these noise types are controlled. Practical guidance to meet with Building Regulation requirements is given within Approved Document E.

UK Building Regulations approved Document E 2003 incorporates a unit of measurement to determine low frequency airborne sound transmission.

Due to proven intrinsic difficulties of measuring low frequency sound, in domestic sized rooms, it must be expected that there could be significant deviations in the accuracy of these measurements. Furthermore, there will be variations from site to site due to structural differences in buildings, general site conditions and workmanship.

All these factors can influence the repeatability of both impact and airborne acoustic test results. Therefore, any test results must be considered as an indication only and no warranty can be given or implied as to the actual acoustic performance in any particular situation.

Sound insulation, in general terms, is the prevention of airborne and impact sound being transmitted from one part of a building to another through separating floors, ceilings or walls.

Airborne Sound

Airborne sound sources produce noise by vibrating the surrounding air, for example speech, televisions and home entertainment systems. Airborne sound insulation is concerned with reducing this sound transmission through separating floors and walls.

Impact Sound

Impact sound sources produce noise by direct physical excitation of a part of a building, for example footsteps on a floor. Impact sound insulation is concerned with resisting this impact sound upon separating floors.

Flanking transmission

Flanking transmission occurs when sound is transmitted from one space to another indirectly, through adjoining parts of the structure, e.g. impact sound may be transmitted from one room to another through a timber floor, but also through the supporting wall.

Flanking transmission is always a potential problem within any structure, in particular, buildings being converted, and depending on the intensity of the acoustic energy received via flanking transmission paths, the effectiveness of sound insulation of separating partitions can be much lower than expected from their construction.

Careful consideration must be given to the effect of flanking transmission within any building and all potential flanking paths must be identified and eliminated prior to the installation of any sound insulation system.

England & Wales

New Approved Document E

Building Regulations New Approved Document E came into force on 1st July 2003 with the introduction of pre-completion testing (PCT) for sound insulation as a means of demonstrating compliance, and as from 1st July 2004 the use of Robust Details (RD) in new build has been accepted as an alternative to PCT.

Requirements E1, E2 and E3 of Document E apply to the sound insulation of any type of conversion or new build used as a dwelling including; houses, apartments, hostel rooms, hotels, boarding houses, halls of residence and residential homes. Requirement E4 applies to acoustic conditions in schools.

Performance standards are given for each requirement, as follows:

Table 0.1a Dwelling-houses and flats – performance standards for separating walls, separating floors, and stairs that have a separating function

| | Airborne sound insulation sound insulation $D_{nT,w} + C_{tr}$ dB (Minimum values) | Impact sound Insulation $L'_{nT,w}$ dB (Maximum values) |
|---|--|---|
| Purpose built dwelling - houses and flats | | |
| Walls | 45 | - |
| Floors & stairs | 45 | 62 |
| Dwelling - houses and flats formed by material change of use | | |
| Walls | 43 | - |
| Floors & stairs | 43 | 64 |

Table 0.1b Rooms for residential purposes – performance standards for separating walls, separating floors, and stairs that have a separating function

| | Airborne sound insulation sound insulation $D_{nT,w} + C_{tr}$ dB (Minimum values) | Impact sound Insulation $L'_{nT,w}$ dB (Maximum values) |
|--|--|---|
| Purpose built dwelling - houses and flats | | |
| Walls | 43 | - |
| Floors & stairs | 45 | 62 |
| Rooms for residential purposes formed by a material change of use | | |
| Walls | 43 | - |
| Floors & stairs | 43 | 64 |

Table 0.2 Laboratory values for new internal walls and floors within dwelling-houses, flats and rooms for residential purposes, whether purpose built or formed by material change of use

| | Airborne sound insulation R_w dB (Minimum values) |
|--------|---|
| Walls | 40 |
| Floors | 40 |

For further information on Approved Document E visit www.communities.gov.uk or www.planningportal.gov.uk

PCT & Robust Details

Pre-completion testing applies to all conversion projects and new build projects not built by means of Robust Details. At least 10 percent of each type of all new residential properties are tested to determine fulfillment of the regulations and pre-completion testing must always be carried out by an accredited acoustic engineer.

Contact with suitable sound testing companies can be arranged through our technical department.

Robust Details

Robust Details are high performance separating wall and floor constructions that are expected to be sufficiently reliable not to need the check provided by PCT. A set of design details which achieve compliance with requirement E1 have been approved by Robust Details Ltd.

Builders intending to use any of these design details must register the project with Robust Details Ltd and follow, to the letter, procedures issued by Robust Details Ltd.

For further information on Robust Details visit www.robustdetails.com

Scotland & Northern Ireland

Scottish Building Regulations Section 5

Deals with the reduction of sound through separating building elements between domestic buildings.

| | New build and conversions other than traditional buildings | Conversion of traditional buildings* |
|---|--|--------------------------------------|
| Minimum airborne sound transmission ($D_{nT,w}$) (Floors & walls) | 56dB | 53dB |
| Maximum impact sound transmission ($L'_{nT,w}$) (Floors only) | 56dB | 58dB |

For further information please visit www.scotland.gov.uk

Northern Ireland Building Regulations Part G

Northern Ireland Building Regulations Part G, Sound Insulation in Dwellings

| | Airborne sound insulation sound insulation $D_{nT,w}$ dB (Minimum values) | Impact sound insulation $L'_{nT,w}$ dB (Maximum values) |
|-------------------|---|---|
| New Build | | |
| Floors | 52 | 61 |
| Conversion | | |
| Floors | 48 | 65 |

For further information please visit www.buildingcontrol-ni.com