

For more information on Hanson Formpave, visit [www.barbourproductsearch.info](http://www.barbourproductsearch.info)

Hanson Formpave



Formpave

**Aquasett combined  
permeable paving**

**Aquasett® combined paving blocks can be used in conjunction with either tanked or infiltration systems.**

Aquasett® combined blocks are manufactured from concrete with a tensile splitting strength in accordance with BS EN 1338:2003.

Aquasett® combined blocks provide drainage through vertical channels and will allow water through the surface at a rate of approximately 9000mm per hour (9000 litres per m2 per hour). The Inbitex® geotextile beneath the laying course will allow approximately 4500 litres per m2 per hour through and this figure should be used for design purposes.

**Aquasett® combined**

For use on footpaths and domestic drives Range of colours and the Olden finish make the Aquasett® combined appropriate for use in conservation areas or on projects where architectural heritage is a major consideration.

**Sizes**

Large 150 x 250 x 60/80mm

Medium 150 x 150 x 60/80mm

Small 100 x 150 x 60/80mm

Ratio of blocks in 0.8 square metre manufactured format: 10 large, 14 medium and 7 small.

Laying pattern: Staggered stretcher bond

Colours: Traditional, Red Brindle, Vendage and Pennant. Other colours are available to special order.

Finish: Olden and EcoGranite Bush hammered to special order

