

Products for decking maintenance



When exposed to sunlight and adverse weather conditions, the wood undergoes a natural tone and colour alteration over time and tends to turn grey. Regular maintenance with appropriate oils can minimize this process. For this reason, from the long Ravaioli's experience, a new maintenance product line has grown up. Ideal for

decking this line is the result of specialized studies and mixture of high quality components. Particularly indicated to protect wood from wood-eating insects and from the graying process caused by atmosphere factors, the brand new products of **mydeck+** line are a real beauty treatment for Ravaioli's decking.

mydeck+ product line



mydeck+ WOOD OIL

Description: pigmented, impregnating and regenerating water-based oil, particularly resistant to the sun action. Thanks to its staining agents, **mydeck+ WOOD OIL** gives to the wood a pleasant warm color, protecting it against the attack of both moulds and infesting organisms. It is recommended and particularly indicated to make pigmentations colours more homogeneous, especially for those woods which present a non regular tone, such as Ipè.

It is also available **mydeck+ WOOD OIL LIGHT**, which due to the absence of pigmentation, preserves the original color of the wood.

How to use: before applying the product, shake it well and prepare the wood, preferably with 120/150 sandpaper, and proceed with an accurate cleaning of the flooring. When the flooring is completely dry, apply a coat of **mydeck+ WOOD OIL** with a brush along the wood grain. After 2/4 hours apply a second coat without sanding.

It is recommended to apply the product during the morning when the wood's temperature is fresher. It is advisable to use it at least twice a year.

Characteristics:

Mixing Ratio	Performance	Storage Stability	Dust dry	Touch dry	Application temperature
Single component	10m ² / l	1 year (in its original unopened barrel at a temperature ranging from +10°C to +25°C)	2 hours	4 hours	+10°C ÷ +25°C



mydeck+ GREY OFF

Description: regenerating solution for wood that has become grey, ideal to restore the original color of the wooden objects that have been exposed to bad weather, all without damaging expansion joints and rubbers. Biodegradable and Ecotoxic.

How to use: spray the solution keeping it at 20-25 cm from the surface. It can be applied also by brush or roller. After waiting 20/30 minutes, remove the patina by using a brush or a smooth trowel. For large areas, high pressure cleaner can also be used by setting the water jet. In this case, the product can be left on the surface for a maximum of 12 hours. In case of heat, it is advisable to dampen with tap water the surface before proceeding with the application. Avoid the contact with other materials.

Characteristics:

Mixing Ratio	Performance	Storage Stability	Application temperature
Single component	paint spraying: 25m ² /l paint brush: 15m ² /l	1 year (in its original unopened barrel at a temperature ranging from +10°C to +25°C)	+10°C ÷ +25°C



mydeck+ SOAP

Description: cleaning and nourishing soap for exterior floorings. It cleans efficiently dirt, residual chlorine, saltiness and spots, respecting wood without living any stain. Its constant use protract the times of maintenance of the treatment with mydeck+ WOOD OIL.

How to use: shake well before use. For a correct cleaning of the flooring use water and 1/5 of mydeck+ SOAP. Wash a first time using a floor cloth or mop. When dry, wash a second time. The floor can be walked on immediately. It does not leave any stain.

Characteristics:

Mixing Ratio	Storage Stability	Application temperature
Single component	1 year (in its original unopened barrel at a temperature ranging from +10°C to +25°C)	+10°C ÷ +25°C



mydeck+ BALSAM

Description: regenerating balsam which enhances the aspect and the brilliance of the decking exposed to unfavorable atmospheric conditions, corresponding to the hottest period of the year. It is ideal to regenerate the beauty and the natural properties of the wood, even though not for a long lasting period. It is ideal also for a summary cleaning, thanks to its cleaning characteristics.

How to use: shake well before use. Apply directly on wood with a microfiber cloth following the wood grain. If necessary, when dry, proceed with a second application. The floor can be walked on immediately. It does not leave any stain. It is ideal for frequent applications.

Characteristics:

Mixing Ratio	Performance	Storage Stability	Application temperature
Single component	8m ² / l	1 year (in its original unopened barrel at a temperature ranging from +10°C to +25°C)	+10°C ÷ +25°C

Safety: product residues can pose a potential spontaneous combustion hazard. For this reason, the cloths, sponges and felt materials used for application must be soaked in water and allowed to dry outdoors before being discarded. For additional details, please contact Ravaioli and request the relative safety datasheet for the product in question.

Maintenance and Cleaning Data from WALLBARN LTD
www.wallbarn.com, sales@wallbarn.com, 0208 916 2222