


# HUSH FELT UNDERLAY



Hush Felt Underlay is a high performing felt underlay that has been designed to isolate the final floor finish and improve impact acoustic performance. The Hush Felt Underlay is primarily used under carpet, laminate and engineered timber floor finishes.

By selecting to use the Hush Felt over thicker or less dense materials the initial excessive 'bounce' will be eliminated. If the wrong underlay is used then the acoustic efficiency will be lost when the underlay settles. Hush Felt Underlay is crucial for isolating these floor finishes.

Floating floors must survive daily pounding and flexing movement. This demands a resilient material designed taking into account compression, durability and longevity. The felted polypropylene fibres of Hush Felt provide long term resilience and are unaffected by migration of plasticisers common to the polyethylene foams.



## PRODUCT DATA

- Primarily use as an acoustic underlay for laminate, engineered flooring and carpet.
- Supplied in wrapped rolls 11m x 1.37m x 10mm
- Density is 90 kgs/m<sup>3</sup>

## SUITABLE FOR:



## FEATURES

- ✓ Environmentally friendly
- ✓ It may be trimmed with scissors and is pleasant to handle, requiring no precautions against skin or respiratory irritation.
- ✓ Easy to install
- ✓ Excellent impact noise reduction

[VIEW ON OUR WEBSITE](#) ➤

## HUSH ACOUSTICS

TEL: 0151 933 2026

EMAIL: [info@hushacoustics.co.uk](mailto:info@hushacoustics.co.uk)

[www.hushacoustics.co.uk](http://www.hushacoustics.co.uk)

[hush-acoustics](#) [hushacoustics](#)

[@hushacoustics](#) [hushuk.acoustics](#)

44 Canal Street, Bootle, Liverpool L20 8QU

Offices also based in London and Yorkshire



**HUSH ACOUSTICS**  
Sound Insulation Products and Systems