








DISCOVER OUR RANGE OF KIDDE SMOKE DETECTORS

With their compact and elegant design, our detectors seamlessly blend safety with aesthetics, making them a perfect addition to any home. Whether you're upgrading your security or enhancing your interior, our detectors offer both peace of mind and style.

			
	2030-DSR Easy to set-up and use throughout the home, with 9V battery supplied as standard.	DY29 Reliable battery-operated smoke alarm with a replaceable battery that lasts for 5-years.	10Y29 Kidde's premium battery-operated smoke alarm, offering 10-years battery life and warranty.
Battery Life	Minimum 1-year	Minimum 5-years	Minimum 10-years
Alarm Life	10-years	10-years	10-years
Warranty	3-years	5-years	10-years
Dimensions	102mm x 36mm	100mm x 33mm	104mm x 45mm
Alarm Weight (including batteries)	128g	158g	135g
Quantity per Pack	18 units	6 units	6 units
Certifications	 EN14604:2005		 KM 524754 EN 14604:2005

WHY CHOOSE OUR SMOKE DETECTORS?

- **Enhanced Safety:** Protect your home and loved ones with reliable, certified detectors.
- **Easy Installation:** Quick wall or ceiling mounting for instant protection.
- **Minimal Maintenance:** Batteries included that offer hassle-free peace of mind.

CONTACT US TODAY!

For more information, or to place an order, visit our website or contact our dedicated team:

- ✉ **By email:** admin.kiddesafety@carrier.com
- ☎ **By phone:** 03337 722227
- 🌐 **Visit our website:** <https://www.kidde.com/fire-safety/en/uk/>

Protect your home with our range of KIDDE smoke detectors. Your safety is priceless!

Common Features of our Models

- **Optical Sensor:** Fast and accurate detection.
- **Test/Silence:** Convenient feature for testing or silencing the detector.
- **End-of-Life Warning:** Alerts you when the detector needs to be replaced.
- **Versatile Mounting:** Can be installed on the wall or ceiling.
- **Standard:** EN14604:2005, ensuring quality and safety.
- **Humidity Range:** Operates in conditions up to 93% RH (non-condensing).