

MEA®RIN 300 THE NEW DRAINAGE SYSTEM

Climate change and exceptional rainfall events mean that collecting and draining water from surfaces becomes an absolute necessity. The composite technology used in the design of the MEARIN 300 drainage channel offers durable strength for major hydraulic works and environmental protection.



Drainage



MEA®RIN 300





AN INNOVATIVE MATERIAL: SMC

MEARIN drainage channels are manufactured using Sheet Moulding Compound (SMC), a resin-glass fibre composite. The principal qualities of this material are:

- High mechanical and impact strength
- Outstanding chemical resistance
- Toleration of temperature variations (stable in frost and at more than 100° C)
- Light weight: simplifies all stages in installation.

SIMPLE INSTALLATION

Thanks to its low SMC weight (11.8 kg per metre, excluding grating) and assembly system, MEARIN provides optimum conditions for site installation.

SECURE GRATINGS: STARFIX

Gratings are fitted securely using a 4-point system with no screws. A special tool also makes it easy to remove MEARIN 300: DRAINAGE CHANNELS gratings for maintenance work.

STABILITY UNDER HIGH LOADS

The ingenious profile shape makes the channel body - Airports* extremely stable, with an extended range of mechanical strength (Classes C250 to E600). It can be used in a - Urban drainage great variety of applications.

RAPID FLOW

The body shape of the channel optimises water flow and thus facilitates self-cleaning, even in terrains with low gradients.

COMPLETE SYSTEM

A wide range of accessories allows for the design of a reliable and homogeneous system.

COMPLIANCE WITH STANDARD: EN1433

The whole of the MEARIN drainage channel range meets the requirements of the EN 1433 Standard and carries the CE lahel

TWO VERSIONS

For an extensive range of applications.

- MEARIN Plus: Entire drainage channel and edge in SMC composite, in strength Classes C250 to D400
- MEARIN Expert: SMC composite drainage channels with galvanised steel edge protection in strength Classes C250 to E600.

SUITABLE FOR THE FOLLOWING APPLICATIONS:

- Industrial areas
- Road networks
- * not suitable for runways





Ambachtsweg 18, 7021 BT Zelhem - Netherlands Postbus 90, 7020 AB Zelhem - Netherlands Tel.: +31(0)314 - 627 762 - fax: +31(0)314 - 627 777 sales.info@nl.mea.de - www.mearin.com

