

## Hydropanel strip



HYDROPANEL STRIP for joint finishing of beveled HYDROPANEL building boards in combination with HYDROPANEL RM of PM FINISHER.

HYDROPANEL STRIP is a very strong self-adhesive alkali resistant fibre glass mesh with high lateral strength. The fibres have been coated with an alkali resistant vinyl coating.

ARTICLE NUMBER: 4028997

### TECHNICAL CHARACTERISTICS

Dimensions		48 ± 1mm
Thickness		0,3 mm
Design (DIN 53853)	# threads lengthwise	36 ± 1 threads/10 cm
	# threads across	35 ± 1 threads/10 cm
Weight (DIN 53854)		62 g/m <sup>2</sup> ± 7 %
Content of finishing		ca. 40%
Colour		white
Tensile strength (DIN 53857 T1)	length (warp)	≥ 500 N/5cm
	across (weft)	≥ 850 N/5cm
Extension at tensile strength (DIN 53857 T1)	warp	≤ 1,7 %
	weft	≤ 1,9 %
Resistance to alkali (ETAG 004, 28 days)		
Tensile strength after 28 days exposure	warp	≥ 50 % from initial value
	weft	≥ 50 % from initial value



### PACKAGING

Packaging: 90m per roll, 24 rolls per cardboard box

### PROCESSING

Consult the application guidelines "HYDROPANEL INTERIOR"

This product information sheet replaces any previous editions. MARLEY ETERNIT reserves the right to amend this information sheet without prior notice. Readers should always satisfy themselves that they are referring to the most recent version of this document. No part of this text can be changed without permission of MARLEY ETERNIT.

Marley Eternit Ltd  
Lichfield Road  
Branston  
Tel 01283 722588  
Fax 01283 722219  
[hydropanel@marleyeternit.co.uk](mailto:hydropanel@marleyeternit.co.uk)  
[www.marleyeternit.co.uk](http://www.marleyeternit.co.uk)  
[www.hydropanel.co.uk](http://www.hydropanel.co.uk)