



 Cheriton Victorian <i>AB, PB, BC, SC</i>	<i>R21</i>	<i>R22</i>	<i>R23</i>	<i>R24</i>	<i>R26</i>	<i>R31</i>	<i>R32</i>	<i>BCP</i>	<i>TP</i>
Insert type	2 way Rocker	2 way Rocker	2 way Rocker	2 way Rocker	2 way Rocker	intermediate Rocker	Intermediate Rocker	Push to Make Rocker	Rocker
Plate material (see general notes)	Metal	Metal	Metal	Metal	Metal	Metal	Metal	Metal	Metal
Size (single) height	88mm	88mm	88mm			88mm	88mm	88mm	88mm
Size (single) width	88mm	88mm	88mm			88mm	88mm	88mm	88mm
Size (single) depth	8.5mm	8.5mm	8.5mm			8.5mm	8.5mm	8.5mm	8.5mm
Size (double) height				86mm	86mm				
Size (double) width				146mm	146mm				
Size (double) depth				8.5mm	8.5mm				
Box fixing hole centres	60.3mm	60.3mm	60.3mm	120.6mm	120.6mm	60.3mm	60.3mm	60.3mm	60.3mm
Grid fixing hole centres	Grid fixing inserts are available on Cheriton Victorian plates. For full details refer to GRID-IT technical pages and GRID-IT catalogue								
Minimum wall box depth	25mm	25mm	25mm	25mm	25mm	25mm	25mm	25mm	25mm
Wattage									
Current rating	10AX	10AX	10AX	10AX	10AX	10AX	10AX	10AX	10A
Voltage	220/250V AC	220/250V AC	220/250V AC	220/250V AC	220/250V AC	220/250V AC	220/250V AC	220/250V AC	220/250V AC
Max load	10amp inductive	10amp inductive	10amp inductive	10amp inductive	10amp inductive	10amp inductive	10amp inductive	10amp inductive	10amp resistive
Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz
IP rating	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD
Poles	Single	Single	Single	Single	Single	Single	Single	Single	Triple
Contact Gap Minimum	3mm	3mm	3mm	3mm	3mm	3mm	3mm	3mm	3mm
Terminal Capacity	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²
	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²
	1 x 2.5mm ²	1 x 2.5mm ²	1 x 2.5mm ²	1 x 2.5mm ²	1 x 2.5mm ²	1 x 2.5mm ²	1 x 2.5mm ²	1 x 2.5mm ²	1 x 2.5mm ²
	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand
Earth Terminal Capacity	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²
	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²
	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²
	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²
	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand
Product Class 1	Must be earthed	Must be earthed	Must be earthed	Must be earthed	Must be earthed	Must be earthed	Must be earthed	Must be earthed	Must be earthed
Ambient Operating Temperature	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C
Recommended Location	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only
Max installation Altitude	2000m	2000m	2000m	2000m	2000m	2000m	2000m	2000m	2000m
BS EN ISO Standard	BS EN 60669-1	BS EN 60669-1	BS EN 60669-1	BS EN 60669-1	BS EN 60669-1	BS EN 60669-1	BS EN 60669-1	BS EN 60669-1	BS EN 60669-1
Cable outlet (min)									
Cable outlet (max)									
Additional Notes :									


 Cheriton Victorian <i>AB, PB, BC, SC</i>	<i>S21</i>	<i>S22</i>	<i>S23</i>	<i>S24</i>	<i>S31</i>	<i>SDP</i>	<i>SBCP</i>	<i>SS1</i>	<i>SS2</i>
Insert type	2 way Dolly	2 way Dolly	2 way Dolly	2 way Dolly	Intermediate Dolly	Double Pole Dolly	Push to Make Dolly	Switched Socket	Switched Socket
Plate material (see general notes)	Metal	Metal	Metal	Metal	Metal	Metal	Metal	Metal	Metal
Size (single) height	88mm	88mm			88mm	88mm	88mm	88mm	
Size (single) width	88mm	88mm			88mm	88mm	88mm		
Size (single) depth	8.5mm	8.5mm			8.5mm	8.5mm	8.5mm		
Size (double) height			86mm	86mm					86mm
Size (double) width			146mm	146mm					146mm
Size (double) depth			8.5mm	8.5mm					8.5mm
Box fixing hole centres	60.3mm	60.3mm	120.6mm	120.6mm	60.3mm	60.3mm	60.3mm	60.3mm	120.6mm
Grid fixing hole centres	Grid fixing inserts are available on Cheriton Victorian plates. For full details refer to GRID-IT technical pages and GRID-IT catalogue								
Minimum wall box depth	25mm	25mm	25mm	25mm	25mm	25mm	25mm	35mm	35mm
Wattage									
Current rating	20AX	20AX	20AX	20AX	20AX	20AX	10AX	13 amps	13 amps
Voltage	220/250V AC	220/250V AC	220/250V AC	220/250V AC	220/250V AC	250v AC	250v AC	220/250V AC	220/250V AC
Max load	20amp inductive	20amp inductive	20amp inductive	20amp inductive	20amp inductive	20amp inductive	10amp inductive	13amps	13amps
Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz
IP rating	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD
Poles	Single	Single	Single	Single	Single	Single	Single	Double	Double
Contact Gap Minimum	3mm	3mm	3mm	3mm	3mm	3mm	3mm	3mm	3mm
Terminal Capacity	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	4 x 2.5mm ²	4 x 2.5mm ²
	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	3 x 4mm ²	3 x 4mm ²
	2 x 2.5mm ²	2 x 2.5mm ²	2 x 2.5mm ²	2 x 2.5mm ²	2 x 2.5mm ²	2 x 2.5mm ²	2 x 2.5mm ²	2 x 6mm ² Multi-Strand	2 x 6mm ² Multi-Strand
	2 x 4mm ² Multi-Strand	2 x 4mm ² Multi-Strand	2 x 4mm ² Multi-Strand	2 x 4mm ² Multi-Strand	2 x 4mm ² Multi-Strand	2 x 4mm ² Multi-Strand	2 x 4mm ² Multi-Strand	1 x 10mm ²	1 x 10mm ²
Earth Terminal Capacity	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	4 x 2.5mm ²	4 x 2.5mm ²
	6 x 1mm ²	6 x 1mm ²	6 x 1mm ²	6 x 1mm ²	6 x 1mm ²	6 x 1mm ²	6 x 1mm ²	3 x 4mm ²	3 x 4mm ²
	5 x 1.5mm ²	5 x 1.5mm ²	5 x 1.5mm ²	5 x 1.5mm ²	5 x 1.5mm ²	5 x 1.5mm ²	5 x 1.5mm ²	3 x 2.5mm ²	2 x 6mm ² Multi-Strand
	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	1 x 10mm ²	1 x 10mm ²
Product Class 1	Must be earthed	Must be earthed	Must be earthed	Must be earthed	Must be earthed	Must be earthed	Must be earthed	Must be earthed	Must be earthed
Ambient Operating Temperature	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5°C to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C
Recommended Location	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only
Max installation Altitude	2000m	2000m	2000m	2000m	2000m	2000m	2000m	2000m	2000m
BS EN ISO Standard	BS EN 60669-1	BS EN 60669-1	BS EN 60669-1	BS EN 60669-1	BS EN 60669-1	BS EN 60669-1	BS EN 60669-1	BS 1363	BS 1363
Cable outlet (min)									
Cable outlet (max)									
Additional Notes :									


 Cheriton Victorian AB, PB, BC, SC	<i>US2</i>	<i>US5</i>	<i>SHS</i>	<i>SP</i>	<i>SPN</i>	<i>SPNCO</i>	<i>FO</i>	<i>FOCO</i>
Insert type	Unswitched Socket	Unswitched Socket	Shaver Socket (Vertical)	Spur	Spur & neon	Spur, neon, cable outlet	Fuse only	Fuse & cable outlet
Plate material (see general notes)	Metal	Metal	Metal	Metal	Metal	Metal	Metal	Metal
Size (single) height	88mm	88mm		88mm	88mm	88mm	88mm	88mm
Size (single) width	88mm	88mm		88mm	88mm	88mm	88mm	88mm
Size (single) depth	8.5mm	8.5mm		8.5mm	8.5mm	8.5mm	8.5mm	8.5mm
Size (double) height			146mm					
Size (double) width			86mm					
Size (double) depth			8.5mm					
Box fixing hole centres	60.3mm	60.3mm	120.6mmV	60.3mm	60.3mm	60.3mm	60.3mm	60.3mm
Grid fixing hole centres	Grid fixing inserts are available on Cheriton Victorian plates. For full details refer to GRID-IT technical pages and GRID-IT catalogue							
Minimum wall box depth	35mm	35mm	47mm	35mm	35mm	35mm	35mm	35mm
Wattage								
Current rating	2 amps	5 amps	20VA	13amps	13amps	13amps	13amps	13amps
Voltage	220/250V AC	220/250V AC	220/240V AC	250v AC	220/250V AC	220/250V AC	250v AC	250v AC
Max load	2amps	5amps	200/240v input; 115/230v output	13amps	13amps	13amps	13amps	13amps
Hz	50/60Hz	50/60Hz	50Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz
IP rating	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD
Poles	n/a	n/a	Single	Double	Double	Double		
Contact Gap Minimum	n/a	n/a	n/a	3mm	3mm	3mm	n/a	n/a
Terminal Capacity	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	5 x 1mm ²	5 x 1mm ²
	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	2 x 4mm ² Multi-Strand	2 x 4mm ² Multi-Strand	2 x 4mm ² Multi-Strand	4 x 1.5mm ²	4 x 1.5mm ²
	2 x 2.5mm ²	2 x 2.5mm ²	3 x 2.5mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	3 x 2.5mm ²	3 x 2.5mm ²
	1 x 4mm ²	1 x 4mm ²	2 x 4mm ² Multi-Strand				1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand
Earth Terminal Capacity	5 x 1mm ²	5 x 1mm ²	9 x 1mm ²	6 x 1mm ²	6 x 1mm ²	6 x 1mm ²	6 x 1mm ²	6 x 1mm ²
	4 x 1.5mm ²	4 x 1.5mm ²	6 x 1.5mm ²	5 x 1.5mm ²	5 x 1.5mm ²	5 x 1.5mm ²	5 x 1.5mm ²	5 x 1.5mm ²
	2 x 2.5mm ²	2 x 2.5mm ²	4 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²
	1 x 4mm ²	1 x 4mm ²	2 x 4mm ² Multi-Strand	2 x 4mm ² Multi-Strand	2 x 4mm ² Multi-Strand	2 x 4mm ² Multi-Strand	2 x 4mm ² Multi-Strand	2 x 4mm ² Multi-Strand
Product Class 1	Must be earthed	Must be earthed	Must be earthed	Must be earthed	Must be earthed	Must be earthed	Must be earthed	Must be earthed
Ambient Operating Temperature	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C
Recommended Location	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only
Max installation Altitude	2000m	2000m	2000m	2000m	2000m	2000m	2000m	2000m
BS EN ISO Standard	BS 546	BS 546	BS EN 61558 - BS 4573	BS 1363	BS 1363	BS 1363	BS 1363	BS 1363
Cable outlet (min)						0.75mm ²		0.75mm ²
Cable outlet (max)						2.5mm ²		2.5mm ²
Additional Notes :								


 Cheriton Victorian <i>AB, PB, BC, SC</i>	<i>DP</i>	<i>DPN</i>	<i>DPNCO</i>	<i>45DP</i>	<i>45DPN</i>	<i>45VDPN</i>	<i>45DPNSS1</i>
Insert type	Rocker	Rocker & neon	Rocker, neon & cable outlet	Red rocker	Red rocker & neon	Vertical red rocker & neon	Red rocker, neon & socket
Plate material (see general notes)	Metal	Metal	Metal	Metal	Metal	Metal	Metal
Size (single) height	88mm	88mm	88mm	88mm	88mm		
Size (single) width	88mm	88mm	88mm	88mm	88mm		
Size (single) depth	8.5mm	8.5mm	8.5mm	8.5mm	8.5mm		
Size (double) height							
Size (double) width						86mm	146mm
Size (double) depth						8.5mm	8.5mm
Box fixing hole centres	60.3mm	60.3mm	60.3mm	60.3mm	60.3mm	120.6mm	120.6mm
Grid fixing hole centres	Grid fixing inserts are available on Cheriton Victorian plates. For full details refer to GRID-IT technical pages and GRID-IT catalogue						
Minimum wall box depth	25mm	25mm	25mm	46mm	46mm	47mm	47mm
Wattage							
Current rating	20amp	20amp	20amp	45amp	45amp	45amp	Switch 45amp; socket 13amp
Voltage	220/250V AC	220/250V AC	220/250V AC	220/250V AC	220/250V AC	220/250V AC	220/250V AC
Max load	20amps	20amp	20amps	45amp	45amps	45amp	Switch 45amp; socket 13amp
Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz
IP rating	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD
Poles	Double	Double	Double	Double	Double	Double	Double
Contact Gap Minimum	3mm	3mm	3mm	3mm	3mm	3mm	3mm
Terminal Capacity	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 6mm ²	3 x 6mm ²	3 x 6mm ²	3 x 6mm ²
	2 x 4mm ² Multi-Strand	2 x 4mm ² Multi-Strand	2 x 4mm ² Multi-Strand	2 x 10mm ²	2 x 10mm ²	2 x 10mm ²	2 x 10mm ²
	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 16mm ²	1 x 16mm ²	1 x 16mm ²	1 x 16mm ²
Earth Terminal Capacity	6 x 1mm ²	6 x 1mm ²	6 x 1mm ²	3 x 6mm ²	3 x 6mm ²	3 x 6mm ²	3 x 6mm ²
	5 x 1.5mm ²	5 x 1.5mm ²	5 x 1.5mm ²	2 x 10mm ²	2 x 10mm ²	2 x 10mm ²	2 x 10mm ²
	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	1 x 16mm ²	1 x 16mm ²	1 x 16mm ²	1 x 16mm ²
	2 x 4mm ² Multi-Strand	2 x 4mm ² Multi-Strand	2 x 4mm ² Multi-Strand				
	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²				
Product Class 1	Must be earthed	Must be earthed	Must be earthed	Must be earthed	Must be earthed	Must be earthed	Must be earthed
Ambient Operating Temperature	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C
Recommended Location	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only
Max installation Altitude	2000m	2000m	2000m	2000m	2000m	2000m	2000m
BS EN ISO Standard	BS EN 60669-1	BS EN 60669-1	BS EN 60669-1	BS EN 60669-1	BS EN 60669-1	BS EN 60669-1	BS 4177
Cable outlet (min)			0.75mm ²				
Cable outlet (max)			2.5mm ²				
Additional Notes :							


 Cheriton Victorian AB, PB, BC, SC	<i>TV</i>	<i>TV2</i>	<i>TVFM</i>	<i>TVI</i>	<i>TV+SAT</i>	<i>SAT</i>	<i>SATI</i>							
Insert type	Aerial socket	Aerial socket	Aerial socket	Aerial socket	Aerial socket	Aerial socket	Aerial socket							
Plate material (see general notes)	Metal	Metal	Metal	Metal	Metal	Metal	Metal							
Size (single) height	88mm	88mm	88mm	88mm	88mm	88mm	88mm							
Size (single) width	88mm	88mm	88mm	88mm	88mm	88mm	88mm							
Size (single) depth	8.5mm	8.5mm	8.5mm	8.5mm	8.5mm	8.5mm	8.5mm							
Size (double) height														
Size (double) width														
Size (double) depth														
Box fixing hole centres	60.3mm	60.3mm	60.3mm	60.3mm	60.3mm	60.3mm	60.3mm							
Grid fixing hole centres	Grid fixing inserts are available on Cheriton Victorian plates. For full details refer to GRID-IT technical pages and GRID-IT catalogue													
Minimum wall box depth	25mm	25mm	25mm	25mm	35mm	35mm	35mm							
Wattage														
Current rating														
Voltage														
Max load														
Hz														
IP rating	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD							
Poles														
Contact Gap Minimum														
Terminal Capacity														
Earth Terminal Capacity								5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²
								4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²
								3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²
								1 x 4mm ² Multi-Strand 1 x 6mm ²	1 x 4mm ² Multi-Strand 1 x 6mm ²	1 x 4mm ² Multi-Strand 1 x 6mm ²	1 x 4mm ² Multi-Strand 1 x 6mm ²	1 x 4mm ² Multi-Strand 1 x 6mm ²	1 x 4mm ² Multi-Strand 1 x 6mm ²	1 x 4mm ² Multi-Strand 1 x 6mm ²
Product Class 1	Must be earthed if supply cable is metallic													
Ambient Operating Temperature	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C							
Recommended Location	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only							
Max installation Altitude	2000m	2000m	2000m	2000m	2000m	2000m	2000m							
BS EN ISO Standard														
Cable outlet (min)														
Cable outlet (max)														
Additional Notes :	<p>Note Mains operated and extra low voltage products must not be installed in the same face plate aperture. When installing within the same back box , phase barriers MUST be used to separate the two voltages. See BS 7671 Wiring regulations for further details.</p>													

 Cheriton Victorian AB, PB, BC, SC	<i>DGTRI</i>	<i>DGTVF</i>	<i>DGTVM</i>	<i>DGSAT</i>	<i>DGENT</i>	<i>DGENT+TVF +TCS</i>	<i>TCM</i>	<i>TCS</i>	<i>RJ12</i>	<i>RJ12/2</i>	<i>RJ45</i>	<i>RJ45/2</i>
Insert type	Digital Aerial socket	Digital Aerial socket	Digital Aerial socket	Digital Aerial socket	Digital Aerial socket	Digital Aerial socket	LJ Telephone master socket	LJ Telephone slave socket	6 wire Telephone socket	6 wire double Telephone socket	8 wire data socket	8 wire double data socket
Plate material (see general notes)	Metal	Metal	Metal	Metal	Metal	Metal	Metal	Metal	Metal	Metal	Metal	Metal
Size (single) height	88mm	88mm	88mm	88mm	88mm		88mm	88mm	88mm	88mm	88mm	88mm
Size (single) width	88mm	88mm	88mm	88mm	88mm		88mm	88mm	88mm	88mm	88mm	88mm
Size (single) depth	8.5mm	8.5mm	8.5mm	8.5mm	8.5mm		8.5mm	8.5mm	8.5mm	8.5mm	8.5mm	8.5mm
Size (double) height						86mm						
Size (double) width						146mm						
Size (double) depth						8.5mm						
Box fixing hole centres	60.3mm	60.3mm	60.3mm	60.3mm	60.3mm	120.6mm	60.3mm	60.3mm	60.3mm	60.3mm	60.3mm	60.3mm
Grid fixing hole centres	Grid fixing inserts are available on Cheriton Victorian plates. For full details refer to GRID-IT technical pages and GRID-IT catalogue											
Minimum wall box depth	35mm	35mm	35mm	35mm	35mm	35mm	25mm	25mm	35mm	35mm	35mm	35mm
Wattage												
Current rating												
Voltage												
Max load												
Hz												
IP rating	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD
Poles												
Contact Gap Minimum												
Terminal Capacity												
Earth Terminal Capacity	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²
	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²
	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²
	1 x 4mm ² Multi-Strand 1 x 6mm ²	1 x 4mm ² Multi-Strand 1 x 6mm ²	1 x 4mm ² Multi-Strand 1 x 6mm ²	1 x 4mm ² Multi-Strand 1 x 6mm ²	1 x 4mm ² Multi-Strand 1 x 6mm ²	1 x 4mm ² Multi-Strand 1 x 6mm ²	1 x 4mm ² Multi-Strand 1 x 6mm ²	1 x 4mm ² Multi-Strand 1 x 6mm ²	1 x 4mm ² Multi-Strand 1 x 6mm ²	1 x 4mm ² Multi-Strand 1 x 6mm ²	1 x 4mm ² Multi-Strand 1 x 6mm ²	1 x 4mm ² Multi-Strand 1 x 6mm ²
Product Class 1	Must be earthed if supply cable is						Must be earthed if supply cable is metallic					
Ambient Operating Temperature	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C
Recommended Location	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only
Max installation Altitude	2000m	2000m	2000m	2000m	2000m	2000m	2000m	2000m	2000m	2000m	2000m	2000m
BS EN ISO Standard												
Cable outlet (min)												
Cable outlet (max)												
Additional Notes :	Note Mains operated and extra low voltage products must not be installed in the same face plate aperture. When installing within the same back box , phase barriers MUST be used to separate the two voltages. See BS 7671 Wiring regulations for further details.											


 Cheriton Victorian AB, PB, BC, SC	<i>P1X400</i>	<i>P2X400</i>	<i>P3X400</i>	<i>P4X400</i>	<i>P1X600</i>	<i>P1X1000</i>	<i>P1X200VA</i>	<i>P2X200VA</i>	<i>P1X300VA</i>
Insert type	Dimmer (resistive)*	Dimmer (resistive)*	Dimmer (resistive)*	Dimmer (resistive)*	Dimmer (resistive)*	Dimmer (resistive)*	Dimmer (inductive)*	Dimmer (inductive)*	Dimmer (inductive)*
Plate material (see general notes)	Metal	Metal	Metal	Metal	Metal	Metal	Metal	Metal	Metal
Size (single) height	88mm	88mm			88mm			88mm	88mm
Size (single) width	88mm	88mm			88mm			88mm	
Size (single) depth	8.5mm	8.5mm			8.5mm			8.5mm	
Size (double) height			86mm	86mm			86mm		
Size (double) width			146mm	146mm			146mm		
Size (double) depth			8.5mm	8.5mm			8.5mm		
Box fixing hole centres	60.3mm	60.3mm	120.6mm	120.6mm	60.3mm	120.6mm	60.3mm	60.3mm	60.3mm
Grid fixing hole centres	Grid fixing inserts are available on Cheriton Victorian plates. For full details refer to GRID-IT technical pages and GRID-IT catalogue								
Minimum wall box depth	35mm	35mm	35mm	35mm	35mm	35mm	35mm	35mm	35mm
Wattage	400w	400w	400w	300w	600w	1kw	200va (low voltage)	200va (low voltage) per gang	300 va (low voltage)
Current rating	1.66 amps	1.66amps per gang	1.66amps per gang	1.25amps per gang	2.5 amps	4.16amps	0.8 amps	0.8 amps	1.25 amps
Voltage	220/250V AC	220/250V AC	220/250V AC	220/250V AC	220/250V AC	220/250V AC	220/250V AC	220/250V AC	220/250V AC
Max load	400w resistive	400w resistive per gang	400w resistive per gang	300w resistive per gang	600w resistive	1kw resistive	200va (low voltage)	200va per gang (low voltage)	300va (low voltage)
Hz	50 Hz	50 Hz	50 Hz	50 Hz	50 Hz	50 Hz	50 Hz	50Hz	50 Hz
IP rating	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD
Poles	Single	Single	Single	Single	Single	Single	Single	1	Single
Contact Gap Minimum	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
Terminal Capacity	2 x 1mm ²	2 x 1mm ²	2 x 1mm ²	2 x 1mm ²	2 x 1mm ²	2 x 1mm ²	2 x 1mm ²	2 x 1mm ²	2 x 1mm ²
	2 x 1.5mm ²	2 x 1.5mm ²	2 x 1.5mm ²	2 x 1.5mm ²	2 x 1.5mm ²	2 x 1.5mm ²	2 x 1.5mm ²	2 x 1.5mm ²	2 x 1.5mm ²
Earth Terminal Capacity	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²
	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²
	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²
	1 x 4mm ² Multi-Strand 1 x 6mm ²	1 x 4mm ² Multi-Strand 1 x 6mm ²	1 x 4mm ² Multi-Strand 1 x 6mm ²	1 x 4mm ² Multi-Strand 1 x 6mm ²	1 x 4mm ² Multi-Strand 1 x 6mm ²	1 x 4mm ² Multi-Strand 1 x 6mm ²	1 x 4mm ² Multi-Strand 1 x 6mm ²	1 x 4mm ² Multi-Strand 1 x 6mm ²	1 x 4mm ² Multi-Strand 1 x 6mm ²
Product Class 1	When dimmer modules are fitted to a metal face plate, the face plate must be earthed								
Ambient Operating Temperature	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C
Recommended Location	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only
Max installation Altitude	2000m	2000m	2000m	2000m	2000m	2000m	2000m	2000m	2000m
BS EN ISO Standard	BS EN 60669-2-1	BS EN 60669-2-1	BS EN 60669-2-1	BS EN 60669-2-1	BS 5518			BS 5518	
Cable outlet (min)									
Cable outlet (max)									
Additional Notes :	<p>* Denotes LEADING EDGE TECHNOLOGY DIMMERS. Resistive dimmers are suitable for control of incandescent lamps. When dimming GU10 type mains halogen or linear halogen lamps the dimmers need to be derated by 25%. When used for dimming low voltage electronic halogen transformers, it must be noted that the dimmer controls the primary side of the transformer. It is important that you seek advice from the transformer manufacturer that their transformers are suitable to be dimmed by a leading edge type dimmer and that it is compatible with a Hamilton manufactured, resistive, leading edge dimmer. Inductive dimmers are suitable for dimming Laminated or Toroidal type low voltage halogen transformers only.</p>								

 Cheriton Victorian AB, PB, BC, SC	<i>P1XTE25</i>	<i>P2XTE25</i>	<i>P3XTE25</i>	<i>P4XTE25</i>	<i>1XTM25</i>	<i>2XTM25</i>	<i>3XTM25</i>	<i>4XTM25</i>	
Insert type	Dimmer (resistive and inductive)*	Dimmer (resistive and inductive)*	Dimmer (resistive and inductive)*	Dimmer (resistive and inductive)*	Dimmer (resistive and inductive)*	Dimmer (resistive and inductive)*	Dimmer (resistive and inductive)*	Dimmer (resistive and inductive)*	
Plate material (see general notes)	Metal	Metal	Metal	Metal	Metal	Metal	Metal	Metal	
Size (single) height	88mm	88mm			88mm	88mm			
Size (single) width	88mm	88mm			88mm	88mm			
Size (single) depth	8.5mm	8.5mm			8.5mm	8.5mm			
Size (double) height			86mm	86mm			86mm	86mm	
Size (double) width			146mm	146mm			146mm	146mm	
Size (double) depth			8.5mm	8.5mm			8.5mm	8.5mm	
Box fixing hole centres	60.3mm	60.3mm	120.6mm	120.6mm	60.3mm	60.3mm	120.6mm	120.6mm	
Grid fixing hole centres									
Minimum wall box depth	35mm	35mm	35mm	35mm	35mm	35mm	35mm	35mm	
Wattage	250W Resistive 210VA Inductive	250W Resistive 210VA Inductive	250W Resistive 210VA Inductive	250W Resistive 210VA Inductive	250W Resistive 210VA Inductive	250W Resistive 210VA Inductive	250W Resistive 210VA Inductive	250W Resistive 210VA Inductive	
Current rating	1.1 amps per gang	1.1 amps per gang	1.1 amps per gang	1.1 amps per gang	1.1 amps per gang	1.1 amps per gang	1.1 amps per gang	1.1 amps per gang	
Voltage	220/250V AC	220/250V AC	220/250V AC	220/250V AC	220/250V AC	220/250V AC	220/250V AC	220/250V AC	
Max load	250W Resistive 210VA Inductive	250W Resistive per gang 210VA Inductive per gang	250W Resistive per gang 210VA Inductive per gang	250W Resistive per gang 210VA Inductive per gang	250W Resistive 210VA Inductive	250W Resistive per gang 210VA Inductive per gang	250W Resistive per gang 210VA Inductive per gang	250W Resistive per gang 210VA Inductive per gang	
Hz	50Hz	50Hz	50Hz	50Hz	50Hz	50Hz	50Hz	50Hz	
IP rating	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	
Poles	Single	Single	Single	Single	n/a	n/a	n/a	n/a	
Contact Gap Minimum	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	
Terminal Capacity	2 x 1mm ² 2 x 1.5mm ²	2 x 1mm ² 2 x 1.5mm ²	2 x 1mm ² 2 x 1.5mm ²	2 x 1mm ² 2 x 1.5mm ²	2 x 1mm ² 2 x 1.5mm ²	2 x 1mm ² 2 x 1.5mm ²	2 x 1mm ² 2 x 1.5mm ²	2 x 1mm ² 2 x 1.5mm ²	
Earth Terminal Capacity	5 x 1mm ² 4 x 1.5mm ² 3 x 2.5mm ² 1 x 4mm ² Multi-Strand 1 x 6mm ²	5 x 1mm ² 4 x 1.5mm ² 3 x 2.5mm ² 1 x 4mm ² Multi-Strand 1 x 6mm ²	5 x 1mm ² 4 x 1.5mm ² 3 x 2.5mm ² 1 x 4mm ² Multi-Strand 1 x 6mm ²	5 x 1mm ² 4 x 1.5mm ² 3 x 2.5mm ² 1 x 4mm ² Multi-Strand 1 x 6mm ²	5 x 1mm ² 4 x 1.5mm ² 3 x 2.5mm ² 1 x 4mm ² Multi-Strand 1 x 6mm ²	5 x 1mm ² 4 x 1.5mm ² 3 x 2.5mm ² 1 x 4mm ² Multi-Strand 1 x 6mm ²	5 x 1mm ² 4 x 1.5mm ² 3 x 2.5mm ² 1 x 4mm ² Multi-Strand 1 x 6mm ²	5 x 1mm ² 4 x 1.5mm ² 3 x 2.5mm ² 1 x 4mm ² Multi-Strand 1 x 6mm ²	5 x 1mm ² 4 x 1.5mm ² 3 x 2.5mm ² 1 x 4mm ² Multi-Strand 1 x 6mm ²
	When dimmer modules are fitted to a metal face plate, the face plate must be earthed								
	Ambient Operating Temperature	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C
	Recommended Location	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only
Max installation Altitude	2000m	2000m	2000m	2000m	2000m	2000m	2000m	2000m	
BS EN ISO Standard	BS EN 60669-2-1	BS EN 60669-2-1	BS EN 60669-2-1	BS EN 60669-2-1	BS EN 60669-2-1	BS EN 60669-2-1	BS EN 60669-2-1	BS EN 60669-2-1	
Cable outlet (min)									
Cable outlet (max)									
Additional Notes :	* Denotes TRAILING EDGE TECHNOLOGY DIMMERS. Are suitable for control of both resistive and inductive loads. When used for dimming low voltage electronic halogen transformers, it must be noted that the dimmer controls the primary side of the transformer.								

 Cheriton Victorian AB, PB, BC, SC	<i>1XTS</i>	<i>2XTS</i>	<i>3XTS</i>	<i>4XTS</i>	<i>BPS</i>	<i>BPD</i>	<i>EURO2</i>	<i>EURO4</i>				
Insert type	Touch Slave	Touch Slave	Touch Slave	Touch Slave	Single blank plate	Double blank plate	Single plate with 2 x Eurodata cutout	Double plate with 4 x Eurodata cut out				
Plate material (see general notes)	Metal	Metal	Metal	Metal	Metal	Metal	Metal	Metal (2 part)				
Size (single) height	88mm	88mm			88mm			88mm				
Size (single) width	88mm	88mm			88mm							
Size (single) depth	8.5mm	8.5mm			8.5mm							
Size (double) height			86mm	86mm			86mm	86mm				
Size (double) width			146mm	146mm			146mm					
Size (double) depth			8.5mm	8.5mm			8.5mm					
Box fixing hole centres	60.3mm	60.3mm	120.6mm	120.6mm	60.3mm	120.6mm	60.3mm	120.6mm				
Grid fixing hole centres												
Minimum wall box depth									35mm	35mm	35mm	35mm
Wattage									N/A	N/A	N/A	N/A
Current rating									n/a	n/a	n/a	n/a
Voltage									220/250V AC	220/250V AC	220/250V AC	220/250V AC
Max load									N/A	N/A	N/A	N/A
Hz									50Hz	50Hz	50Hz	50Hz
IP rating									IP2XD	IP2XD	IP2XD	IP2XD
Poles									n/a	n/a	n/a	n/a
Contact Gap Minimum									n/a	n/a	n/a	n/a
Terminal Capacity									2 x 1mm ²	2 x 1mm ²	2 x 1mm ²	2 x 1mm ²
									2 x 1.5mm ²	2 x 1.5mm ²	2 x 1.5mm ²	2 x 1.5mm ²
Earth Terminal Capacity									5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²
	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²				
	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²				
	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand				
	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²				
Product Class 1	When slave modules are fitted to a metal face plate, the face plate must be earthed											
Ambient Operating Temperature	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C								
Recommended Location	Indoor use only	Indoor use only	Indoor use only	Indoor use only								
Max installation Altitude	2000m	2000m	2000m	2000m								
BS EN ISO Standard	BS EN 60669-2-1	BS EN 60669-2-1	BS EN 60669-2-1	BS EN 60669-2-1								
Cable outlet (min)												
Cable outlet (max)												
Additional Notes :							See Data & media catalogue for a full range of inserts.					

 Cheriton Victorian SB, BK	R21	R22	R23	R24	R26	R31	R32	BCP	TP
Insert type	2 way Rocker	2 way Rocker	2 way Rocker	2 way Rocker	2 way Rocker	Intermediate Rocker	Intermediate Rocker	Push to Make Rocker	Rocker
Plate material (see general notes)	Metal	Metal	Metal	Metal	Metal	Metal	Metal	Metal	Metal
Size (single) height	88mm	88mm	88mm			88mm	88mm	88mm	88mm
Size (single) width	88mm	88mm	88mm			88mm	88mm	88mm	88mm
Size (single) depth	8.5mm	8.5mm	8.5mm			8.5mm	8.5mm	8.5mm	8.5mm
Size (double) height				88mm	88mm				
Size (double) width				146mm	146mm				
Size (double) depth				8.5mm	8.5mm				
Box fixing hole centres	60.3mm	60.3mm	60.3mm	120.6mm	120.6mm	60.3mm	60.3mm	60.3mm	60.3mm
Grid fixing hole centres	Grid fixing inserts are available on Cheriton Victorian plates. For full details refer to GRID-IT technical pages and GRID-IT catalogue								
Minimum wall box depth	25mm	25mm	25mm	25mm	25mm	25mm	25mm	25mm	25mm
Wattage									
Current rating	10AX	10AX	10AX	10AX	10AX	10AX	10AX	10AX	10A
Voltage	220/250V AC	220/250V AC	220/250V AC	220/250V AC	220/250V AC	220/250V AC	220/250V AC	220/250V AC	220/250V AC
Max load	10amp inductive	10amp inductive	10amp inductive	10amp inductive	10amp inductive	10amp inductive	10amp inductive	10amp inductive	10amp resistive
Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz
IP rating	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD
Poles	Single	Single	Single	Single	Single	Single	Single	Single	Triple
Contact Gap Minimum	3mm	3mm	3mm	3mm	3mm	3mm	3mm	3mm	3mm
Terminal Capacity	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²
	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²
	1 x 2.5mm ²	1 x 2.5mm ²	1 x 2.5mm ²	1 x 2.5mm ²	1 x 2.5mm ²	1 x 2.5mm ²	1 x 2.5mm ²	1 x 2.5mm ²	1 x 2.5mm ²
	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand
Earth Terminal Capacity	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²
	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²
	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²
	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²
	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand
	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²
Product Class 1	Must be earthed	Must be earthed	Must be earthed	Must be earthed	Must be earthed	Must be earthed	Must be earthed	Must be earthed	Must be earthed
Ambient Operating Temperature	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C
Recommended Location	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only
Max installation Altitude	2000m	2000m	2000m	2000m	2000m	2000m	2000m	2000m	2000m
BS EN ISO Standard	BS EN 60669-1	BS EN 60669-1	BS EN 60669-1	BS EN 60669-1	BS EN 60669-1	BS EN 60669-1	BS EN 60669-1	BS EN 60669-1	BS EN 60669-1
Cable outlet (min)									
Cable outlet (max)									
Additional Notes :									


 Cheriton Victorian SB, BK	<i>S21</i>	<i>S22</i>	<i>S23</i>	<i>S24</i>	<i>S31</i>	<i>SDP</i>	<i>SBCP</i>	<i>SS1</i>	<i>SS2</i>	
Insert type	2 way Dolly	2 way Dolly	2 way Dolly	2 way Dolly	Intermediate dolly	Double Pole Dolly	Push to Make Dolly	Switched Socket	Switched Socket	
Plate material (see general notes)	Metal	Metal	Metal	Metal	Metal	Metal	Metal	Metal	Metal	
Size (single) height	88mm	88mm			88mm	88mm	88mm	88mm		
Size (single) width	88mm	88mm			88mm	88mm	88mm			
Size (single) depth	8.5mm	8.5mm			8.5mm	8.5mm	8.5mm			
Size (double) height			88mm	88mm					88mm	
Size (double) width			146mm	146mm					146mm	
Size (double) depth			8.5mm	8.5mm					8.5mm	
Box fixing hole centres	60.3mm	60.3mm	120.6mm	120.6mm	60.3mm	60.3mm	60.3mm	60.3mm	120.6mm	
Grid fixing hole centres	Grid fixing inserts are available on Cheriton Victorian plates. For full details refer to GRID-IT technical pages and GRID-IT catalogue									
Minimum wall box depth	25mm	25mm	25mm	25mm	25mm	25mm	25mm	35mm	35mm	
Wattage										
Current rating	20AX	20AX	20AX	20AX	20AX	20AX	10AX	13 amps	13 amps	
Voltage	220/250V AC	220/250V AC	220/250V AC	220/250V AC	220/250V AC	250v AC	250v AC	220/250V AC	220/250V AC	
Max load	20amp inductive	20amp inductive	20amp inductive	20amp inductive	20amp inductive	20amp inductive	10amp inductive	13amps	13amps	
Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz	
IP rating	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	
Poles	Single	Single	Single	Single	Single	Single	Single	Double	Double	
Contact Gap Minimum	3mm	3mm	3mm	3mm	3mm	3mm	3mm	3mm	3mm	
Terminal Capacity	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	4 x 2.5mm ²	4 x 2.5mm ²
	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	3 x 4mm ²	3 x 4mm ²
	2 x 2.5mm ²	2 x 2.5mm ²	2 x 2.5mm ²	2 x 2.5mm ²	2 x 2.5mm ²	2 x 2.5mm ²	2 x 2.5mm ²	2 x 2.5mm ²	2 x 6mm ² Multi-Strand	2 x 6mm ² Multi-Strand
	2 x 4mm ² Multi-Strand	2 x 4mm ² Multi-Strand	2 x 4mm ² Multi-Strand	2 x 4mm ² Multi-Strand	2 x 4mm ² Multi-Strand	2 x 4mm ² Multi-Strand	2 x 4mm ² Multi-Strand	2 x 4mm ² Multi-Strand	1 x 10mm ²	1 x 10mm ²
Earth Terminal Capacity	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²		
	6 x 1mm ²	6 x 1mm ²	6 x 1mm ²	6 x 1mm ²	6 x 1mm ²	6 x 1mm ²	6 x 1mm ²	6 x 1mm ²	4 x 2.5mm ²	4 x 2.5mm ²
	5 x 1.5mm ²	5 x 1.5mm ²	5 x 1.5mm ²	5 x 1.5mm ²	5 x 1.5mm ²	5 x 1.5mm ²	5 x 1.5mm ²	5 x 1.5mm ²	3 x 4mm ²	3 x 4mm ²
	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	2 x 6mm ² Multi-Strand	2 x 6mm ² Multi-Strand
	2 x 4mm ² Multi-Strand	2 x 4mm ² Multi-Strand	2 x 4mm ² Multi-Strand	2 x 4mm ² Multi-Strand	2 x 4mm ² Multi-Strand	2 x 4mm ² Multi-Strand	2 x 4mm ² Multi-Strand	2 x 4mm ² Multi-Strand	1 x 10mm ²	1 x 10mm ²
	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²		
Product Class 1	Must be earthed	Must be earthed	Must be earthed	Must be earthed	Must be earthed	Must be earthed	Must be earthed	Must be earthed	Must be earthed	
Ambient Operating Temperature	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5°C to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	
Recommended Location	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	
Max installation Altitude	2000m	2000m	2000m	2000m	2000m	2000m	2000m	2000m	2000m	
BS EN ISO Standard	BS EN 60669-1	BS EN 60669-1	BS EN 60669-1	BS EN 60669-1	BS EN 60669-1	BS EN 60669-1	BS EN 60669-1	BS 1363	BS 1363	
Cable outlet (min)										
Cable outlet (max)										
Additional Notes :										


 Cheriton Victorian SB, BK	<i>US2</i>	<i>US5</i>	<i>SHS</i>	<i>SP</i>	<i>SPN</i>	<i>SPNCO</i>	<i>FO</i>	<i>FOCO</i>
Insert type	Unswitched Socket	Unswitched Socket	Shaver Socket (Vertical)	Spur	Spur & Neon	Spur, neon, cable outlet	Fuse only	Fuse & cable outlet
Plate material (see general notes)	Metal	Metal	Metal	Metal	Metal	Metal	Metal	Metal
Size (single) height	88mm	88mm		88mm	88mm	88mm	88mm	88mm
Size (single) width	88mm	88mm		88mm	88mm	88mm	88mm	88mm
Size (single) depth	8.5mm	8.5mm		8.5mm	8.5mm	8.5mm	8.5mm	8.5mm
Size (double) height			146mm					
Size (double) width			88mm					
Size (double) depth			8.5mm					
Box fixing hole centres	60.3mm	60.3mm	120.6mm V	60.3mm	60.3mm	60.3mm	60.3mm	60.3mm
Grid fixing hole centres	Grid fixing inserts are available on Cheriton Victorian plates. For full details refer to GRID-IT technical pages and GRID-IT catalogue							
Minimum wall box depth	35mm	35mm	47mm	35mm	35mm	35mm	35mm	35mm
Wattage								
Current rating	2 amps	5 amps	20VA	13amps	13amps	13amps	13amps	13amps
Voltage	220/250V AC	220/250V AC	220/240V AC	250v AC	220/250V AC	220/250V AC	250v AC	250v AC
Max load	2amps	5amps	200/240v input; 115/230v output	13amps	13amps	13amps	13amps	13amps
Hz	50/60Hz	50/60Hz	50Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz
IP rating	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD
Poles	n/a	n/a	Single	Double	Double	Double		
Contact Gap Minimum	n/a	n/a	n/a	3mm	3mm	3mm	n/a	n/a
Terminal Capacity	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	5 x 1mm ²	5 x 1mm ²
	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	2 x 4mm ² Multi-Strand	2 x 4mm ² Multi-Strand	2 x 4mm ² Multi-Strand	4 x 1.5mm ²	4 x 1.5mm ²
	2 x 2.5mm ²	2 x 2.5mm ²	3 x 2.5mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	3 x 2.5mm ²	3 x 2.5mm ²
	1 x 4mm ²	1 x 4mm ²	2 x 4mm ² Multi-Strand				1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand
Earth Terminal Capacity			1 x 6mm ²				1 x 6mm ²	1 x 6mm ²
	5 x 1mm ²	5 x 1mm ²	9 x 1mm ²	6 x 1mm ²	6 x 1mm ²	6 x 1mm ²	6 x 1mm ²	6 x 1mm ²
	4 x 1.5mm ²	4 x 1.5mm ²	6 x 1.5mm ²	5 x 1.5mm ²	5 x 1.5mm ²	5 x 1.5mm ²	5 x 1.5mm ²	5 x 1.5mm ²
	2 x 2.5mm ²	2 x 2.5mm ²	4 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²
		2 x 4mm ² Multi-Strand	2 x 4mm ² Multi-Strand	2 x 4mm ² Multi-Strand	2 x 4mm ² Multi-Strand	2 x 4mm ² Multi-Strand	2 x 4mm ² Multi-Strand	2 x 4mm ² Multi-Strand
		1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²
Product Class 1	Must be earthed	Must be earthed	Must be earthed	Must be earthed	Must be earthed	Must be earthed	Must be earthed	Must be earthed
Ambient Operating Temperature	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C
Recommended Location	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only
Max installation Altitude	2000m	2000m	2000m	2000m	2000m	2000m	2000m	2000m
BS EN ISO Standard	BS 546	BS 546	BS EN 61558 - BS 4573	BS 1363	BS 1363	BS 1363	BS 1363	BS 1363
Cable outlet (min)						0.75mm ²		
Cable outlet (max)						2.5mm ²		
Additional Notes :								

It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.


Technical Info - Cher Vict SB, BK


March 2009


 Cheriton Victorian SB, BK	<i>DP</i>	<i>DPN</i>	<i>DPNCO</i>	<i>45DP</i>	<i>45DPN</i>	<i>45VDPN</i>	<i>45DPNSS1</i>
Insert type	Rocker	Rocker & neon	Rocker, neon & cable outlet	Red rocker	Red rocker & neon	Vertical red rocker & neon	Red rocker, neon & Socket
Plate material (see general notes)	Metal	Metal	Metal	Metal	Metal	Metal	Metal
Size (single) height	88mm	88mm	88mm	88mm	88mm		
Size (single) width	88mm	88mm	88mm	88mm	88mm		
Size (single) depth	8.5mm	8.5mm	8.5mm	8.5mm	8.5mm		
Size (double) height						146mm	88mm
Size (double) width						88mm	146mm
Size (double) depth						8.5mm	8.5mm
Box fixing hole centres	60.3mm	60.3mm	60.3mm	60.3mm	60.3mm	120.6mm \sqrt{V}	120.6mm
Grid fixing hole centres	Grid fixing inserts are available on Cheriton Victorian plates. For full details refer to GRID-IT technical pages and GRID-IT catalogue						
Minimum wall box depth	25mm	25mm	25mm	46mm	46mm	47mm	47mm
Wattage							
Current rating	20amp	20amp	20amp	45amp	45amp	45amp	Switch 45amp; socket 13amp
Voltage	220/250V AC	220/250V AC	220/250V AC	220/250V AC	220/250V AC	220/250V AC	220/250V AC
Max load	20amps	20amp	20amps	45amp	45amps	45amp	Switch 45amp; socket 13amp
Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz
IP rating	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD
Poles	Double	Double	Double	Double	Double	Double	Double
Contact Gap Minimum	3mm	3mm	3mm	3mm	3mm	3mm	3mm
Terminal Capacity	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 6mm ²	3 x 6mm ²	3 x 6mm ²	3 x 6mm ²
	2 x 4mm ² Multi-Strand	2 x 4mm ² Multi-Strand	2 x 4mm ² Multi-Strand	2 x 10mm ²	2 x 10mm ²	2 x 10mm ²	2 x 10mm ²
	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 16mm ²	1 x 16mm ²	1 x 16mm ²	1 x 16mm ²
Earth Terminal Capacity	6 x 1mm ²	6 x 1mm ²	6 x 1mm ²	3 x 6mm ²	3 x 6mm ²	3 x 6mm ²	3 x 6mm ²
	5 x 1.5mm ²	5 x 1.5mm ²	5 x 1.5mm ²	2 x 10mm ²	2 x 10mm ²	2 x 10mm ²	2 x 10mm ²
	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	1 x 16mm ²	1 x 16mm ²	1 x 16mm ²	1 x 16mm ²
	2 x 4mm ² Multi-Strand	2 x 4mm ² Multi-Strand	2 x 4mm ² Multi-Strand				
	1 x 6mm ²	1 x 6mm ²					
Product Class 1	Must be earthed	Must be earthed	Must be earthed	Must be earthed	Must be earthed	Must be earthed	Must be earthed
Ambient Operating Temperature	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C
Recommended Location	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only
Max installation Altitude	2000m	2000m	2000m	2000m	2000m	2000m	2000m
BS EN ISO Standard	BS EN 60669-1	BS EN 60669-1	BS EN 60669-1	BS EN 60669-1	BS EN 60669-1	BS EN 60669-1	BS 4177
Cable outlet (min)			0.75mm ²				
Cable outlet (max)			2.5mm ²				
Additional Notes :							


 Cheriton Victorian SB, BK	<i>TV</i>	<i>TV2</i>	<i>TVFM</i>	<i>TVI</i>	<i>TV+SAT</i>	<i>SAT</i>	<i>SATI</i>
Insert type	Aerial Socket	Aerial Socket	Aerial Socket	Aerial Socket	Aerial Socket	Aerial Socket	Aerial Socket
Plate material (see general notes)	Metal	Metal	Metal	Metal	Metal	Metal	Metal
Size (single) height	88mm	88mm	88mm	88mm	88mm	88mm	88mm
Size (single) width	88mm	88mm	88mm	88mm	88mm	88mm	88mm
Size (single) depth	8.5mm	8.5mm	8.5mm	8.5mm	8.5mm	8.5mm	8.5mm
Size (double) height							
Size (double) width							
Size (double) depth							
Box fixing hole centres	60.3mm	60.3mm	60.3mm	60.3mm	60.3mm	60.3mm	60.3mm
Grid fixing hole centres	Grid fixing inserts are available on Cheriton Victorian plates. For full details refer to GRID-IT technical pages and GRID-IT catalogue						
Minimum wall box depth	25mm	25mm	25mm	25mm	35mm	35mm	35mm
Wattage							
Current rating							
Voltage							
Max load							
Hz							
IP rating	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD
Poles							
Contact Gap Minimum							
Terminal Capacity							
Earth Terminal Capacity	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²
	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²
	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²
	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand
	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²
Product Class 1	Must be earthed if supply cable is metallic						
Ambient Operating Temperature	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C
Recommended Location	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only
Max installation Altitude	2000m	2000m	2000m	2000m	2000m	2000m	2000m
BS EN ISO Standard							
Cable outlet (min)							
Cable outlet (max)							
Additional Notes :	Note Mains operated and extra low voltage products must not be installed in the same face plate aperture. When installing within the same back box , phase barriers MUST be used to separate the two voltages. See BS 7671 Wiring regulations for further details.						

It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.

	<i>DGTRID</i>	<i>DGTVF</i>	<i>DGTVM</i>	<i>DGSAT</i>	<i>DGENT</i>	<i>DGENT+TVF +TCS</i>	<i>TCM</i>	<i>TCS</i>	<i>RJ12</i>	<i>RJ12/2</i>	<i>RJ45</i>	<i>RJ45/2</i>	
Insert type	Digital Aerial Socket	Digital Aerial Socket	Digital Aerial Socket	Digital Aerial Socket	Digital Aerial Socket	Digital Aerial Socket	LJ Telephone master Socket	LJ Telephone slave Socket	6 wire Telephone Socket	6 wire double Telephone Socket	8 wire data Socket	8 wire double data Socket	
Plate material (see general notes)	Metal	Metal	Metal	Metal	Metal	Metal	Metal	Metal	Metal	Metal	Metal	Metal	
Size (single) height	88mm	88mm	88mm	88mm	88mm		88mm	88mm	88mm	88mm	88mm	88mm	
Size (single) width	88mm	88mm	88mm	88mm	88mm		88mm	88mm	88mm	88mm	88mm	88mm	
Size (single) depth	8.5mm	8.5mm	8.5mm	8.5mm	8.5mm		8.5mm	8.5mm	8.5mm	8.5mm	8.5mm	8.5mm	
Size (double) height							88mm						
Size (double) width							146mm						
Size (double) depth							8.5mm						
Box fixing hole centres	60.3mm	60.3mm	60.3mm	60.3mm	60.3mm	120.6mm	60.3mm	60.3mm	60.3mm	60.3mm	60.3mm	60.3mm	
Grid fixing hole centres	Grid fixing inserts are available on Cheriton Victorian plates. For full details refer to GRID-IT technical pages and GRID-IT catalogue												
Minimum wall box depth	35mm	35mm	35mm	35mm	35mm	35mm	25mm	25mm	35mm	35mm	35mm	35mm	
Wattage													
Current rating													
Voltage													
Max load													
Hz													
IP rating	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	
Poles													
Contact Gap Minimum													
Terminal Capacity													
Earth Terminal Capacity	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	
	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	
	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	
	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand
Product Class 1	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	
Ambient Operating Temperature	Must be earthed if supply cable is metallic												
Recommended Location	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	
Max installation Altitude	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	
BS EN ISO Standard	2000m	2000m	2000m	2000m	2000m	2000m	2000m	2000m	2000m	2000m	2000m	2000m	
Cable outlet (min)													
Cable outlet (max)													
Additional Notes :	Note Mains operated and extra low voltage products must not be installed in the same face plate aperture. When installing within the same back box , phase barriers MUST be used to separate the two voltages. See BS 7671 Wiring regulations for further details.												


 Cheriton Victorian SB, BK	<i>P1X400</i>	<i>P2X400</i>	<i>P3X400</i>	<i>P4X400</i>	<i>P1X600</i>	<i>P1X1000</i>	<i>P1X200VA</i>	<i>P2X200VA</i>	<i>P1X300VA</i>
Insert type	Dimmer (resistive)*	Dimmer (resistive)*	Dimmer (resistive)*	Dimmer (resistive)*	Dimmer (resistive)*	Dimmer (resistive)*	Dimmer (inductive)*	Dimmer (inductive)*	Dimmer (inductive)*
Plate material (see general notes)	Metal	Metal	Metal	Metal	Metal	Metal	Metal	Metal	Metal
Size (single) height	88mm	88mm			88mm			88mm	88mm
Size (single) width	88mm	88mm			88mm			88mm	
Size (single) depth	8.5mm	8.5mm			8.5mm			8.5mm	
Size (double) height			88mm	88mm			88mm		
Size (double) width			146mm	146mm			146mm		
Size (double) depth			8.5mm	8.5mm			8.5mm		
Box fixing hole centres	60.3mm	60.3mm	120.6mm	120.6mm	60.3mm	120.6mm	60.3mm	60.3mm	60.3mm
Grid fixing hole centres	Grid fixing inserts are available on Cheriton Victorian plates. For full details refer to GRID-IT technical pages and GRID-IT catalogue								
Minimum wall box depth	35mm	35mm	35mm	35mm	35mm	35mm	35mm	35mm	35mm
Wattage	400w	400w	400w	300w	600w	1kw	200va (low voltage)	200va (low voltage) per gang	300 va (low voltage)
Current rating	1.66 amps	1.66amps per gang	1.66amps per gang	1.25amps per gang	2.5 amps	4.16amps	0.8 amps	0.8 amps	1.25 amps
Voltage	220/250V AC	220/250V AC	220/250V AC	220/250V AC	220/250V AC	220/250V AC	220/250V AC	220/250V AC	220/250V AC
Max load	400w resistive	400w resistive per gang	400w resistive per gang	300w resistive per gang	600w resistive	1kw resistive	200va (low voltage)	200va per gang (low voltage)	300va (low voltage)
Hz	50 Hz	50 Hz	50 Hz	50 Hz	50 Hz	50 Hz	50 Hz	50Hz	50 Hz
IP rating	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD
Poles	Single	Single	Single	Single	Single	Single	Single	1	Single
Contact Gap Minimum	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
Terminal Capacity	2 x 1mm ²	2 x 1mm ²	2 x 1mm ²	2 x 1mm ²	2 x 1mm ²	2 x 1mm ²	2 x 1mm ²	2 x 1mm ²	2 x 1mm ²
	2 x 1.5mm ²	2 x 1.5mm ²	2 x 1.5mm ²	2 x 1.5mm ²	2 x 1.5mm ²	2 x 1.5mm ²	2 x 1.5mm ²	2 x 1.5mm ²	2 x 1.5mm ²
Earth Terminal Capacity	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²
	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²
	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²
	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand
	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²
Product Class 1	When dimmer modules are fitted to a metal face plate, the face plate must be earthed								
Ambient Operating Temperature	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C
Recommended Location	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only
Max installation Altitude	2000m	2000m	2000m	2000m	2000m	2000m	2000m	2000m	2000m
BS EN ISO Standard	BS EN 60669-2-1	BS EN 60669-2-1	BS EN 60669-2-1	BS EN 60669-2-1	BS 5518			BS 5518	
Cable outlet (min)									
Cable outlet (max)									
Additional Notes :	* Denotes LEADING EDGE TECHNOLOGY DIMMERS. Resistive dimmers are suitable for control of incandescent lamps. When dimming GU10 type mains halogen or linear halogen lamps the dimmers need to be derated by 25%. When used for dimming low voltage electronic halogen transformers, it must be noted that the dimmer controls the primary side of the transformer. It is important that you seek advice from the transformer manufacturer that their transformers are suitable to be dimmed by a leading edge type dimmer and that it is compatible with a Hamilton manufactured, resistive, leading edge dimmer. Inductive dimmers are suitable for dimming Laminated or Toroidal type low voltage halogen transformers only.								

 Cheriton Victorian SB, BK	<i>P1XTE25</i>	<i>P2XTE25</i>	<i>P3XTE25</i>	<i>P4XTE25</i>	<i>1XTM25</i>	<i>2XTM25</i>	<i>3XTM25</i>	<i>4XTM25</i>
Insert type	Dimmer (resistive and inductive)	Dimmer (resistive and inductive)	Dimmer (resistive and inductive)	Dimmer (resistive and inductive)	Dimmer (resistive and inductive)	Dimmer (resistive and inductive)	Dimmer (resistive and inductive)	Dimmer (resistive and inductive)
Plate material (see general notes)	Metal	Metal	Metal	Metal	Metal	Metal	Metal	Metal
Size (single) height	88mm	88mm			88mm	88mm		
Size (single) width	88mm	88mm			88mm	88mm		
Size (single) depth	8.5mm	8.5mm			8.5mm	8.5mm		
Size (double) height			88mm	88mm			88mm	88mm
Size (double) width			146mm	146mm			146mm	146mm
Size (double) depth			8.5mm	8.5mm			8.5mm	8.5mm
Box fixing hole centres	60.3mm	60.3mm	120.6mm	120.6mm	60.3mm	60.3mm	120.6mm	120.6mm
Grid fixing hole centres								
Minimum wall box depth	35mm	35mm	35mm	35mm	35mm	35mm	35mm	35mm
Wattage	250W Resistive 210VA Inductive	250W Resistive 210VA Inductive	250W Resistive 210VA Inductive	250W Resistive 210VA Inductive	250W Resistive 210VA Inductive	250W Resistive 210VA Inductive	250W Resistive 210VA Inductive	250W Resistive 210VA Inductive
Current rating	1.1 amps per gang	1.1 amps per gang	1.1 amps per gang	1.1 amps per gang	1.1 amps per gang	1.1 amps per gang	1.1 amps per gang	1.1 amps per gang
Voltage	220/250V AC	220/250V AC	220/250V AC	220/250V AC	220/250V AC	220/250V AC	220/250V AC	220/250V AC
Max load	250W Resistive 210VA Inductive	250W Resistive per gang 210VA Inductive per gang	250W Resistive per gang 210VA Inductive per gang	250W Resistive per gang 210VA Inductive per gang	250W Resistive 210VA Inductive	250W Resistive per gang 210VA Inductive per gang	250W Resistive per gang 210VA Inductive per gang	250W Resistive per gang 210VA Inductive per gang
Hz	50Hz	50Hz	50Hz	50Hz	50Hz	50Hz	50Hz	50Hz
IP rating	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD
Poles	Single	Single	Single	Single	n/a	n/a	n/a	n/a
Contact Gap Minimum	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
Terminal Capacity	2 x 1mm ²	2 x 1mm ²	2 x 1mm ²	2 x 1mm ²	2 x 1mm ²	2 x 1mm ²	2 x 1mm ²	2 x 1mm ²
	2 x 1.5mm ²	2 x 1.5mm ²	2 x 1.5mm ²	2 x 1.5mm ²	2 x 1.5mm ²	2 x 1.5mm ²	2 x 1.5mm ²	2 x 1.5mm ²
Earth Terminal Capacity	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²
	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²
	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²
	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand
	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²
Product Class 1	When dimmer modules are fitted to a metal face plate, the face plate must be earthed							
Ambient Operating Temperature	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C
Recommended Location	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only
Max installation Altitude	2000m	2000m	2000m	2000m	2000m	2000m	2000m	2000m
BS EN ISO Standard	BS EN 60669-2-1	BS EN 60669-2-1	BS EN 60669-2-1	BS EN 60669-2-1	BS EN 60669-2-1	BS EN 60669-2-1	BS EN 60669-2-1	BS EN 60669-2-1
Cable outlet (min)								
Cable outlet (max)								
Additional Notes :	* Denotes TRAILING EDGE TECHNOLOGY DIMMERS. Are suitable for control of both resistive and inductive loads. When used for dimming low voltage electronic halogen transformers, it must be noted that the dimmer controls the primary side of the transformer.							

 Hamilton <i>Cheriton Victorian</i> SB, BK	<i>1XTS</i>	<i>2XTS</i>	<i>3XTS</i>	<i>4XTS</i>	<i>BPS</i>	<i>BPD</i>	<i>EURO2</i>	<i>EURO4</i>				
Insert type	Touch Slave	Touch Slave	Touch Slave	Touch Slave	Blanking Plate	Blanking Plate	Single plate with 2 x Eurodata cutout	Double plate with 4 x Eurodata cut out				
Plate material (see general notes)	Metal	Metal	Metal	Metal	Metal	Metal	Metal	Metal (2 part)				
Size (single) height	88mm	88mm			88mm		88mm					
Size (single) width	88mm	88mm			88mm							
Size (single) depth	8.5mm	8.5mm			8.5mm							
Size (double) height			88mm	88mm			88mm	88mm				
Size (double) width			146mm	146mm			146mm					
Size (double) depth			8.5mm	8.5mm			8.5mm					
Box fixing hole centres	60.3mm	60.3mm	120.6mm	120.6mm	60.3mm	120.6mm	60.3mm	120.6mm				
Grid fixing hole centres												
Minimum wall box depth	35mm	35mm	35mm	35mm								
Wattage	N/A	N/A	N/A	N/A								
Current rating	n/a	n/a	n/a	n/a								
Voltage	220/250V AC	220/250V AC	220/250V AC	220/250V AC								
Max load	N/A	N/A	N/A	N/A								
Hz	50Hz	50Hz	50Hz	50Hz								
IP rating	IP2XD	IP2XD	IP2XD	IP2XD								
Poles	n/a	n/a	n/a	n/a								
Contact Gap Minimum	n/a	n/a	n/a	n/a								
Terminal Capacity	2 x 1mm ² 2 x 1.5mm ²	2 x 1mm ² 2 x 1.5mm ²	2 x 1mm ² 2 x 1.5mm ²	2 x 1mm ² 2 x 1.5mm ²								
Earth Terminal Capacity	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²								
	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²								
	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²								
	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand								
	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²								
Product Class 1	When slave modules are fitted to a metal face plate, the face plate must be earthed											
Ambient Operating Temperature	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C								
Recommended Location	Indoor use only	Indoor use only	Indoor use only	Indoor use only								
Max installation Altitude	2000m	2000m	2000m	2000m								
BS EN ISO Standard	BS EN 60669-2-1	BS EN 60669-2-1	BS EN 60669-2-1	BS EN 60669-2-1								
Cable outlet (min)												
Cable outlet (max)												
Additional Notes :							See Data & media catalogue for a full range of inserts.					

 Cheriton Georgian	R21	R22	R23	R24	R26	R31	R32	BCP	TP	
Insert type	2 way Rocker	2 way Rocker	2 way Rocker	2 way Rocker	2 way Rocker	intermediate Rocker	Intermediate Rocker	Push to Make Rocker	Rocker	
Plate material (see general notes)	Metal	Metal	Metal	Metal	Metal	Metal	Metal	Metal	Metal	
Size (single) height	88mm	88mm	88mm			88mm	88mm	88mm	88mm	
Size (single) width	88mm	88mm	88mm			88mm	88mm	88mm	88mm	
Size (single) depth	10.8mm	10.8mm	10.8mm			10.8mm	10.8mm	10.8mm	10.8mm	
Size (double) height				86mm	86mm					
Size (double) width				146mm	146mm					
Size (double) depth				10.8mm	10.8mm					
Box fixing hole centres	60.3mm	60.3mm	60.3mm	120.6mm	120.6mm	60.3mm	60.3mm	60.3mm	60.3mm	
Grid fixing hole centres	Grid fixing inserts are available on Cheriton Georgian plates. For full details refer to GRID-IT technical pages and GRID-IT catalogue									
Minimum wall box depth	25mm	25mm	25mm	25mm	25mm	25mm	25mm	25mm	25mm	
Wattage										
Current rating	10AX	10AX	10AX	10AX	10AX	10AX	10AX	10AX	10A	
Voltage	220/250V AC	220/250V AC	220/250V AC	220/250V AC	220/250V AC	220/250V AC	220/250V AC	220/250V AC	220/250V AC	
Max load	10amp inductive	10amp inductive	10amp inductive	10amp inductive	10amp inductive	10amp inductive	10amp inductive	10amp inductive	10amp resistive	
Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz	
IP rating	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	
Poles	Single	Single	Single	Single	Single	Single	Single	Single	Triple	
Contact Gap Minimum	3mm	3mm	3mm	3mm	3mm	3mm	3mm	3mm	3mm	
Terminal Capacity	5 x 1mm ² 4 x 1.5mm ² 1 x 2.5mm ² 1 x 4mm ² Multi-Strand 1 x 6mm ²	5 x 1mm ² 4 x 1.5mm ² 1 x 2.5mm ² 1 x 4mm ² Multi-Strand 1 x 6mm ²	5 x 1mm ² 4 x 1.5mm ² 1 x 2.5mm ² 1 x 4mm ² Multi-Strand 1 x 6mm ²	5 x 1mm ² 4 x 1.5mm ² 1 x 2.5mm ² 1 x 4mm ² Multi-Strand 1 x 6mm ²	5 x 1mm ² 4 x 1.5mm ² 1 x 2.5mm ² 1 x 4mm ² Multi-Strand 1 x 6mm ²	5 x 1mm ² 4 x 1.5mm ² 1 x 2.5mm ² 1 x 4mm ² Multi-Strand 1 x 6mm ²	5 x 1mm ² 4 x 1.5mm ² 1 x 2.5mm ² 1 x 4mm ² Multi-Strand 1 x 6mm ²	5 x 1mm ² 4 x 1.5mm ² 1 x 2.5mm ² 1 x 4mm ² Multi-Strand 1 x 6mm ²	5 x 1mm ² 4 x 1.5mm ² 1 x 2.5mm ² 1 x 4mm ² Multi-Strand 1 x 6mm ²	5 x 1mm ² 4 x 1.5mm ² 1 x 2.5mm ² 1 x 4mm ² Multi-Strand 1 x 6mm ²
Earth Terminal Capacity	5 x 1mm ² 4 x 1.5mm ² 3 x 2.5mm ² 1 x 4mm ² Multi-Strand 1 x 6mm ²	5 x 1mm ² 4 x 1.5mm ² 3 x 2.5mm ² 1 x 4mm ² Multi-Strand 1 x 6mm ²	5 x 1mm ² 4 x 1.5mm ² 3 x 2.5mm ² 1 x 4mm ² Multi-Strand 1 x 6mm ²	5 x 1mm ² 4 x 1.5mm ² 3 x 2.5mm ² 1 x 4mm ² Multi-Strand 1 x 6mm ²	5 x 1mm ² 4 x 1.5mm ² 3 x 2.5mm ² 1 x 4mm ² Multi-Strand 1 x 6mm ²	5 x 1mm ² 4 x 1.5mm ² 3 x 2.5mm ² 1 x 4mm ² Multi-Strand 1 x 6mm ²	5 x 1mm ² 4 x 1.5mm ² 3 x 2.5mm ² 1 x 4mm ² Multi-Strand 1 x 6mm ²	5 x 1mm ² 4 x 1.5mm ² 3 x 2.5mm ² 1 x 4mm ² Multi-Strand 1 x 6mm ²	5 x 1mm ² 4 x 1.5mm ² 3 x 2.5mm ² 1 x 4mm ² Multi-Strand 1 x 6mm ²	5 x 1mm ² 4 x 1.5mm ² 3 x 2.5mm ² 1 x 4mm ² Multi-Strand 1 x 6mm ²
Product Class 1	Must be earthed	Must be earthed	Must be earthed	Must be earthed	Must be earthed	Must be earthed	Must be earthed	Must be earthed	Must be earthed	
Ambient Operating Temperature	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	
Recommended Location	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	
Max installation Altitude	2000m	2000m	2000m	2000m	2000m	2000m	2000m	2000m	2000m	
BS EN ISO Standard	BS EN 60669-1	BS EN 60669-1	BS EN 60669-1	BS EN 60669-1	BS EN 60669-1	BS EN 60669-1	BS EN 60669-1	BS EN 60669-1	BS EN 60669-1	
Cable outlet (min)										
Cable outlet (max)										
Additional Notes :										


 Cheriton Georgian	<i>S21</i>	<i>S22</i>	<i>S23</i>	<i>S24</i>	<i>S31</i>	<i>SDP</i>	<i>SBCP</i>	<i>SS1</i>	<i>SS2</i>
Insert type	2 way Dolly	2 way Dolly	2 way Dolly	2 way Dolly	Intermediate Dolly	Double Pole Dolly	Push to Make Dolly	Switched Socket	Switched Socket
Plate material (see general notes)	Metal	Metal	Metal	Metal	Metal	Metal	Metal	Metal	Metal
Size (single) height	88mm	88mm			88mm	88mm	88mm	88mm	
Size (single) width	88mm	88mm			88mm	88mm	88mm		
Size (single) depth	10.8mm	10.8mm			10.8mm	10.8mm	10.8mm		
Size (double) height			86mm	86mm					86mm
Size (double) width			146mm	146mm					146mm
Size (double) depth			10.8mm	10.8mm					10.8mm
Box fixing hole centres	60.3mm	60.3mm	120.6mm	120.6mm	60.3mm	60.3mm	60.3mm	60.3mm	120.6mm
Grid fixing hole centres	Grid fixing inserts are available on Cheriton Georgian plates. For full details refer to GRID-IT technical pages and GRID-IT catalogue								
Minimum wall box depth	25mm	25mm	25mm	25mm	25mm	25mm	25mm	35mm	35mm
Wattage									
Current rating	20AX	20AX	20AX	20AX	20AX	20AX	10AX	13 amps	13 amps
Voltage	220/250V AC	220/250V AC	220/250V AC	220/250V AC	220/250V AC	250v AC	250v AC	220/250V AC	220/250V AC
Max load	20amp inductive	20amp inductive	20amp inductive	20amp inductive	20amp inductive	20amp inductive	10amp inductive	13amps	13amps
Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz
IP rating	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD
Poles	Single	Single	Single	Single	Single	Single	Single	Double	Double
Contact Gap Minimum	3mm	3mm	3mm	3mm	3mm	3mm	3mm	3mm	3mm
Terminal Capacity	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	4 x 2.5mm ²	4 x 2.5mm ²
	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	3 x 4mm ²	3 x 4mm ²
	2 x 2.5mm ²	2 x 2.5mm ²	2 x 2.5mm ²	2 x 2.5mm ²	2 x 2.5mm ²	2 x 2.5mm ²	2 x 2.5mm ²	2 x 6mm ² Multi-Strand	2 x 6mm ² Multi-Strand
	2 x 4mm ² Multi-Strand	2 x 4mm ² Multi-Strand	2 x 4mm ² Multi-Strand	2 x 4mm ² Multi-Strand	2 x 4mm ² Multi-Strand	2 x 4mm ² Multi-Strand	2 x 4mm ² Multi-Strand	1 x 10mm ²	1 x 10mm ²
	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²		
Earth Terminal Capacity	6 x 1mm ²	6 x 1mm ²	6 x 1mm ²	6 x 1mm ²	6 x 1mm ²	6 x 1mm ²	6 x 1mm ²	4 x 2.5mm ²	4 x 2.5mm ²
	5 x 1.5mm ²	5 x 1.5mm ²	5 x 1.5mm ²	5 x 1.5mm ²	5 x 1.5mm ²	5 x 1.5mm ²	5 x 1.5mm ²	3 x 4mm ²	3 x 4mm ²
	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	2 x 6mm ² Multi-Strand	2 x 6mm ² Multi-Strand
	2 x 4mm ² Multi-Strand	2 x 4mm ² Multi-Strand	2 x 4mm ² Multi-Strand	2 x 4mm ² Multi-Strand	2 x 4mm ² Multi-Strand	2 x 4mm ² Multi-Strand	2 x 4mm ² Multi-Strand	1 x 10mm ²	1 x 10mm ²
	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²		
Product Class 1	Must be earthed	Must be earthed	Must be earthed	Must be earthed	Must be earthed	Must be earthed	Must be earthed	Must be earthed	Must be earthed
Ambient Operating Temperature	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5°C to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C
Recommended Location	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only
Max installation Altitude	2000m	2000m	2000m	2000m	2000m	2000m	2000m	2000m	2000m
BS EN ISO Standard	BS EN 60669-1	BS EN 60669-1	BS EN 60669-1	BS EN 60669-1	BS EN 60669-1	BS EN 60669-1	BS EN 60669-1	BS 1363	BS 1363
Cable outlet (min)									
Cable outlet (max)									
Additional Notes :									


	<i>US2</i>	<i>US5</i>	<i>SHS</i>	<i>SP</i>	<i>SPN</i>	<i>SPNCO</i>	<i>FO</i>	<i>FOCO</i>
Insert type	Unswitched Socket	Unswitched Socket	Shaver Socket (<i>Vertical</i>)	Spur	Spur & neon	Spur, neon, cable outlet	Fuse only	Fuse & cable outlet
Plate material (see general notes)	Metal	Metal	Metal	Metal	Metal	Metal	Metal	Metal
Size (single) height	88mm	88mm		88mm	88mm	88mm	88mm	88mm
Size (single) width	88mm	88mm		88mm	88mm	88mm	88mm	88mm
Size (single) depth	10.8mm	10.8mm		10.8mm	10.8mm	10.8mm	10.8mm	10.8mm
Size (double) height			146mm					
Size (double) width			86mm					
Size (double) depth			10.8mm					
Box fixing hole centres	60.3mm	60.3mm	120.6mm V	60.3mm	60.3mm	60.3mm	60.3mm	60.3mm
Grid fixing hole centres	Grid fixing inserts are available on Cheriton Georgian plates. For full details refer to GRID-IT technical pages and GRID-IT catalogue							
Minimum wall box depth	35mm	35mm	47mm	35mm	35mm	35mm	35mm	35mm
Wattage								
Current rating	2 amps	5 amps	20VA	13amps	13amps	13amps	13amps	13amps
Voltage	220/250V AC	220/250V AC	220/240V AC	250v AC	220/250V AC	220/250V AC	250v AC	250v AC
Max load	2amps	5amps	200/240v input; 115/230v output	13amps	13amps	13amps	13amps	13amps
Hz	50/60Hz	50/60Hz	50Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz
IP rating	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD
Poles	n/a	n/a	Single	Double	Double	Double		
Contact Gap Minimum	n/a	n/a	n/a	3mm	3mm	3mm	n/a	n/a
Terminal Capacity	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	5 x 1mm ²	5 x 1mm ²
	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	2 x 4mm ² Multi-Strand	2 x 4mm ² Multi-Strand	2 x 4mm ² Multi-Strand	4 x 1.5mm ²	4 x 1.5mm ²
	2 x 2.5mm ²	2 x 2.5mm ²	3 x 2.5mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	3 x 2.5mm ²	3 x 2.5mm ²
	1 x 4mm ²	1 x 4mm ²	2 x 4mm ² Multi-Strand				1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand
Earth Terminal Capacity			1 x 6mm ²				1 x 6mm ²	1 x 6mm ²
	5 x 1mm ²	5 x 1mm ²	9 x 1mm ²	6 x 1mm ²	6 x 1mm ²	6 x 1mm ²	6 x 1mm ²	6 x 1mm ²
	4 x 1.5mm ²	4 x 1.5mm ²	6 x 1.5mm ²	5 x 1.5mm ²	5 x 1.5mm ²	5 x 1.5mm ²	5 x 1.5mm ²	5 x 1.5mm ²
	2 x 2.5mm ²	2 x 2.5mm ²	4 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²
1 x 4mm ²	1 x 4mm ²	2 x 4mm ² Multi-Strand	2 x 4mm ² Multi-Strand	2 x 4mm ² Multi-Strand	2 x 4mm ² Multi-Strand	2 x 4mm ² Multi-Strand	2 x 4mm ² Multi-Strand	
Product Class 1	Must be earthed	Must be earthed	Must be earthed	Must be earthed	Must be earthed	Must be earthed	Must be earthed	Must be earthed
Ambient Operating Temperature	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C
Recommended Location	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only
Max installation Altitude	2000m	2000m	2000m	2000m	2000m	2000m	2000m	2000m
BS EN ISO Standard	BS 546	BS 546	BS EN 61558 - BS 4573	BS 1363	BS 1363	BS 1363	BS 1363	BS 1363
Cable outlet (min)						0.75mm ²		
Cable outlet (max)						2.5mm ²		
Additional Notes :								

It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.

Technical Info - Cher Georgian

March 2009


 Cheriton Georgian	<i>DP</i>	<i>DPN</i>	<i>DPNCO</i>	<i>45DP</i>	<i>45DPN</i>	<i>45VDPN</i>	<i>45DPNSS1</i>
Insert type	Rocker	Rocker & neon	Rocker, neon & cable outlet	Red rocker	Red rocker & neon	Vertical red rocker & neon	Red rocker, neon & socket
Plate material (see general notes)	Metal	Metal	Metal	Metal	Metal	Metal	Metal
Size (single) height	88mm	88mm	88mm	88mm	88mm		
Size (single) width	88mm	88mm	88mm	88mm	88mm		
Size (single) depth	10.8mm	10.8mm	10.8mm	10.8mm	10.8mm		
Size (double) height							
Size (double) width						86mm	146mm
Size (double) depth						10.8mm	10.8mm
Box fixing hole centres	60.3mm	60.3mm	60.3mm	60.3mm	60.3mm	120.6mmV	120.6mm
Grid fixing hole centres	Grid fixing inserts are available on Cheriton Georgian plates. For full details refer to GRID-IT technical pages and GRID-IT catalogue						
Minimum wall box depth	25mm	25mm	25mm	46mm	46mm	47mm	47mm
Wattage							
Current rating	20amp	20amp	20amp	45amp	45amp	45amp	Switch 45amp; socket 13amp
Voltage	220/250V AC	220/250V AC	220/250V AC	220/250V AC	220/250V AC	220/250V AC	220/250V AC
Max load	20amps	20amp	20amps	45amp	45amps	45amp	Switch 45amp; socket 13amp
Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz
IP rating	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD
Poles	Double	Double	Double	Double	Double	Double	Double
Contact Gap Minimum	3mm	3mm	3mm	3mm	3mm	3mm	3mm
Terminal Capacity	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 6mm ²	3 x 6mm ²	3 x 6mm ²	3 x 6mm ²
	2 x 4mm ² Multi-Strand	2 x 4mm ² Multi-Strand	2 x 4mm ² Multi-Strand	2 x 10mm ²	2 x 10mm ²	2 x 10mm ²	2 x 10mm ²
	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 16mm ²	1 x 16mm ²	1 x 16mm ²	1 x 16mm ²
Earth Terminal Capacity	6 x 1mm ²	6 x 1mm ²	6 x 1mm ²	3 x 6mm ²	3 x 6mm ²	3 x 6mm ²	3 x 6mm ²
	5 x 1.5mm ²	5 x 1.5mm ²	5 x 1.5mm ²	2 x 10mm ²	2 x 10mm ²	2 x 10mm ²	2 x 10mm ²
	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	1 x 16mm ²	1 x 16mm ²	1 x 16mm ²	1 x 16mm ²
	2 x 4mm ² Multi-Strand	2 x 4mm ² Multi-Strand	2 x 4mm ² Multi-Strand				
	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²				
Product Class 1	Must be earthed	Must be earthed	Must be earthed	Must be earthed	Must be earthed	Must be earthed	Must be earthed
Ambient Operating Temperature	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C
Recommended Location	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only
Max installation Altitude	2000m	2000m	2000m	2000m	2000m	2000m	2000m
BS EN ISO Standard	BS EN 60669-1	BS EN 60669-1	BS EN 60669-1	BS EN 60669-1	BS EN 60669-1	BS EN 60669-1	BS 4177
Cable outlet (min)				0.75mm ²			
Cable outlet (max)				2.5mm ²			
Additional Notes :							

 Cheriton Georgian	<i>TV</i>	<i>TV2</i>	<i>TVFM</i>	<i>TVI</i>	<i>TV+SAT</i>	<i>SAT</i>	<i>SATI</i>							
Insert type	Aerial socket	Aerial socket	Aerial socket	Aerial socket	Aerial socket	Aerial socket	Aerial socket							
Plate material (see general notes)	Metal	Metal	Metal	Metal	Metal	Metal	Metal							
Size (single) height	88mm	88mm	88mm	88mm	88mm	88mm	88mm							
Size (single) width	88mm	88mm	88mm	88mm	88mm	88mm	88mm							
Size (single) depth	10.8mm	10.8mm	10.8mm	10.8mm	10.8mm	10.8mm	10.8mm							
Size (double) height														
Size (double) width														
Size (double) depth														
Box fixing hole centres	60.3mm	60.3mm	60.3mm	60.3mm	60.3mm	60.3mm	60.3mm							
Grid fixing hole centres	Grid fixing inserts are available on Cheriton Georgian plates. For full details refer to GRID-IT technical pages and GRID-IT catalogue													
Minimum wall box depth	25mm	25mm	25mm	25mm	35mm	35mm	35mm							
Wattage														
Current rating														
Voltage														
Max load														
Hz														
IP rating	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD							
Poles														
Contact Gap Minimum														
Terminal Capacity														
Earth Terminal Capacity								5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²
								4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²
								3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²
								1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand
	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²							
Product Class 1	Must be earthed if supply cable is metallic													
Ambient Operating Temperature	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C							
Recommended Location	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only							
Max installation Altitude	2000m	2000m	2000m	2000m	2000m	2000m	2000m							
BS EN ISO Standard														
Cable outlet (min)														
Cable outlet (max)														
Additional Notes :	Note Mains operated and extra low voltage products must not be installed in the same face plate aperture. When installing within the same back box , phase barriers MUST be used to separate the two voltages. See BS 7671 Wiring regulations for further details.													

It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.

Technical Info - Cher Georgian


March 2009


	DGTRI	DGTVF	DGTVM	DGSAT	DGENT	DGENT+TVF +TCS	TCM	TCS	RJ12	RJ12/2	RJ45	RJ45/2												
Insert type	Digital Aerial socket	Digital Aerial socket	Digital Aerial socket	Digital Aerial socket	Digital Aerial socket	Digital Aerial socket	LJ Telephone master socket	LJ Telephone slave socket	6 wire Telephone socket	6 wire double Telephone socket	8 wire data socket	8 wire double data socket												
Plate material (see general notes)	Metal	Metal	Metal	Metal	Metal	Metal	Metal	Metal	Metal	Metal	Metal	Metal												
Size (single) height	88mm	88mm	88mm	88mm	88mm		88mm	88mm	88mm	88mm	88mm	88mm												
Size (single) width	88mm	88mm	88mm	88mm	88mm		88mm	88mm	88mm	88mm	88mm	88mm												
Size (single) depth	10.8mm	10.8mm	10.8mm	10.8mm	10.8mm		10.8mm	10.8mm	10.8mm	10.8mm	10.8mm	10.8mm												
Size (double) height							86mm																	
Size (double) width							146mm																	
Size (double) depth							10.8mm																	
Box fixing hole centres	60.3mm	60.3mm	60.3mm	60.3mm	60.3mm	120.6mm	60.3mm	60.3mm	60.3mm	60.3mm	60.3mm	60.3mm												
Grid fixing hole centres	Grid fixing inserts are available on Cheriton Georgian plates. For full details refer to GRID-IT technical pages and GRID-IT catalogue																							
Minimum wall box depth	35mm	35mm	35mm	35mm	35mm	35mm	25mm	25mm	35mm	35mm	35mm	35mm												
Wattage																								
Current rating																								
Voltage																								
Max load																								
Hz																								
IP rating	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD												
Poles																								
Contact Gap Minimum																								
Terminal Capacity																								
Earth Terminal Capacity													5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²
													4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²
													3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²
													1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand
Product Class 1	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²												
Ambient Operating Temperature	Must be earthed if supply cable is metallic																							
Recommended Location	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C												
Max installation Altitude	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only												
BS EN ISO Standard	2000m	2000m	2000m	2000m	2000m	2000m	2000m	2000m	2000m	2000m	2000m	2000m												
Cable outlet (min)																								
Cable outlet (max)																								
Additional Notes :	Note Mains operated and extra low voltage products must not be installed in the same face plate aperture. When installing within the same back box , phase barriers MUST be used to separate the two voltages. See BS 7671 Wiring regulations for further details.																							


It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.

Technical Info - Cher Georgian

March 2009

	<i>P1X400</i>	<i>P2X400</i>	<i>P3X400</i>	<i>P4X400</i>	<i>P1X600</i>	<i>P1X1000</i>	<i>P1X200VA</i>	<i>P2X200VA</i>	<i>P1X300VA</i>	
Insert type	Dimmer (resistive)*	Dimmer (resistive)*	Dimmer (resistive)*	Dimmer (resistive)*	Dimmer (resistive)*	Dimmer (resistive)*	Dimmer (resistive)*	Dimmer (inductive)*	Dimmer (inductive)*	Dimmer inductive)*
Plate material (see general notes)	Metal	Metal	Metal	Metal	Metal	Metal	Metal	Metal	Metal	Metal
Size (single) height	88mm	88mm				88mm				88mm
Size (single) width	88mm	88mm				88mm				88mm
Size (single) depth	10.8mm	10.8mm				10.8mm				10.8mm
Size (double) height			86mm	86mm			86mm			
Size (double) width			146mm	146mm			146mm			
Size (double) depth			10.8mm	10.8mm			10.8mm			
Box fixing hole centres	60.3mm	60.3mm	120.6mm	120.6mm	60.3mm	120.6mm	60.3mm	60.3mm	60.3mm	
Grid fixing hole centres	Grid fixing inserts are available on Cheriton Georgian plates. For full details refer to GRID-IT technical pages and GRID-IT catalogue									
Minimum wall box depth	35mm	35mm	35mm	35mm	35mm	35mm	35mm	35mm	35mm	35mm
Wattage	400w	400w	400w	300w	600w	1kw	200va (low voltage)	200va (low voltage) per gang	300 va (low voltage)	
Current rating	1.66 amps	1.66amps per gang	1.66amps per gang	1.25amps per gang	2.5 amps	4.16amps	0.8 amps	0.8 amps	1.25 amps	
Voltage	220/250V AC	220/250V AC	220/250V AC	220/250V AC	220/250V AC	220/250V AC	220/250V AC	220/250V AC	220/250V AC	
Max load	400w resistive	400w resistive per gang	400w resistive per gang	300w resistive per gang	600w resistive	1kw resistive	200va (low voltage)	200va per gang (low voltage)	300va (low voltage)	
Hz	50 Hz	50 Hz	50 Hz	50 Hz	50 Hz	50 Hz	50 Hz	50Hz	50 Hz	
IP rating	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	
Poles	Single	Single	Single	Single	Single	Single	Single	1	Single	
Contact Gap Minimum	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	
Terminal Capacity	2 x 1mm ²	2 x 1mm ²	2 x 1mm ²	2 x 1mm ²	2 x 1mm ²	2 x 1mm ²	2 x 1mm ²	2 x 1mm ²	2 x 1mm ²	2 x 1mm ²
	2 x 1.5mm ²	2 x 1.5mm ²	2 x 1.5mm ²	2 x 1.5mm ²	2 x 1.5mm ²	2 x 1.5mm ²	2 x 1.5mm ²	2 x 1.5mm ²	2 x 1.5mm ²	
Earth Terminal Capacity	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	
	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	
	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	
	1 x 4mm ² Multi-Strand 1 x 6mm ²	1 x 4mm ² Multi-Strand 1 x 6mm ²	1 x 4mm ² Multi-Strand 1 x 6mm ²	1 x 4mm ² Multi-Strand 1 x 6mm ²	1 x 4mm ² Multi-Strand 1 x 6mm ²	1 x 4mm ² Multi-Strand 1 x 6mm ²	1 x 4mm ² Multi-Strand 1 x 6mm ²	1 x 4mm ² Multi-Strand 1 x 6mm ²	1 x 4mm ² Multi-Strand 1 x 6mm ²	1 x 4mm ² Multi-Strand 1 x 6mm ²
Product Class 1	When dimmer modules are fitted to a metal face plate, the face plate must be earthed									
Ambient Operating Temperature	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C
Recommended Location	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only
Max installation Altitude	2000m	2000m	2000m	2000m	2000m	2000m	2000m	2000m	2000m	2000m
BS EN ISO Standard	BS EN 60669-2-1	BS EN 60669-2-1	BS EN 60669-2-1	BS EN 60669-2-1	BS 5518				BS 5518	
Cable outlet (min)										
Cable outlet (max)										
Additional Notes :	<p>* Denotes LEADING EDGE TECHNOLOGY DIMMERS. Resistive dimmers are suitable for control of incandescent lamps. When dimming GU10 type mains halogen or linear halogen lamps the dimmers need to be derated by 25%. When used for dimming low voltage electronic halogen transformers, it must be noted that the dimmer controls the primary side of the transformer. It is important that you seek advice from the transformer manufacturer that their transformers are suitable to be dimmed by a leading edge type dimmer and that it is compatible with a Hamilton manufactured, resistive, leading edge dimmer. Inductive dimmers are suitable for dimming Laminated or Toroidal type low voltage halogen transformers only.</p>									

	<i>P1XTE25</i>	<i>P2XTE25</i>	<i>P3XTE25</i>	<i>P4XTE25</i>	<i>1XTM25</i>	<i>2XTM25</i>	<i>3XTM25</i>	<i>4XTM25</i>
Insert type	Dimmer (resistive and inductive)*	Dimmer (resistive and inductive)*	Dimmer (resistive and inductive)*	Dimmer (resistive and inductive)*	Dimmer (resistive and inductive)*	Dimmer (resistive and inductive)*	Dimmer (resistive and inductive)*	Dimmer (resistive and inductive)*
Plate material (see general notes)	Metal	Metal	Metal	Metal	Metal	Metal	Metal	Metal
Size (single) height	88mm	88mm			88mm	88mm		
Size (single) width	88mm	88mm			88mm	88mm		
Size (single) depth	10.8mm	10.8mm			10.8mm	10.8mm		
Size (double) height			86mm	86mm			86mm	86mm
Size (double) width			146mm	146mm			146mm	146mm
Size (double) depth			10.8mm	10.8mm			10.8mm	10.8mm
Box fixing hole centres	60.3mm	60.3mm	120.6mm	120.6mm	60.3mm	60.3mm	120.6mm	120.6mm
Grid fixing hole centres								
Minimum wall box depth	35mm	35mm	35mm	35mm	35mm	35mm	35mm	35mm
Wattage	250W Resistive 210VA Inductive	250W Resistive 210VA Inductive	250W Resistive 210VA Inductive	250W Resistive 210VA Inductive	250W Resistive 210VA Inductive	250W Resistive 210VA Inductive	250W Resistive 210VA Inductive	250W Resistive 210VA Inductive
Current rating	1.1 amps per gang	1.1 amps per gang	1.1 amps per gang	1.1 amps per gang	1.1 amps per gang	1.1 amps per gang	1.1 amps per gang	1.1 amps per gang
Voltage	220/250V AC	220/250V AC	220/250V AC	220/250V AC	220/250V AC	220/250V AC	220/250V AC	220/250V AC
Max load	250W Resistive 210VA Inductive	250W Resistive per gang 210VA Inductive per gang	250W Resistive per gang 210VA Inductive per gang	250W Resistive per gang 210VA Inductive per gang	250W Resistive 210VA Inductive	250W Resistive per gang 210VA Inductive per gang	250W Resistive per gang 210VA Inductive per gang	250W Resistive per gang 210VA Inductive per gang
Hz	50Hz	50Hz	50Hz	50Hz	50Hz	50Hz	50Hz	50Hz
IP rating	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD	IP2XD
Poles	Single	Single	Single	Single	n/a	n/a	n/a	n/a
Contact Gap Minimum	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
Terminal Capacity	2 x 1mm ²	2 x 1mm ²	2 x 1mm ²	2 x 1mm ²	2 x 1mm ²	2 x 1mm ²	2 x 1mm ²	2 x 1mm ²
	2 x 1.5mm ²	2 x 1.5mm ²	2 x 1.5mm ²	2 x 1.5mm ²	2 x 1.5mm ²	2 x 1.5mm ²	2 x 1.5mm ²	2 x 1.5mm ²
Earth Terminal Capacity	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²
	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²
	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²
	1 x 4mm ² Multi-Strand 1 x 6mm ²	1 x 4mm ² Multi-Strand 1 x 6mm ²	1 x 4mm ² Multi-Strand 1 x 6mm ²	1 x 4mm ² Multi-Strand 1 x 6mm ²	1 x 4mm ² Multi-Strand 1 x 6mm ²	1 x 4mm ² Multi-Strand 1 x 6mm ²	1 x 4mm ² Multi-Strand 1 x 6mm ²	1 x 4mm ² Multi-Strand 1 x 6mm ²
Product Class 1	When dimmer modules are fitted to a metal face plate, the face plate must be earthed							
Ambient Operating Temperature	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C
Recommended Location	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only
Max installation Altitude	2000m	2000m	2000m	2000m	2000m	2000m	2000m	2000m
BS EN ISO Standard	BS EN 60669-2-1	BS EN 60669-2-1	BS EN 60669-2-1	BS EN 60669-2-1	BS EN 60669-2-1	BS EN 60669-2-1	BS EN 60669-2-1	BS EN 60669-2-1
Cable outlet (min)								
Cable outlet (max)								
Additional Notes :	* Denotes TRAILING EDGE TECHNOLOGY DIMMERS. Are suitable for control of both resistive and inductive loads. When used for dimming low voltage electronic halogen transformers, it must be noted that the dimmer controls the primary side of the transformer.							

	<i>1XTS</i>	<i>2XTS</i>	<i>3XTS</i>	<i>4XTS</i>	<i>BPS</i>	<i>BPD</i>	<i>EURO2</i>	<i>EURO4</i>
Insert type	Touch Slave	Touch Slave	Touch Slave	Touch Slave	Single blank plate	Double blank plate	Single plate with 2 x Eurodata cutout	Double plate with 4 x Eurodata cut out
Plate material (see general notes)	Metal	Metal	Metal	Metal	Metal	Metal	Metal	Metal (2 part)
Size (single) height	88mm	88mm			88mm			88mm
Size (single) width	88mm	88mm			88mm			88mm
Size (single) depth	10.8mm	10.8mm			10.8mm			10.8mm
Size (double) height			86mm	86mm			86mm	86mm
Size (double) width			146mm	146mm			146mm	146mm
Size (double) depth			10.8mm	10.8mm			10.8mm	10.8mm
Box fixing hole centres	60.3mm	60.3mm	120.6mm	120.6mm	60.3mm	120.6mm	60.3mm	120.6mm
Grid fixing hole centres								
Minimum wall box depth	35mm	35mm	35mm	35mm				
Wattage	N/A	N/A	N/A	N/A				
Current rating	n/a	n/a	n/a	n/a				
Voltage	220/250V AC	220/250V AC	220/250V AC	220/250V AC				
Max load	N/A	N/A	N/A	N/A				
Hz	50Hz	50Hz	50Hz	50Hz				
IP rating	IP2XD	IP2XD	IP2XD	IP2XD				
Poles	n/a	n/a	n/a	n/a				
Contact Gap Minimum	n/a	n/a	n/a	n/a				
Terminal Capacity	2 x 1mm ²	2 x 1mm ²	2 x 1mm ²	2 x 1mm ²				
	2 x 1.5mm ²	2 x 1.5mm ²	2 x 1.5mm ²	2 x 1.5mm ²				
Earth Terminal Capacity	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²	5 x 1mm ²
	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²	4 x 1.5mm ²
	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²	3 x 2.5mm ²
	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand	1 x 4mm ² Multi-Strand
	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²	1 x 6mm ²
Product Class 1	When slave modules are fitted to a metal face plate, the face plate must be earthed							
Ambient Operating Temperature	-5° to +40°C	-5° to +40°C	-5° to +40°C	-5° to +40°C				
Recommended Location	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only	Indoor use only
Max installation Altitude	2000m	2000m	2000m	2000m	2000m	2000m	2000m	2000m
BS EN ISO Standard	BS EN 60669-2-1	BS EN 60669-2-1	BS EN 60669-2-1	BS EN 60669-2-1				
Cable outlet (min)								
Cable outlet (max)								
Additional Notes :							See Data & media catalogue for a full range of inserts.	