

ROYAL PRESTIGE REVOLVING DOOR



Attention to Detail and Quality

Bespoke design

Royal Prestige revolving doors offer an unbeatable combination of custom design and attention to detail and quality. Using the very best materials and durable construction methods, these doors provide impressive, energy-efficient entrances to suit any building. All Prestige revolving doors feature an internal stainless steel framework for maximum strength and durability, allowing a much greater range of sizes than with an inferior aluminum framework. This framework can be overclad with a wide variety of materials to produce an outstanding finish. The Royal Prestige is available with 2, 3 or 4 door leaves and with diameters over 3000mm. All sizes are available with fully automatic operation and can be supplied with heights in excess of 9 metres. As an option the Circular Prestige revolvers can have a security function with swipe cards.

TECHNICAL DATA.

Product Reference:	ROYAL PRESTIGE REVOLVING DOOR
Material:	Glass Overclad stainless steel frame for added durability and strength
Number of wings:	Two Wing Three Wing Four Wing
Operation:	Fully Automatic Security mode with controlled access
Diameter:	3000mm+. Available in 1mm increments
Internal Height:	3000mm – 9000mm+. Available in 1mm increments
Clear Opening:	2060mm+* *Dependent on door configuration and diameter
Locking:	Automatic Manual

Glazing:	Singled Glazed/Double Glazed Clear Low Iron Coloured Fritted Special Glazing Options
Canopy:	50mm +. Available in 1mm increments Please contact Bauporte for minimum heights if lighting or hot air units are required.
Surface Finishes:	Stainless Steel Polyester Powder Coated Special Finishes on request
Accessories:	Night Security Screens or Night Security Wall Matting, Water Drainage Reservoir Heaters integrated into the mat well RC2, RC3, RC4 and PAS24:2016 Options Available
Push Bars:	Vertical or Horizontal Handles are available
Safety:	Designed, Manufactured and installed to EN 16005
Power Supply:	230 V/50 Hz
Drive Unit:	Canopy installation, minimum canopy height 350mm Underfloor Drive Unit Pit size 1200 x 400x400mm (L x W x D)
Warranties:	Two Years or Lifetime with service contract* *Please contact Bauporte for further information
Construction:	Fixed curved drum walls will be constructed from welded through stainless steel profiles, which are covered with 2mm aluminum sheeting or chosen special finish. Glazed curved drum walls formed from clear curved 12mm laminated glass in one piece over the full height of the door and divided by the midstyle. No bottom glazing profiles, the glazing fits directly into the floor construction. The rotating part will have four door leaves, constructed out of a welded through SS structure, which will be covered with aluminum sheets. In the center, there is a central post of Stainless steel connecting the top-part and bottom-part. Diameter post is 60m. Glass: clear flat 12mm toughened glass. The profiles around each door panel are 27mm high. Door leaves are provided with single brushes on all edges.

www.bauporte.com

BV Bauporte Design Entrances
Zandsteen 14, 2132 MR Hoofddorp,
Netherlands, Postbus 558,
2130 AN Hoofddorp
Tel: +31 (0)85 066 1203
Sales: sales@bauporte.com

Bauporte Doors UK Ltd
Office 212, Dowgate House,
14-16 Dowgate Hill, London
EC4R 2SU
Tel: +44 (0)20 3411 5023
Sales: sales@bauporte.com

Making an entrance 