

# Ecophon Solo Cloud

Solo Cloud is a free-hanging unit, offering high level design possibilities. Three different suspension systems offer opportunities to create several layers and angles. Suitable when the room volume should be maintained or when it's not possible to install a wall-to-wall ceiling.



# SYSTEM RANGE



| Size, mm       | 1200x553 | 2400x1106 |
|----------------|----------|-----------|
| Special Fixing | •        | •         |
| Thickness      | 40       | 40        |
| Inst. Diagr.   | M430     | M430      |

© Saint-Gobain Ecophon AB Ecophon Solo™ Cloud, 2023-10-16



Acoustic panel Solo Freedom in cloud shape



Suspension with Connect Adjustable wire hanger and Connect Absorber anchor

#### **Acoustic**



For acoustic data on the panel - please see Solo Rectangle.



# **Indoor Air Quality**

| Certificate / Label          | Plant |          |
|------------------------------|-------|----------|
| Eurofins Indoor Air Comfort® | IAC   | IAC Gold |
| French VOC                   | Α     | A+       |
| Finnish M1                   | •     | •        |









### **Environmental Footprint**

|                    | kg CO2 equiv/m² |
|--------------------|-----------------|
| Solo Freedom       | 8,41            |
| Solo Freedom/Plant | 5,21            |

life-cycle stages A1 to C4 from EPD, in conformity with ISO 14025 / EN 15804



# Circularity

| Minimum post-consumer recycled content | 57%              |
|--|------------------|
| Recyclability                          | Fully recyclable |



# Fire safety

| Country |            | Class    |
|---------|------------|----------|
| Europe  | EN 13501-1 | A2-s1,d0 |

The glass wool core of the tiles is tested and classified as non-combustible according to EN ISO 1182.



#### **Humidity Resistance**

| Product  |                          |
|----------|--------------------------|
| Standard | Class C, RH 95% and 30°C |
| Plant    | Class A, RH 70% and 25°C |

According to EN 13964:2014



# Visual appearance

White Frost, nearest NCS colour sample S 0500-N, 85% light reflectance. Gloss < 1.



#### Cleanability

Daily dusting and vacuum cleaning. Weekly wet wiping.

© Saint-Gobain Ecophon AB Ecophon Solo™ Cloud, 2023-10-16

# Accessibility



The tiles are demountable.



# Installation

Installed according to installation diagrams, installation guides and drawing aid. For information regarding minimum overall depth of system see quantity specification.




#### **Mechanical properties**

The tile can take both point loads and distributed loads. See Functional demands, Mechanical properties at www.ecophon.com.




# CE


Ecophon ceiling systems are CE marked according to the European harmonized standard EN13964:2014. CE marked construction products are covered by a Declaration of Performance (DOP) which enables customers and users to easily compare performance of products available on the European market.




QUANTITY SPECIFICATION (EXCL. WASTAGE)

|   |   | Size, mm |           |
|---|---|----------|-----------|
|   |   | 1200×553 | 2400×1106 |
| 1 | Solo Freedom                                  | -        | -         |
| 2 | Connect Adjustable wire hanger (Alt 1)        | -        | -         |
| 3 | Connect Covering cup (Alt 1, Optional)        | -        | -         |
| 4 | Connect Adjustable wire kit (Alt 1, Optional) | -        | -         |
| 5 | Connect Absorber anchor                       | -        | -         |
|   | $\Delta$ Min. overall depth of system: 140 mm | -        | -         |






Two types of Adjustable wire solutions



Panels can be suspended underneath each other



Panels can be installed in angles