

EMS DC022 (Entrance Matting Systems Debris Channel with 022 inserts) Aluminium Grid Entrance Matting

TYPICAL SPECIFICATION

N10 General Fixtures/Furnishings/Equipment **300** Entrance Matting **40** Miscellaneous Fittings

Reference	EMS DC022
Height	12mm or 16mm
Insert	<p>Heavy ribbed Polypropylene. Colours: Anthracite, Black, Grey, Tan</p> 
Installation	Recessed in matwell or surface-laid with ramp frame

DETAILED SPECIFICATION

Reference	EMS DC022
Conformity	Manufactured to ISO9001:2008. Conforms to current BS8300 DDA Regulations
Grid Construction	Aluminium – minimum 95% recycled content in closed construction format
Insert	Heavy ribbed polypropylene. Colours: Anthracite, Black, Grey, Tan BRE A+ rating
Height	12mm or 16mm
Module Size	EMS panels are manufactured specifically to customer requirements. Panel lengths upto 4000mm left to right as required
Fire Rating	Hot Metal Nut BS4790:1987 (1996)
Installation	Recessed in matwell or surface-laid with ramp frame
Anodising Options	Aluminium grid can be anodised black, gold, gun metal grey or bronze

Description

EMS Debris Channel aluminium grid entrance matting is a primary matting system for specification in commercial applications where the removal of footborne dirt is essential. EMS products are manufactured for high traffic areas such as hotels, retail stores, shopping centres, schools, hospitals and airports to name a few.

The matting is bespoke made. Each front to back panel has a male and female edge which lock together. Any left to right size can be achieved by simply butting the panels together. No T-Bar is required. All EMS matting systems come with a 20 year guarantee and interchangeable infills.

Entrance Matting Systems

Unit 12 -14 Freiston Enterprise Park, Boston, Lincolnshire PE22 0JZ

T: +44 (0) 1205 761757

F: +44 (0) 1205 761811

E: info@entrance-matting.com

W: www.entrance-matting.com