# Product Data Sheet April 2016

## **Spectraplan D Membrane**

/ (• **DOI**vmeric

Excellence in Polymer Technology

### Non Reinforced TPE Membrane

#### **Product Details**

Thickness	1.5mm	
Length	10m, 25m	
Width	0.75m	
Colour	Light Grey	
Material	TPE	
Reinforcement	None	

#### Introduction

Spectraplan D membrane is a non-reinforced TPE membrane for detailing on Spectraplan roof systems. The membrane offers excellent flexibility allowing the material to be formed easily into intricate details ensuring the roof installation is fully waterproofed. Spectraplan D Membrane is adhered to suitable substrates using Spectraplan TPE Contact Adhesive. All overlaps and joints with are heated welded using suitable hot-air welding equipment.

Spectraplan D membrane can be used to waterproof the joints between Spectraplan membrane coated metal flashing sections and gutter joints or used to form complex details such as pipe penetrations or external corners.

Colour	Width	Length	Item Number	
Light Grey	0.75m	10m	44440008	
Light Grey	0.75m	25m	44440005	

### **Further Product Information**

**Spectraplan D Membrane Roll Sizes** 

Full product literature and technical sheets are available as downloads from our website: www.ikopolymeric.com or on request by email: polymeric.marketing@iko.com

Whilst every care is taken to see that the information given in this literature is correct and up to date it is not intended to form part of any contract or give rise to any collateral liability, which is hereby specifically excluded. Intending purchasers of our materials should therefore verify with the company whether any changes in our specification or application details or otherwise have taken place since this literature was issued.



Company Registered in England No. 2678296 - Registered Office: Appley Lane North, Appley Bridge, Wigan, Lancashire, WN6 9AB

IKO Polymeric Coney Green Road, Clay Cross, Chesterfield, S45 9HZ Tel: 01257 488 000 Sales: polymeric.sales.uk@iko.com Technical: polymeric.technical.uk@iko.com



## Features & Benefits

- Excellent flexibility for complex detailing \_\_\_\_\_\_
- Excellent UV resistance and durability
- Excellent mechanical properties
  and product performance
- Efficient and safe installation
- Secure seam welding quality