



COMPLIANCE DATASHEET

Styccobond F49

Hybrid pressure sensitive adhesive



Tested to the standards of the International Marine Organisation and approved for use in marine floor installations

Identification of Hazards: This product is classified as hazardous according to Regulation EC 1272/2008. Obtain the relevant Safety Data Sheets and follow the advice given.

Indoor Air Quality (VOC)

Not tested

LEED

VOC test according to South Coast Air Quality Management District Rule #1168

In house testing to ASTM D2369 Standard Test Method for Volatile Content of Coatings and Adhesives: VOC emissions met

VOC level (g/l less water)

2.00

VOC limit (g/l less water)

50

BREEAM; BS EN 13999-1:2013

In-house testing to the test method described in BS EN 13999 parts 2-4

Product does not contain carcinogenic or sensitising volatile substances

Life Cycle Assessment (LCA)

LCA according to ISO 14040/44: EPD according to EN 15804

Functional unit (FU) 1kg product; cradle - gate

Model EPD available on request.

REACH Directive 1907/2006/EC

Product does not contain any SVHC in concentrations greater than 0.1% (w/w)

Explosive Precursors EU Regulation 98/2013

Product does not contain explosive precursors above the limit values laid in Annex I of the regulation.

Air Pollution Control (Volatile Organic Compounds) Regulations – Hong Kong

Not tested.

