

ACOUSTIC PRODUCTS

TOPAKUSTIK ACOUSTIC PLANKS

K13/170 NBS STYLE TECHNICAL SPECIFICATION

ACOUSTIC PLANKS TO: _____

Refer to drawings: _____

Manufacturer and reference: **Topakustik** acoustic planks, design reference by
Acoustic Products Ltd
139 Tankerton Road
Whitstable
Kent
CT5 2AW
Tel 01227 281140
Fax 01227 281141
Email enquiries@acoustic-products.co.uk

Panel Substrate: 16 mm thick DIN B2 non fire rated MDF/16 mm thick DIN B1 fire retardant
MDF/DIN A1 "RESAP" gypsum chipboard non combustible composite

Front Surface Finish:veneer with DIN B2 non fire rated factory
applied lacquer finish/DIN B1 fire retardant factory applied
lacquer finish

Factory spray painted to RAL/NCS colour reference

Melamine colour/design reference

Laminate colour/design reference

Edges: Long edges tongued and grooved, ends square cut in raw
MDF/"RESAP"

Rear: Black acoustic fleece on rear surface covering rear perforations

Plank sizes & quantities: (DIN B2 MDF in 128 mm cover width x
2050, 2600, 2780, 3640 or 4080 mm lengths + or -2 mm/DIN B1 MDF in 128 mm cover width x
2780, 3640 or 4080 mm lengths + or -2 mm/DIN A1 "RESAP" in 128 mm cover width x 2550 or
2950 mm lengths + or - 2 mm, cut to specific lengths + or - 0.3 mm per 1000 mm in the factory
subject to waste surcharge).

Acoustic Insulation: 30 mm thick mineral wool (40-60 kgs/cu M, 2.5-3.75 pcf) behind panels

Installation: Method of fixing panels & support framework: in accordance with
manufacturer's recommendations