

# Technical Data Sheet

## ALBANY WOODCARE – ADVANCED

Albany ADVANCED Durable Woodstain is ideal for interior and exterior use on doors, windows and conservatories. It can be applied to bare and previously stained wood. Suitable for joinery such as windows, doors, fascia boards, garden furniture and cladding. Albany ADVANCED's microporous properties allows the wood to "breathe", resisting cracking, blistering and peeling.

For maximum protection use with Albany ORIGINAL (1 coat Albany ORIGINAL, 2 coats Albany ADVANCED).

For new, bare or untreated wood applying preserver is recommended.

### AVAILABILITY

Colour Range Refer to Albany Woodcare literature.

Packaging 1, 2.5 and 5 litres.

### PROPERTIES

Drying Time Under normal drying conditions touch dry 4-6 hours and recoatable 16-24 hours.

Do not apply in adverse weather conditions.

Finish Satin

Composition  
Pigment  
Binder: Alkyd Resin  
Solvent: Dearomatised white spirit

Spreading Rate 15m<sup>2</sup> per litre, depending on the nature and porosity of the timber

Wet Film Thickness 67 microns.

Dry Film Thickness 31 microns.

Flash Point 45°C (113°F) Closed Cup

VOC Content EU Limit Value for this product (Cat A/e): 400 g/l (2010).  
This product contains max 400 g/l VOC.  
HIGH VOC CONTENT 25-50%.

Product Limitations Do not apply if there is a risk of rain. Do not apply when air or substrate temperatures are likely to fall below 10°C or above 25°C or when the relative humidity is above 80% during application or the drying period.  
Do not use on substrates previously coated with water repellent preservative treatments. The use of linseed oil putty or other, non-setting compounds are not recommended with our Albany Woodcare products. Albany ADVANCED Durable Woodstain is supplied ready to use and should not be thinned.

### PREPARATION

General Timber All surfaces must be clean, dry and free from loose and flaking material. Old paint and varnish should be completely removed. Ensure that all timbers to be treated are sound, dry and free from dirt, dust, grease or any other surface contaminants. Treat any mould or lichen with Albany Fungicidal Wash. Softwood intended for exterior use which has not already been pre-treated should first be given a coat of clear preservative. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre 1960s paint surfaces over wood and metal as they may contain harmful lead.

New Timber All surfaces must be sound, suitably dry and free from anything that could interfere with the adhesion of the material to be applied. It is recommended that preserver be applied to any bare or untreated wood in the direction of the grain, before applying Albany ADVANCED. Allow 16-24 hours before overcoating.

---

## ALBANY WOODCARE – ADVANCED

Previously Painted	<p>All surfaces must be sound, suitably dry and free from anything that could interfere with the adhesion of the material to be applied.</p> <p>Remove any defects such as flaking or cracked woodstain / varnish and fill any crack or joints with wood filler. Should be primed with Albany ORIGINAL.</p>
<b>COATING SYSTEM</b>	<p>Apply 2-3 coats on its own. Can be used as a system with Albany Woodcare ORIGINAL (1 coat Albany ORIGINAL, 2 coats Albany ADVANCED).</p>
<b>APPLICATION</b>	<p>Stir well before use, Apply by brush, working the material well into the timber along the grain.</p>
<b>CLEANING</b>	<p>Clean equipment immediately after use with Albany Brush Cleaner or White Spirit</p>
<b>MAINTENANCE INFORMATION FOR CDM FILE</b>	<p>Maintenance requirement can be indicated by lightening of colour, reduction in sheen or a loss of water repellence.</p> <p>All defective/peeling coatings must be removed. Grey exposed timber surfaces must be thoroughly sanded back and cleaned. If there are any growths, these must be removed and treated with Albany Fungicidal Solution.</p> <p>Ensure surfaces are washed with a warm water and liquid detergent solution to remove any surface dirt, rinse with clean water and allow to dry before overcoating</p>
<b>HEALTH AND SAFETY</b>	<p>Please refer to the Safety, Health and Environmental Information on the container. Take special precautions during the surface preparation of pre 1960's painted surfaces as they may contain harmful lead. For further information contact the Customer Relations Team. When preparing all surfaces avoid the inhalation of dust and/or metal particles. Wear a suitable facemask. Material Safety Data Sheets for this and all other Albany products are freely available from the place of purchase or the address below. Store in secure dry conditions between 10°C and 40°C and inaccessible to children or animals. Containers should be kept closed during storage. Do not empty into drains, watercourses or access routes to septic tanks.</p>
<b>GENERAL INFORMATION</b>	<p>Apply all products in accordance with BS 6150: 2019 Code of practice for painting of buildings and BS 8000: Part 12: 1989 Code of practice for decorative wallcoverings and painting. Under normal and frost free conditions this product will remain usable for up to two years if stored correctly and unopened.</p> <p>Every care is taken to ensure that all information provided on this Technical Data Sheet is accurate. C Brewer &amp; Sons Ltd are unable to guarantee results as it has no control over the conditions under which its products are applied.</p> <p>Before using this product, please ensure you have the latest information.</p> <p>For help or more information contact:</p> <p><b>Brewers</b> Tel <b>01323 411080</b> E-mail <b>enquiries@brewers.co.uk</b> Website <b>www.brewers.co.uk</b></p>

This information is correct at date of issue April 2024