

Opening Doors Worldwide!

Sliding Door Drive
SLIDEDOOR Win Drive 2201 Frameless



★★★★★
TORMAX
AUTOMATIC

For more information on TORMAX visit www.barbourproductsearch.info



Absolute transparency in the entrance area

All-glass sliding doors for the most challenging design and aesthetic applications are now possible with the Win Drive 2201 frameless mounting kit.

The black anodised suspension system completely disappears into the drive unit cover (100 mm installation height).

The stylish transparency of the all-glass solution creates a totally new sensation of space in the door area.



Application

- All-glass sliding doors in commercial, private and public buildings
- Modern architecture indoors and outdoors

Advantages

- Complete transparency in the door area
- No visible obstructions created by profiles
- Supports innovative building design
- Meets the most stringent architectural demands for ambitious projects
- The frameless mounting kit is based on the proven Win Drive 2201 sliding door drive
- The sliding door drive requires an installation height of only 100 mm

Special functions

- Adjustable force
- Emergency opening and closing function
- Display of operation hours, opening cycles and fault recording
- System messages (door status, lock status, faults etc.)
- Bell and light activation
- Manual operation for servicing and cleaning purposes

Accessories/Options

- TORMAX control panel with 5 operating modes and fault display
- Mode selector covering 3 operating modes
- Battery-powered emergency opening / emergency power supply
- Emergency opening with spring force or rubber string
- Electro-mechanical locking with status monitoring
- Interior and exterior manual disengagement


Standards

- CE conformity
- ISO certified
- EN 12100-1, EN 12100-2, EN 60335-1, EN-61000-6-2, EN 61000-6-3

Technical data

System length	min. 1706 mm ¹ min. 1766 mm ²
Passage width	800–2200 mm ¹ 800–2900 mm ²
Passage height	max. 2700 mm
Header cross-section (H × T)	100 × 142 mm
Max. leaf weight ³	≤ 1 × 120 kg ¹ ≤ 2 × 100 kg ²
Leaf width ratio (B:H)	min. 1:5
Opening speed ⁴	0–60 cm/s ¹ 16–160 cm/s ²
Hold-open time	0,5–120 s
Power connection	115 VAC/60 Hz or 230 VAC/50 Hz, 160 VA
Sensor supply Lock supply	24 VDC / 1,0 A 12 VDC
Protection class	IP20
Operating modes	Off / Auto / Auto reduced opening / Exit / Open
7 Inputs	activators (2), key switch (1), safety devices (2), programmable inputs (2)
3 Outputs	electric lock controls (2), programmable output (1)
Courses of motion and power	freely adjustable
Ambient temperature	–20 °C to 50 °C
Glass	10 mm or 12 mm toughened safety glass (laminated sa- fety glass, LSG)

¹Single-leaf ²Double-leaf ³Higher weights possible (slow speed, little activation only) ⁴ max. speeds dependent upon the weight of the leaf and the prevailing regulations



★★★★★
TORMAX
AUTOMATIC

TORMAX
Landert Motoren AG
CH-8180 Bülach-Zürich
www.tormax.com
info@tormax.com

TORMAX is a division
and a registered
trademark of
Landert Motoren AG

For more information on TORMAX visit www.barbourproductsearch.info