

LOW VOLTAGE WC FLUSHVALVE KIT

With Mains PSU

WC03-013

The DVS WC no-touch flushing system is an electronically operated drop valve which replaces the traditional siphon and delivers a WRAS Approved 4L single flush from the cistern to the lavatory bowl.

PRODUCT NUMBER

WC03-013 WC Flushvalve Kit

TECHNICAL DATA

Flushvalve:

Weight	1.05 kg
Material	ABS Plastic
Power supply	Through WC control box
Outlet size	1½"
Internal overflow	Yes
Type of operation	Programmable sensor operation
Type of mounting	WC flush valve
Functional principle	Electronic self closing
Failsafe close	Yes




Control Box:

Weight	1 kg
Material	ABS Plastic
Run Times	*Please refer to AC02-037 Tech spec sheet*
Power source	6V DC Mains PSU
IP rating	54
Amps	0.14A (MAX)
Voltage	6V DC

Sensor:

Material	316 Stainless Steel
Surface finish	Brushed
Gross weight	0.2 kg
Operation type	A.IR (Active Infrared) touch-free
Overall dimensions	60mm (L) x Ø50mm
Thread diameter	Ø26.44mm (¾"BSP)
Type of mounting	Wall mounted (Ø27mm drill hole required)

For Adjustable sensor settings please refer to **AC02-037** Tech spec sheet.
(Contact Dart Valley Systems)



ALL DIMENSIONS IN MM

2018-09-06, Dart Valley Systems

