






## Oplia dB

Oplia dB is a smooth laminated finish providing enhanced sound attenuation performance for improving the privacy between adjacent spaces.

## Key Features

- Excellent level of sound attenuation: up to 41 dB
- High light reflectance: 86%
- Better finish and more durable edges
- ISO 5 / A+
- Ideal for individual offices

Edge Detail	Board	Tegular24	Tegular15
			
<b>Thickness (mm)</b>	19	19	19
<b>Modules (mm)</b>	600 x 600 ..... 3191M	600 x 600 ..... 3192M	600 x 600 ..... 2095M
<b>Suspension Systems</b>	Gridline 24 Butt Cut / Joggled Prelude 24 Sixty <sup>2</sup>	Gridline 24 Butt Cut / Joggled Prelude 24 Sixty <sup>2</sup>	Gridline 15 Butt Cut / Joggled Interlude HRC Silhouette

## Sustainability



39



A+



EN 13964 / E1



## Colour

Global white

## Acoustics



EN ISO 354  
& EN ISO 11654



EN ISO 10848-2  
& EN ISO 717-1



EN ISO 140-3  
& EN ISO 717-1

Hz  $\alpha_p$

	$\alpha_w$	$D_{nfw}$	$R_w$	Class	NRC	125	250	500	1000	2000	4000
Board, Tegular24, Tegular15	0.60(H)	41 dB	21 dB	C	0.65	0.30	0.40	0.55	0.70	0.85	0.95

## Fire Reaction



Euroclass A2-s1, d0  
EN 13501-1

## Performances & Features



86%



95% RH



30 Year  
System  
Guarantee



7.6 Kg/m<sup>2</sup>



ISO 5



ISO 14644-1



BIM  
READY

If you would like to order a sample or have any queries about this product please contact our Technical Sales Team on **0800 371 849** or email [enquiries@zentia.com](mailto:enquiries@zentia.com)

TDS 171.2.03.24