

Bardon Supercolour™ product information



A range of red/rustic coloured asphalt products based around BS/EN Close, dense and medium graded standard mixtures. The product can be used in any application appropriate to the standard mixture but particularly where colour differentiation is deemed an important aspect such as for; private drives, cycle-ways, pedestrian areas, residential roads etc.

There are three colour grades:

1. **Supercolour:** Basic level of pigmentation.
2. **Supercolour Advanced:** Increased level of pigmentation for deeper colour saturation.
3. **Supercolour Extra:** Uses a complementary coloured aggregate for a longer lasting colour effect.

Applications

- Residential roads
- Cycleways
- Car parks
- Pedestrian areas.

Layer

Surface course, thickness appropriate to the grade used and as described in BS594987.



Bardon Supercolour™ product information

Sustainability and local sourcing

Energy use: Aggregate Industries is at the forefront of sustainability and has committed to reduce carbon emissions by 20% by 2012 based on a 2008 base line.

Recyclable: 100% of the product can be recycled thus reducing the amount of material that is sent to landfill.

Manufacturing location: Produced in the UK, under strict environmental and social legislation.

Responsible sourcing: Aggregate Industries is the first company in the world to achieve a BES 6001:2008 Responsible Sourcing Certificate from BRE Global. Products are assessed on:

- quality management
- environmental management
- health and safety management
- greenhouse gas emissions
- minimising raw material usage
- labour practice
- biodiversity
- community engagement.

Bardon Supercolour is certified as EXCELLENT under the BES 6001 standard.

Aggregate

Bardon Supercolour is available using a range of standard aggregates appropriate to the BS/EN mixture selected. For a longer lasting colour then the Permanent grade should be selected; this will ensure that a red aggregate is used if available and appropriate to the specification of polished stone valve.

Binder

All grades appropriate to the BS/EN mixture selected are available, although it is recommended that the harder grades should be specified to provide maximum durability. Workability enhancers can be added if required.

Samples

Samples of the product can be provided however it is stressed that pigmentation will vary over time and that the samples provided are approximations of the finished appearance. Specifically they will not represent the colour of the material after trafficking and weathering.

Manufacturing standard

All Aggregate Industries' products are manufactured in accordance with ISO 9001 and Highway Sector Scheme 14 with factory compliance to ISO 14001.

Policies

Aggregate Industries' policies on the environment and community, health and safety and sustainable solutions for different product applications can be viewed on our website www.aggregate.com

Health and safety: COSHH data

Full COSHH data on Bardon Asphalt products is available on request. Please call the technical helpline on 0845 600 0860.

Technical support

Detailed guidance and assistance with the preparation of specification and use of Bardon Asphalt products is available through the sales office. A free technical service is also available.

For further information, please refer to Bardon Asphalt technical services on 0845 600 0860 or email: techhelp@aggregate.com

Bardon Hill, Coalville
Leicestershire LE67 1TL

www.aggregate.com



A member of the Holcim Group