

AGGREGATE INDUSTRIES

Landscaping

Charcon StoneMaster® block paving Life®

54%[†] non-primary materials



A revolutionary range of flag and block paving with all the inherent beauty of indigenous stone.

- Fine sandstone mix replicating natural sandstone and granite
- Three stunning shades of grey and buff replicating natural granite and yorkstone
- Pencil chamfer for enhanced aesthetics and protection against laying damage
- Guaranteed minimum 47% reclaimed and recycled material
- UK produced for nationwide stock availability
- More economical than natural stone for a cost effective solution
- Fixed sizes for ease of design
- Has a permeable option in the range.

Installation

Please lay using blocks from various packs so that different shades are chosen. This ensures that a natural colour variation is achieved much like that found in natural stone areas.

Applications

StoneMaster block paving is suitable for all pedestrian areas and town centres and areas subject to vehicular overrun. Refer to our technical

department for further guidance on suitability for given applications. For correct choice of block thickness to suit your application, refer to BS7533 Part 1 and 7.

Manufacturing standard

StoneMaster block paving is manufactured using a semi-dry process and is manufactured in accordance with and complies with all relevant sections of BS EN 1338: Precast Concrete Block Paving – requirements and test methods.

Aggregate Industries fully operates an accredited Quality Assurance scheme, certified to BS EN 9001:2008 which is independently and regularly assessed by BSI (British Standards Institution). All Charcon manufacturing sites are also certified to BS EN 14001 Environmental Management Systems.

Performance with slip resistance

Unpolished slip resistance values, when tested in accordance with BS EN 1338, are available on request. All Aggregate Industries block paving is classified as having a low potential for slip i.e. a USRV of greater than 40.


Polished slip resistance values can be provided on request.



Complementary products

StoneMaster flag paving and Charcon kerb.

Colour swatches



1. Light Buff
2. Medium Buff
3. Dark Buff
4. Light Grey
5. Medium Grey
6. Dark Grey

[†] Represents non-primary material within the complete mix design.

StoneMaster block paving

Size (mm)	600x200	300x300	300x200	200x200	200x100	100x100
Thickness (mm)	80	80	80	80	80	80
Weight (kg)	21	16.5	11.0	7.3	3.8	1.7
Units/m ² (approx)	8.33	11.11	17	25	50	100
No. per pack	36	54	108	160	320	560
M ² /pack	4.32	4.86	6.46	6.40	6.40	5.60
Pack weight (T)	0.76	0.89	1.18	1.17	1.16	1.00
Colour available	Db, Dg	Mb, Mg	Lb, Lg	Db, Dg	Mb, Mg	Lb, Lg
Chamfered	Yes	Yes	Yes	Yes	Yes	Yes

Db - Dark Buff / Mb - Medium Buff / Lb - Light Buff / Dg - Dark Grey / Mg - Medium Grey / Lg - Light Grey
All on a made to order basis.

Available as an Infiltra concrete block permeable paver (CBPP) in 200x100x80 size on made to order basis.



Q24. For NBS clauses, refer to Aggregate Industries technical services

Charcon StoneMaster® block paving

Sustainability and local sourcing

Energy use: Aggregate Industries is at the forefront of sustainability and has committed to reduce carbon emissions by 20% by 2016 based on a 2012 base line.

Recyclable: 100% of the product can be recycled thus reducing the amount of material that is sent to landfill.

Manufacturing location: produced in the UK, with locally sourced materials under strict environmental and social legislation, for local supply.

Responsible sourcing: Aggregate Industries is the first company in the world to achieve accreditation to the BES 6001 Framework Standard for the Responsible Sourcing of Construction Products. Aggregate Industries has achieved an 'Excellent' rating for major product groups. The BES 6001 standard assesses:

- quality management
- environmental management
- health and safety management
- a range of social and environmental issues.

Life

Life is our range of sustainable products and services. For more information please visit www.aggregate.com/life

Key aggregates and recycled content

Locally sourced specialist sand face mix and standard back mix with over 47% reclaimed and recycled material content.

Generic green guide rating*

Concrete block pavers, CBP (80mm) over prepared recycled sub-base - **A rated.**

Concrete block pavers, CBP (80mm) over prepared sub-base - **B rated.**

Policies

Aggregate Industries' policies on the environment and community, health and safety and sustainable solutions for different product applications can be viewed on our website www.aggregate.com

Design and installation

For pavement design guidance refer to BS 7533 Parts 1 and 7. For successful installation refer to BS 7533 Part 3. For specific design, installation and maintenance guidance, please contact our technical department on 01335 372222.

StoneMaster should be laid from a minimum of 3-5 packs to prevent colour banding.

Maintenance and cleaning

Aggregate Industries can supply on request advice on specific stain removal and general maintenance, suitable cleaning products and referrals to specialist cleaning companies.

COSHH data

Full COSHH data on the Charcon range of products is available on request. Please call the technical helpline on 01335 372222.

Technical support

Detailed guidance and assistance with the preparation of specification of the Charcon range of hard landscaping products, including model clauses, is available through the sales office. A free technical design service is also available.

For further information, please refer to our technical services on 01335 372222.

*Ratings based upon generic green guide values (2009) supplied by BRE Global Ltd, www.thegreenguide.co.uk

Hulland Ward, Ashbourne,
Derbyshire DE6 3ET

Tel: 01335 372222

Fax: 01335 370074

www.aggregate.com

