

## Landscaping

# Charcon Courtstone® flag paving



Faithfully replicating natural Caithness stone paving, Courtstone's detailed riven profile is derived from natural stone masters.

- Sizing reflects quarried flagstone sizes
- Extremely durable
- Deep charcoal colour replicates that of natural Caithness stone paving
- Non-slip riven finish
- Ideal for urban pavements, shopping precincts and areas with occasional car, HGV or mechanical sweeper overrun.

### Manufacturing standard

Courtstone flag paving is manufactured using a wet pressed process in moulds mastered from original Scottish Caithness stone and is manufactured in accordance with and complies with all relevant sections of BS EN 1339: Precast Concrete Flags – requirements and test methods.

Aggregate Industries fully operates an accredited Quality Assurance scheme, certified to BS EN 9001:2008 which is independently and regularly assessed by BSI (British Standards Institution). All Charcon manufacturing sites are also certified to BS EN 14001 Environmental Management Systems.

### Performance with slip resistance

Not applicable. Due to riven surface slip resistance is deemed satisfactory to BS EN 1339.

### Complementary products

Designed for use with Cairnhill kerb and can be used to contrast Moordale paving.



### Colour swatch



1. Charcoal

### Applications

Courtstone flag paving is suitable for high volume pedestrian areas, town centres, shopping precincts and footways as well as occasional car or mechanical sweeper overrun, footways with cars and HGV vehicle or service areas. Refer to technical department for advice on applications – Tel: 01335 372222. For correct choice of flag size to suit your application, refer to BS7533 Part 8.

### Courtstone flag paving

Size (mm)	900x600	750x600	600x600	600x450	450x450
Finish	Riven	Riven	Riven	Riven	Riven
Thickness (mm)	63	63	63	63	63
Weight (kg)	83.3	71.3	58.7	45.3	30.0
Units/m <sup>2</sup> (approx)	1.85	2.22	2.78	3.70	4.94
No. per pack	15	15	15	15	30
M <sup>2</sup> /pack (approx)	8.11	6.76	5.40	4.05	6.07
Pack weight (T)	1.25	1.07	0.88	0.68	0.90
Colour available	Ch	Ch	Ch	Ch	Ch
Chamfered	No	No	No	No	No

Ch - Charcoal



Q25. For NBS clauses, refer to Aggregate Industries technical services

# Charcon Courtstone® flag paving

## Sustainability and local sourcing

**Energy use:** Aggregate Industries is at the forefront of sustainability and has committed to reduce carbon emissions by 20% by 2016 based on a 2012 base line.

**Recyclable:** 100% of the product can be recycled thus reducing the amount of material that is sent to landfill.

**Manufacturing location:** Produced in the UK, with locally sourced materials under strict environmental and social legislation, for local supply.

**Responsible sourcing:** Aggregate Industries is the first company in the world to achieve a BES 6001:2008 Responsible Sourcing Certificate from BRE Global. Products are assessed on:

- quality management
- environmental management
- health and safety management
- greenhouse gas emissions
- minimising raw material usage
- labour practice
- biodiversity
- community engagement.

## Key aggregate and recycled content

Courtstone flag paving is manufactured using whinstone aggregates. It is made in a wet pressed process in moulds mastered from original Scottish Caithness stone.

## Generic green guide rating\*

Concrete paving flags (60mm with a prepared recycled sub-base) - **A+ rated.**

Concrete paving flags (60mm with a prepared sub-base) - **A rated.**

## Policies

Aggregate Industries' policies on the environment and community, health and safety and sustainable solutions for different product applications can be viewed on our website [www.aggregate.com](http://www.aggregate.com)

## Design and installation

For pavement design guidance refer to BS 7533 Parts 8. For successful installation refer to BS 7533 Part 4. For specific design, installation and maintenance guidance, please contact our technical department on 01335 372222.

## Maintenance and cleaning

Aggregate Industries can supply on request advice on specific stain removal and general maintenance, suitable cleaning products and referrals to specialist cleaning companies.

## COSHH data

Full COSHH data on the Charcon range of products is available on request. Please call the technical helpline on 01335 372222.

## Technical support

Detailed guidance and assistance with the preparation of specification of the Charcon range of hard landscaping products, including model clauses, is available through the sales office. A free technical design service is also available.

**For further information, please refer to our technical services on 01335 372222.**

\*Ratings based upon generic green guide values (2009) supplied by BRE Global Ltd, [www.thegreenguide.co.uk](http://www.thegreenguide.co.uk)

Hulland Ward, Ashbourne,  
Derbyshire DE6 3ET

Tel: 01335 372222

Fax: 01335 370074

[www.aggregate.com](http://www.aggregate.com)

