

SPECIFICATION SHEET: S029

SUBLINE CUBICLE RANGE

POSTFORMED CUBICLE SYSTEM



Detailed Product Specification

This elegant system is suitable for dry change areas and washrooms.

Facias:	38mm thick moisture resistant or standard core of medium density fibreboard (MDF) faced with 1mm high pressure laminate, postformed on vertical edges. Option of high density chipboard or WBP plywood to allow for concealed high strength fixings.
Doors and partitions:	18mm thick moisture resistant or standard core of medium density fibreboard (MDF) faced with 1mm high pressure laminate (HPL), edged with 2mm ABS or square as face.
Top Rail:	Angled aluminium top rail provides additional strength and stability and is bonded and mechanically fixed to fascia panels and postformed headrail.
Door Latch/Indicator Bolt:	Robust easy action door latch. Emergency exterior opening facility. Cubicle occupied indicator. Incorporates satin anodised aluminium rubber buffer for quiet door closure.
Door Hinge:	Each door fitted with 2 heavy-duty hinges, incorporating anti-finger trap and anti-lift off design. Door can be adjustable to door open/close/ajar, and open inward or out.
Pedestal Leg:	AA10 satin anodised aluminium pedestal leg 150mm high allowing 30mm adjustability for uneven / sloping floors.
Coat Hook:	Single aluminium coat hook with rubber safety buffer.
Panel Fixings:	Aluminium 'U' and angle bracket fixings for securing panels to each other and to walls. Minimum of 3 to each vertical panel. Tamper proof fixings are available as an alternative to the standard.
Sizes:	Cubicle sizes are tailored to suit your individual requirements. However, standard overall cubicle height is 1950mm which includes 150mm adjustable leg, cubicle width 750-1000mm.
Accessories:	Optional extra: Modesty panels, special fittings for disabled, baby change, standard supply toilet roll holder. As well as cubicles the Sublime range includes co-ordinated options for Vanity Units, Wall Linings and Ducting. A wide variety of alternative hardware is available for special applications.
Finish/Colour:	Doors and Panels: Extensive colour choice from any major laminate supplier in large sheet size. Top rail/Hardware/Door Furniture - AA10 satin anodised aluminium requiring minimum maintenance. Polyester powder coating with stainless or brass finish is an optional extra.
Seating:	Changing cubicles include optional cantilever seat or standard seat bracket. Seats are made of melamine faced particle board with a 2mm ABS edge, with solid grade laminate and wood as options.
Installation:	Helmsman offers a full installation service for its products.

HELMSMAN also provide an extensive range of lockers and changing room furniture.

After-sales Service: All of our products are supported by the Helmsman Service team who provide technical advice, maintenance schemes, prompt delivery of replacement keys/parts and product refurbishment. Contact them on 01284 727633 or email service@helmsman.co.uk

- Health & Safety: Lockers must be firmly secured to wall or floor and fixed together in runs for safety purposes. If applicable, install in accordance with specific product instructions.
- All dimensions are nominal.
- To enable us to interpret your requirements accurately, please state at time of enquiry/order the choice of locker type, colour, locking and nesting arrangement and delivery requirement.
- The products described in this specification sheet herein are the subjects of patent, trademark, design and copyright protection or application thereof.
- In the interest of efficiency and service to our customers, the company reserves the right to modify the specifications of any of its products.

