

## NBS SPECIFICATION

### L20 DOORS/ SHUTTERS/ HATCHES

#### 530 SLIDING FOLDING EXTERNAL DOORS

- **Manufacturer:** Becker (Sliding Partitions) Ltd  
Wemco House,  
477 Whippendell Road  
Watford, Herts, WD18 7QY  
Tel: 01923 236906  
Telefax:01923 230149  
Email: [sales@becker.uk.com](mailto:sales@becker.uk.com)  
[www.becker.uk.com](http://www.becker.uk.com)
- **Product reference:** Sunflex Sliding Folding Doors  
Becker supply a wide range of fully glazed sliding partitions, for internal and external applications.
- **SF45 Non-Thermal Aluminium**  
Designed for internal and external applications with the strength and ability to be used for commercial applications.
- **SF65 Laminated Timber**  
Comprises laminated sections for strength and stability, and available in a choice of timber types.
- **SF70 Thermally Broken Aluminium**  
Includes a polyamide thermal break to combat heat loss and condensation.
- **SF80 Timber/Aluminium**  
Comprises aluminium external and timber internal components.
- **SF99/155:** Thermally broken aluminium.  
A straight sliding system offering the maximum area of glazing.
- **System:** Purpose made sliding/folding and straight sliding partitions to suit a wide range of external and internal applications.
- **Construction:** The door running mechanism consists of tough polyamide wheels encasing maintenance free sealed bearings, ensuring smooth operation and a long life. The systems are available severe weather rated and can be inward or outward opening, with a wide range of opening variations. A high security locking system is fitted, together with finger safe gaskets. A choice of threshold options is available, including a flush threshold. The doors can be positioned to open-up corners and radius curves are possible. Venetian blinds can be incorporated within the double glazed units.  
All Sunflex sliding folding doors are custom made to individual requirements.
- **Operation:** Manual.
- **Acoustic:** Dependant on performance of glazing.
- **Track system:** Top hung with floor guide or floor supported with top guide. Flush floor track option available.

- **Parking:** Panels park to one or both sides of opening, parked panels to project internally or externally as required.
- **Finish:** Satin anodized aluminium or a selection from our standard RAL range. Range of Sikkens colours available for timber systems.
- **Size:** .... mm wide x ..... mm high (to be site checked before manufacture)
- **Installation:** Becker provide survey, drawings and installation to openings fully prepared by others.