

### Tremproof 250 GC

- Cold-applied fully bonded membrane
- Highly elastomeric - excellent crack bridging performance
- Rapid curing - can be overlaid in as little as 4 hours



#### APPLICATION

Supermarket parking deck above basement car park

#### SURFACE

Block paving

#### SPECIFICATION

Tremproof 250 GC-SL @ 3 kg/m<sup>2</sup>  
Tremco Dualflex / Dualflex Drain  
Tremco VCL 3 Protection Course  
Tremco Drainage Mat 4250

#### CONTRACTOR

Cemplas

#### AREA

2,500 m<sup>2</sup>

#### PROJECT DESCRIPTION

The Tremproof 250 GC system was selected as the waterproofing system for the refurbishment of a covered basement car park in a busy retail area. The membrane was installed directly onto the existing slab, prior to the installation of block paving throughout.

Specialist contractor Cemplas was awarded the waterproofing element of the contract, and Tremproof 250 GC was selected as the waterproofing system. Prior to the installation of the membrane, extensive detailing was carried out using Tremco's Dualflex and Dualflex Drain. With joints, drains and vertical junctions reinforced, Tremproof 250 GC was then applied directly onto the slab.

Once installed, the membrane was covered with Tremco VCL 3 Protection Course and Tremco Drainage Mat. This protection system ensures the membrane was protected not only for the duration of the works, but for the working life of the structure.

# TREMCO