

Paracoat Acrylic Coating

WATERPROOFING COATING FOR ROOFS, GUTTERS & SIMILAR STRUCTURES

Description

Paracoat Acrylic Coating is a cost effective, single pack, fibre reinforced, acrylic based, waterproofing coating for roofs, gutters and similar structures.

It can be applied in damp conditions and is ideal for use in emergency repairs to leaking roofs as well as routine maintenance or an overall roof treatment.

This thixotropic coating is applied by brush, trowel or roller and dries to form a tough, durable waterproof film.

Use

Paracoat Acrylic Coating is suitable for use on most conventional roofing systems including bitumen felts, asphalt, asbestos cement sheets, concrete and metal.

- Instant remedy for leaking roofs and gutters
- Can be applied in wet conditions
- Bonds to most roofing materials
- Ideal for roof repairs
- Suitable for use on asbestos cement sheets

Typical Properties

Base:	Acrylic	Solids:	Approx. 70%
Viscosity:	Thixotropic	Specific Gravity:	1.2
Colour:	Grey		

Physical Characteristics

Coverage:	10m ² per 20kg tin, approx coverage (2kg per m ²)
Application Limits:	+5 to + 40°C
Curing Time:	3 days (likely to be touch dry in 4 hours depending on temperature and humidity).
Cleaner:	White Spirit.

Quantities

Drum: 20 kg.

General Application Method

All surfaces to be treated must be sound and free from dust, rust, chippings and other loose material.

Any organic growth must be removed and the area treated with Paracoat Biocidal Wash.

Any surface water must be swept away and best results will be obtained when the substrate is dry.

Metal and very porous substrates (such as asbestos cement sheets) should be primed as follows:

- Metal: **Paracoat Epoxy Primer**
- Porous substrates: **Paracoat PU Primer**

Paracoat Acrylic Coating is applied in one or two coats as required to meet coverage rate, with a brush, roller or trowel. First coat to be dry before application of second coat.

Leaking holes, gaps or joints should be bridged and reinforced by embedding a suitable polyester or glass fibre woven fleece between two coats of **Paracoat Acrylic Coating** making sure all air bubbles and voids are removed by “stippling in” with a paint brush.

Contact Langley Waterproofing Systems Ltd for detailed specifications and fixing instructions.

Storage

Store in a cool dry place away from sunlight.

Shelf Life: 6 months (when stored between 5 and 25°C in unopened containers)

Safety

See Langley Safety Data Sheet.

This document is only a guide. Langley Waterproofing Systems Ltd reserves the right to change the composition and fixing recommendations of products as a result of the evolution of knowledge and technology.

Langley Waterproofing Systems Ltd

Bishop Crewe House, North Street, Daventry, Northants, NN11 4GH

Tel: (01327) 704778 Sales: (01327) 708990 Fax: (01327) 704845

E-mail: enquiries@langley.co.uk

Website: www.langley.co.uk