

Product Datasheet

Euroroof Mastergold Underlay

Sheet No: PD012FR

Issued: May 2012

Pages: 1 of 1

Description

Euroroof Mastergold Underlay is an APP modified, polyester reinforced, high performance bitumen base layer, with a sanded upper face and a thermofusible film to its underside.

Use

For use as a base layer in traditional built-up roofing systems, in both new construction and refurbishment projects.

Approvals

None applicable.

Application

Fully bonded by torch application with 4 Bar propane gas torch equipment.

Laps are sealed by torch application.

Lap sizes: 100mm side, 150mm end

Storage

Store upright in a clean, dry location, away from heat sources.

Product Data

Thickness	3mm
Width	1.0m
Length	10.0m
Weight	3.3kg/m ²
Weight per roll	33kg

Health & Safety

Material Safety Data Sheets are available upon request, and can also be downloaded directly from www.alumascwaterproofing.co.uk

Technical Support

Technical advice is available from Alumasc Technical Services at:

Telephone: +44 (0)1744 648400

Facsimile: +44 (0)1744 648401

Email: waterproofing@alumasc-exteriors.co.uk

The company pursues a policy of constant product development and information contained in this publication is therefore subject to change without notice. The customer is responsible for ensuring that each product is fit for its intended purpose and that the conditions for use are suitable. All quoted data is nominal and subject to production tolerances.