

Product Datasheet

Derbipaint E

Sheet No: PD405FR

Issued: May 2012

Pages: 1 of 1

Description

Derbipaint E is a two-coat water based matt acrylic paint, available in 5 colours: RAL 6026 (Green), RAL7037 (Medium Grey), RAL8023 (Terracotta), RAL9017 (Black) and RAL7035 (Light Grey).

Use

For use as an aesthetic surfacing on suitably prepared new or existing bituminous membranes, on roofs with 1:80 fall or better. Do not use where ponding water is anticipated.

Application

Minimum application temperature 5°C. Stir well before use, until smooth. Apply by brush, roller or airless spray, in two coats. Allow 12-24 hours between coats depending on conditions. Clean equipment immediately after use with water.

Coverage

On new Derbigum or other smooth bituminous membrane:
5m²/l/coat

On old mineral surfaced or sanded bituminous membranes:
1st coat (diluted with 20% water) 3.5m²/l/coat.
2nd coat (not diluted) 3.5m²/l/coat

Product Data

Packaging	Drums:10 and 20litre
Storage	Store in a frost free area. Keep in airtight drums.
Flash Point	Not applicable
Shelf-life	2 years in airtight drums
Density	1.1kg/litre

Health & Safety

Material Safety Data Sheets are available upon request, and can also be downloaded directly from www.alumascwaterproofing.co.uk

Technical Support

Technical advice is available from Alumasc Technical Services at:

Telephone: +44 (0)1744 648400
Facsimile: +44 (0)1744 648401
Email: waterproofing@alumasc-exteriors.co.uk

The company pursues a policy of constant product development and information contained in this publication is therefore subject to change without notice. The customer is responsible for ensuring that each product is fit for its intended purpose and that the conditions for use are suitable. All quoted data is nominal and subject to production tolerances.