

# record R 62

Security Interlock as Access Control System



record R 62



**record**

your global partner for entrance solutions

# record R 62

## Security Interlock as Access Control System

The record R62 security interlock provides pedestrian traffic separation with a range of security levels. The interplay between cutting edge technology and proven engineering techniques enables safe, secure access control for vulnerable and specially protected areas such as can be found in banks, airports and other sensitive applications.

### Protection and Security

The control logic of the record R62 is based on the record FlipFlow, an interlock designed to control the flow of people that has been in operation in hundreds of airports worldwide for many years. For this reason, it follows that the design and development of the record R62 are closely connected to this product family to take advantage of synergies in design and development, and to maintain a uniform layout for operation and maintenance.

The record R62 is basically modular in design with customizable security levels. It can be used as a pure interlock, but also provides the ability to control access with the highest reliability via contact mats or a 3D camera. These measures prevent so-called tailgating and piggybacking.

The operating status of the door together with many other parameters can be reported to a building management system for which up to 16 relay outputs are optionally available.

### Versions

We provide the record R62 in three passage widths of 600mm, 900mm and 1100mm; the two larger versions are suitable for wheelchairs. As far as the design is concerned, we provide you with a wide range of possibilities to enable the interlock

### Technical Specifications

Width of passage A	600mm	900mm	1100mm
Outer diameter Q			
8 mm single glazing	1 035 mm	1 455 mm	1 735 mm
19 mm double glazing	1 090 mm	1 510 mm	1 790 mm
Height of passage G	2 100 – 3 000 mm	2 100 – 3 000 mm	2 100 – 3 000 mm
G with 3D camera	2 200 – 3 000 mm	2 200 – 3 000 mm	2 200 – 3 000 mm
Cover height	220 – 1 000 mm	220 – 1 000 mm	220 – 1 000 mm
Overall height	min. 2 420 mm	min. 2 420 mm	min. 2 420 mm
Wheelchair accessible <sup>1)</sup>	–	●	●
Security level			
Low (without sensor; interlock function)	●	●	●
Middle <sup>2)</sup> (pressure contact mats; anti-tailgating)	●	●	●
High (3D camera; anti-tailgating + anti-piggybacking)	●	●	●

1) local regulations may vary, 2) assembly not possible on finished floors

to fit harmoniously into the overall architectural picture. Optically open and light in the form of a glass construction, or opaque. With regard to the surface finish of all metal parts, you can choose from anodizing or powder coating in any RAL colour. The outer casing is also available in stainless steel.

All components are fully integrated into the cover, safe and secure against unauthorized access. No external control cabinets are needed, which also simplifies embedding it into existing security systems. Installation is performed on a recessed floor ring or on the finished floor itself.

### Benefits at a Glance

- Covers a variety of security levels
- Anti-tailgating monitoring
- Anti-piggybacking monitoring
- Fully integrated components. No external panels required.
- Low hood height of 220 mm enables use even when space is limited
- Installation requires only minor structural work
- Suitable for indoor and outdoor applications
- Wheelchair versions available
- Anodizing, powder coating and stainless steel finishes available
- Easy accessibility of individual components during maintenance
- Can be connected to building management systems







# record R62

## Drawings

Elevation



Horizontal section



Vertical cross section



## Contact

→ record UK limited

Head Office: Unit D, 9 Watt Place – Hamilton International Park – Blantyre – G72 0AH – UK  
 Central Office: 450a Bradford Road – Batley – WF17 5LW – UK  
 Southern Office: 17 Invincible Road – Farnborough – GU14 7QU – UK  
 tel.: +44 1698 376411 – fax: +44 1698 376422 – info@recorduk.co.uk – www.recorduk.co.uk

→ record global export

agtatec ag – Allmendstrasse 24 – 8320 Fehrltorf – Switzerland  
 tel.: +41 44 954 91 91 – e-mail: international@record.global – www.record.global

→ Headquarters

agta record ltd – Allmendstrasse 24 – 8320 Fehrltorf – Switzerland  
 tel.: +41 44 954 91 91 – e-mail: info@record.global – www.record.global

