


AGGREGATE INDUSTRIES

Landscaping

Charcon Andover Washed block paving



Premium washed block for prestigious schemes.

- Pale, understated colour creates a contemporary backdrop to either modern or traditional projects
- Can be used to create different patterning effects in adjacent areas while retaining overall texture and colour consistency
- Guaranteed minimum 52% recycled material in the back mix
- Available as an Infiltra concrete block permeable paver (CBPP)
- Pencil chamfer profile creates a smoother riding surface
- Available in long aspect paving for a versatile contemporary look
- Semi dry manufacturing process then washed
- Andover steps also available within the range.

Applications

Andover washed block paving is suitable for prestigious pedestrian areas and building developments including town centres and shopping precincts. Refer to our technical department for further guidance on suitability for given applications. For correct choice of block thickness to suit your application, refer to BS7533 Part 1 and 7.

Manufacturing standard

Andover Washed block paving is manufactured using a semi-dry process and is manufactured in accordance with and complies with all relevant sections of BS EN 1338: Precast Concrete Block Paving – requirements and test methods.

Aggregate Industries fully operates an accredited Quality Assurance scheme, certified to BS EN 9001:2008 which is independently and regularly assessed by BSI (British Standards Institution). All Charcon manufacturing sites are also certified to BS EN 14001 Environmental Management Systems.


Performance with slip resistance

Unpolished slip resistance values, when tested in accordance with BS EN 1338, are available on request. All Aggregate Industries block paving is classified as having a low potential for slip i.e. a USRV of greater than 40.


Polished slip resistance values can be provided on request.

Complementary products

Complements Andover Textured block paving plus Malvern flag paving and Countryside Classic kerbs. Made to order Andover washed steps also available.



Colour swatches



1. Silver Grey
2. Anthracite Charcoal

† Represents non-primary material within the complete mix design.

Andover Washed block paving

Size (mm)	600x200	300x300	300x200	200x200	200x100	100x100
Thickness (mm)	80	80	80	80	80	80
Weight (kg)	21	16.5	11.0	7.3	3.8	1.7
Units/m ² (approx)	8.33	11.11	17	25	50	100
No. per pack	36	54	108	160	320	560
M ² /pack	4.32	4.86	6.46	6.40	6.40	5.60
Pack weight (T)	0.76	0.89	1.18	1.17	1.16	1.00
Colour available	Sg*, Ac*	Sg*, Ac*	Sg, Ac*	Sg, Ac*	Sg, Ac*	Sg, Ac*

Sg - Silver Grey / Ac - Anthracite Charcoal

*Made to order.

Andover Washed block paving comes banded and shrink-wrapped to a pallet.

Available as an Infiltra concrete block permeable paver (CBPP) in 200x100x80 on MTO basis.

Andover Washed complete step and tread unit available MTO in Silver Grey and Anthracite Charcoal.



Q24. For NBS clauses, refer to Aggregate Industries technical services

Charcon Andover Washed block paving

Sustainability and local sourcing

Energy use: Aggregate Industries is at the forefront of sustainability and has committed to reduce carbon emissions by 20% by 2016 based on a 2012 base line.

Recyclable: 100% of the product can be recycled thus reducing the amount of material that is sent to landfill.

Manufacturing location: produced in the UK, with locally sourced materials under strict environmental and social legislation, for local supply.

Responsible sourcing: Aggregate Industries is the first company in the world to achieve accreditation to the BES 6001 Framework Standard for the Responsible Sourcing of Construction Products. Aggregate Industries has achieved an 'Excellent' rating for major product groups. The BES 6001 standard assesses:

- quality management
- environmental management
- health and safety management
- a range of social and environmental issues.

Life

Life is our range of sustainable products and services. For more information please visit www.aggregate.com/life

Key aggregates and recycled content

Andover Washed is manufactured from specially selected granite aggregates with a minimum of 52% recycled material in the back mix. It is made in a semi-dry process and the face surface is then washed.

Generic green guide rating*

Concrete Block Pavers, CBP (80mm) over prepared recycled sub-base - **A rated**.

Concrete Block Pavers, CBP (80mm) over prepared sub-base - **B rated**.

Policies

Aggregate Industries' policies on the environment and community, health and safety and sustainable solutions for different product applications can be viewed on our website www.aggregate.com

Design and installation

For pavement design guidance refer to BS 7533 Parts 1 and 7. For successful installation refer to BS 7533 Part 3. For specific design, installation and maintenance guidance, please contact our technical department on 01335 372222.

Maintenance and cleaning

After laying light coloured paving on site, care should be taken to protect from dirt and detritus while the remaining construction works are completed.

Aggregate Industries can supply on request advice on specific stain removal and general maintenance, suitable cleaning products and referrals to specialist cleaning companies.

COSHH data

Full COSHH data on the Charcon range of products is available on request. Please call the technical helpline on 01335 372222.

Technical support

Detailed guidance and assistance with the preparation of specification of the Charcon range of hard landscaping products, including model clauses, is available through the sales office. A free technical design service is also available.

For further information, please refer to our technical services on 01335 372222.

*Ratings based upon generic green guide values (2009) supplied by BRE Global Ltd, www.thegreenguide.co.uk

Hulland Ward, Ashbourne,
Derbyshire DE6 3ET

Tel: 01335 372222

Fax: 01335 370074

www.aggregate.com



The information contained within this publication was accurate at time of production. However, Aggregate Industries reserves the right to introduce modifications or changes to detail at any time without notice. No charge is levied for this publication or advice therein, and accordingly the company, its employees and authorised agents can accept no liability whatsoever, either indirectly or directly arising from the use of its products in connection with any information or advice contained in this guide.